

FARWEST PAINT MFG CO -- SPAR VARNISH -- 8010-00-597-7856

===== Product Identification =====

Product ID:SPAR VARNISH

MSDS Date:02/01/1998

FSC:8010

NIIN:00-597-7856

MSDS Number: CHXRV

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:SEATTLE

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-244-8844

CAGE:6F266

=== C

Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 37.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM; 9495

Ingred Name:GLYCOL ETHER EP

CAS:2807-30-9

RTECS #:KM2800000

Fraction by Wt: 4.6%

Other REC Li

mits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: IRRITATION, SENSITIZATION,
DEFATTING; INHALE: HEADACHE, DIZZINESS, NAUSEA, LOSS OF
CONSCIOUSNESS, POSSIBLE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE;
EYES: IRRITANT
Effects of Overexposure:ASPIRATION CAN CAUSE CHEMICAL PNEUMONITIS
Medical Cond Ag
gravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER; REMOVE AND WASH ANY
CONTAM CLOTHING BEFORE REUSE. EYES: FLUSH WITH LARGE QUANTITIES OF
WATER FOR 15 MINUTES; GET MED AID. INGEST: DO NOT INDUCE VOMITING;
KEE P PERSON WARM AND QUIET; GET MED AID. INHALE: REMOVE TO FRESH
AIR IMMED; GET MED AID AT ONCE.

=====
===== Fire Fighting Measures =====

Flash Point
Method:TCC
Flash Point:104F,40C
Autoignition Temp:Autoignition Temp Text:NONE
Lower Limits:1
Upper Limits:7
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG, AND ANY
CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE; USE TO COOL
CONTA
Fire Fighting Procedures:WEAR SCUBA; EVACUATE AREA, WEAR PROTECTIVE
CLOTHING
Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN
AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED
CONTAINERS MAY RUPTURE W
HEN EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION; VENTILLATE
AREA; ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST,
VERMICULITE, OR SAND AND PLACE MATERIAL INTO CLOSED CONTAINER. IF
LARGE SPILL: DIKE - PREVENT FROM ENTERING WATER SYSTEMS OR
SEWERS;PROT EQUIP

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID

ALL UNNECESSARY CONTACT WITH
THIS MATERIAL; KEEP AWAY FROM IGNITABLES; DO NOT WELD ON FULL OR
EMPTY CONTAINERS; KEEP CONTAINERS CLOSED ; LABEL

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANNISTER TYPE RESPIRATOR IS REQUIRED
Ventilation:GENERAL VENTILATION IS REQUIRED FOR NORMAL USE; LOCAL
VENTILATION MAY BE REQUIRED MAY BE REQUIRED SOMETIMES
Protective Gloves:CHEM RESIST NITRILE, NEOPRENE, RUBBER
Eye Protection:FACE SHIELD; CHEM GOGG
LES
Other Protective Equipment:PROTECTIVE CLOTHING, EYEWASH STATION, SAFETY
SHOWER
Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:282F,139C
Vapor Pres:6
Vapor Density:>1 AIR=1
VOC Pounds/Gallon:388
Evaporation Rate & Reference: