View NSN Online: https://aerobasegroup.kr/nsn/6810-00-264-8955

CAMLAUR SCIENTIFIC -- ACETONE -- 6810-00-264-8955

============ Product Identification =========================

Product ID:ACETONE MSDS Date:02/10/1999

FSC:6810

NIIN:00-264-8955

Status Code:A

MSDS Number: CJDXW === Responsible Party ===

Company Name: CAMLAUR SCIENTIFIC

Address:4820 SPANISH TRAIL

City:HOUSTON

State:TX ZIP:77221 Country:US

Info Phone Num:281-343-0364

Emergency Phone Num:213-516-8000

CAGE:TO062 === Contractor I dentification ===

Company Name: CAMLAUR SCIENTIFIC

Address:4820 SPANISH TRAIL

Box:City:HOUSTON

State:TX ZIP:77221 Country:US

Phone:281-343-0364

CAGE:TO062

Company Name: LOS ANGELES CHEMICAL CO

Address:4545 ARDINE ST

Box:1987

City:SOUTH GATE

State:CA ZIP:90280 Country:US

Phone:213-562-9500

Contract Num:SP0450-99-M-C379

CAGE:75656

====== Composition/Information on Ingredients ========

Ingred Name: ACETONE (SARA 313) (CERCLA)

CAS:67-64-1

RTECS #:AL3150000

= Wt:100.

Other REC Limits: NON

E RECOMMENDED OSHA PEL:1000 PPM

ACGIH TLV:750PPM/1000STEL;9596

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

========== Hazards Identification ==============

LD50 LC50 Mixture:LD50 (ORAL, RAT) 5,800 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS: BLOOD, LIVER, KIDNEYS, LUNGS. THE NERVOUS SYSTEM, MUCOUS MEMBRANES. ACUTE- SLIGHTLY DANGEROUS TO DANGEROUS IN

CASE OF SKIN CONTACT (PERMEABLE), OF EYE

CONTACT (IRRITANT), OF INGESTION, OF INHALATION. VERY SLIGHTLY TO SLIGHTLYDANGEROUS IN CASE OF SKIN CONTACT (IRRITANT, SENSITIZER). THIS PRODUCT MAY IRRITATE EYES AND SKIN UPON CONTACT. CHRONIC- THE SUBSTANCE IS TOXIC TO BLOOD, KIDNE YS, LUNGS, THE NERVOUS SYSTEM, LIVER, MUCOUS MEMBRANES. REPEATED OR PROLONGED EXPOSURE TO THE SUBSTANCE CAN PRODUCE TARGET ORGANS DAMAGE.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGR EDIENTS AT

CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:UPPER RESPIRATORY TRACT IRRITATION, WEAKNESS OF THE LEGS, HEADACHE, DIZZINESS, DROWSINESS, NAUSEA, MALAISE, INCOORDINATION, SKIN IRRITATION, DEFATTING, STINGING SENSATION IN EYES, FRUITY ODOR OF THE B REATH, RESTLESSNESS, DIARRHEA, NAUSEA, VOMITING, HEMATEMESIS, COLLAPSE

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROB

LEMS OR IMPAIRED LIVER, KIDNEY OR RESPIRATORY
FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. RINSE WITH PLENTY OF WATER OR UNDER SHOWER. IF IRRITATION PERSISTS, GET MED ICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTI

ON. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK SEVERAL GLASSES OF WATER OR MILK. SEEK IMMEDIATE MEDIC AL ATTENTION.
======================================
Flash Point Method:CC Flash Point:=-20.C, -4.F Autoignition Temp:=465.C, 869.F Lower Limits:2.6 % Upper Limits:12.8% Extinguishing Media:SMALL FIRE: USE DRY CHEMICALS, CARBON DIOXIDE, WATER SPRAY, ALCOHOL FOAM. LARGE FIRE: USE ALCOHOL FOAM, WATER SPRAY OR FOG. Fire Fighting Procedures :WEAR FULL PROTECTIVE CLOTHING, INCLUDING HELMET AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND CAN TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CAN FORM MAY FORM CARBON MONOXIDE, CARBON DIOXIDE.
========== Accidental Release Measures ===========
Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. EVACUATE AR EA.  WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT. VENTILATE AREA. DILUTE WITH WATER AND MOP UP OR ABSORB WITH INERT, NON-FLAMMABLE DRY MATERIAL AND PLACE IN AN A PPROPRIATE WASTE DISPOSAL CONTAINER. Neutralizing Agent:DILUTE WITH WATER
=========== Handling and Storage ============
Handling and Storage Precautions:FLAMMABLE MATERIAL SHOULD BE STORED IN A SEPARATE SAFETY STORAGE CABINET OR ROOM. KEEP AWAY FROM HEAT, SOURCES OF IGNITION IN A COOL, WELL-VENTI LATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. GROUND ALL E QUIPM, ENTS CONTAINING THIS MATERIAL.
Other Precautions:AVOID CONTACT WITH HEAT, SPARKS, FLAMES OR OTHER SOURCES OF IGNITION. VAPORS MAY BE EXPLOASIVE. DO NOT ALLOW UNNECESSARY PERSONNEL IN AREA. DO NOT OVERHEAT CONTAINERS.

C CONTAINERS MAY VIOLENTLY RUPTURE IN FIRE. A REFRIGERATED ROOM WOULD BE PREFERABLE FOR MATERIALS WITH A FLASH POINT LOWER THAN 37.8C (100F)

====== Exposure Controls/Personal Protecti

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: DISPOSABLE VINYL

Eye Protection: SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment: PROTECTIVE CLOTHING AS

REQUIRED TO AVOID

SKIN CONTACT. BE SURE THAT EYE WASH STATION AND SAFETY SHOWER IS PROXIMAL TO THE WORK-STATION LOCATION.

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

======== Physical/Chemical Properties ============

HCC:F2

Boiling Pt:=56.2C, 133.2F

Melt/Freeze Pt:=-95.4C, -139.7F

Vapor Pres:186.2 MM OF HG @ 20 DEG C

Vapo

r Density:2 (AIR=1)

Spec Gravity:0.79 (WATER=1) Viscosity:NOT RELEVANT

Solubility in Water: VERY SOLUBLE Percent Volatiles by Volume: 100 %

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

NO SPECIFIC INFORMATION IS AVAILABLE REGARDING THE REACTIVITY OF THIS MATERIAL IN PRESENCE OF VARIOUS OTHER MATERIALS.

Stability Condition to Avoid:HEAT, OPEN FLAME, IGNITION SOURCES, STATIC ELECTRICITY, SPARKS

Hazardous Decomposition Produc

ts:CARBON MONOXIDE, CARBON DIOXIDE
======== Toxicological Information =========
Toxicological Information: ACUTE DERMAL TOXICITY (LD50): 20000 MG/KG (RABBIT). ACUTE TOXICITY OF THE VAPOR (LC50): 29853 PPM (RAT).
======== Ecological Information ==========
Ecological:NOT EXPECTED TO BE TOXIC TO EQUATIC LIFE. LC50/96 HOUR VALUES FOR FISH ARE OVER 100 MG/L.
======= Disposal Considerations ==========
Waste Disposal Methods:DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. RECYCLE IF POSSIBLE OR BURN FOR ENERGY RECOVERY.
========= Regulatory Information ===========
State Regulatory Information:LISTED BY PENNSYLVANIA AND MASSACHUSETTS

State Regulatory Illionnation. Elone Bill Elvidor Evitablian (1900) illionnation.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.