

RUST-OLEUM CORP -- AEROSOL SPRAY PAINT, 2143 -- 8010-01-177-0797
===== Product Identification =====

Product ID:AEROSOL SPRAY PAINT, 2143

MSDS Date:03/04/1994

FSC:8010

NIIN:01-177-0797

Status Code:A

MSDS Number: CJFGD

=== Responsible Party ===

Company Name:RUST-OLEUM CORP

Address:11 HAWTHORNE PKWY

City:VERNON HILLS

State:IL

ZIP:60061

Country:US

Info Phone Num:708-367-7700

Emergency Phone Num:708-3

67-7700

CAGE:08882

=== Contractor Identification ===

Company Name:RUST-OLEUM CORP

Address:11 HAWTHORN PARKWAY

Box:City:VERNON HILLS

State:IL

ZIP:60061-1583

Country:US

Phone:847-367-7700

CAGE:08882

===== Composition/Information on Ingredients =====

Ingred Name:N-PROPANOL; VP: 14.9MMHG @ 20C; LEL: 2.1%

CAS:71-23-8

RTECS #:UH8125000

= Wt:1.

Other REC Limits:N/K

OSHA PEL:500 MG/M3;200 PPM

OSHA STEL:N/K

ACGIH TLV:492 MG/M3;200 PPM

ACGIH STEL:614 MG/M3;250 PPM

Ingred Name:PETR

OLEUM GASES, LIQUEFIED, SWEETENED; (PROPELLANT
(PROPANE, BUTANE, ISOBUTANE)) VP: 85 PSI @ 20C; LEL: 1.8%
CAS:68476-86-8
= Wt:25.
Other REC Limits:N/K
OSHA PEL:1000 PPM
OSHA STEL:N/K
ACGIH TLV:1000 PPM
ACGIH STEL:N/K

Ingred Name:XYLENE; VP: 9.5MMHG @ 20C; LEL: 1.2%
CAS:1330-20-7
RTECS #:ZE2100000
Minumum % Wt:15.
Maxumum % Wt:30.
Other REC Limits:N/K
OSHA PEL:100 PPM
OSHA STEL:N/K
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:651 MG/M3;150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ing
red Name:TOLUENE; VP: 22.0MMHG @ 20C; LEL: 1.2%
CAS:108-88-3
RTECS #:XS5250000
Minumum % Wt:10.
Maxumum % Wt:25.
Other REC Limits:N/K
OSHA PEL:100 PPM
OSHA STEL:N/K
ACGIH TLV:188 MG/M3;50 PPM
ACGIH STEL:N/K
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM); (VM&P
NAPHTHA) VP: 2.0MMHG @ 20C; LEL: 0.9%
CAS:64742-89-8
Minumum % Wt:0.
Maxumum % Wt:5.
Other REC Limits:N/K
OSHA PEL:300 PPM
OSHA STEL:N/K
ACGIH TLV:300 PPM
ACGIH STEL:N/K

I

ingred Name:2-BUTOXYETHANOL; VP: 0.9MMHG @ 20C; LEL: 1.1%
CAS:111-76-2
RTECS #:KJ8575000
Minumum % Wt:0.
Maxumum % Wt:10.
Other REC Limits:N/K
OSHA PEL:240 MG/M3;50 PPM
OSHA STEL:N/K
ACGIH TLV:121 MG/M3;25 PPM
ACGIH STEL:N/K

Ingred Name:METHYL ETHYL KETONE; VP: 70.0MMHG @ 20C; LEL: 2.0%
CAS:78-93-3
RTECS #:EL6475000
Minumum % Wt:0.
Maxumum % Wt:3.
Other REC Limits:N/K
OSHA PEL:590 MG/M3;200 PPM
OSHA STEL:N/K
ACGIH TLV:590 MG/M3;200 PPM
ACGIH STEL:885 MG/M3;300 PPM
EPA Rpt Qty:5000 LBS
D
OT Rpt Qty:5000 LBS

Ingred Name:ETHYLBENZENE; VP: 10.0MMHG @ 20C; LEL: 1.2%
CAS:100-41-4
RTECS #:DA0700000
Minumum % Wt:1.
Maxumum % Wt:4.
Other REC Limits:N/K
OSHA PEL:435 MG/M3;100 PPM
OSHA STEL:N/K
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:543 MG/M3;125 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcino

genicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHAL: HARMFUL IF INHALED. MAY AFFECT BRAIN & NERV SYS CAUSING DIZZ, HDCH/NAUS. RPTD OVEREXP MAY PROGRESSIVELY LEAD TO STAG GAIT, CONFUSION, UNCON/COMA. CAUSES NOSE & THROAT IRRIT. SKIN/EYE S: CAUSES EYE & SKIN IRRIT WHICH CAN LEAD TO DERM W/RPTD OVEREXP. INGEST: MAY CAUSE GI IRRIT, NAUS, VOMIT & DIARR. CHRONIC: RPTS HAVE ASSOC RPTD & PRLNG OCCUP OVEREXP TO SOLVS W/PERM BRAIN & NERV SY S DMG.

OVEREXP TO XYLENE & TOLUENE

IN LAB ANIMALS HAS BEEN ASSOC W/LIVER, KIDNEY, LUNG, SPLEEN & EYE DMG AS WELL AS ANEMIA. EFTS IN HUMANS HAVE INCLUDED LIVER & CARD ABNORMS. (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ: 2-BUTOXYETHANOL MAY BE HARMFUL IF ABSORBED THRU SKIN & HAS BEEN SHOWN TO CAUSE BLOOD ABNORMS IN LAB ANIMALS. TOLUENE APPEARS ON THE NAVY OCCUP CHEM REPRO HAZ LIST. SEEK CONSULTATION FROM A PPROP HLTH PROFE

SSIONALS CONCERNING LATEST

HAZ LIST INFO & SAFE HNDLG & EXPOS INFO . ANIMAL STUDIES CLEARLY DEMONSTRATED DOSE-RELATED ADVERSE EFTS ON THE CNS, HEMATOPOIETIC TISS, BLOOD, KIDNEYS , & LIVER, ASSOC W/ADMIN OF 2-BUTOXYETHANOL (EXTRACTED FROM DHHS (NIOSH) PUBLICATION #90-118) .

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE, RESTORE BREATHING AND

NOTIFY A PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. NOTIFY A PHYSICIAN. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION. ASPIRATION OF THIS MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

=====
===== Fire Fighting Measures =====

Fla
sh Point Method:TCC
Flash Point: