

FARWEST PAINT MFG CO -- WHITE STENCIL PAINT COLOR #37875 -- 8010-00-285-4933

=====
Product Identification
=====

Product ID:WHITE STENCIL PAINT COLOR #37875

MSDS Date:03/01/1998

FSC:8010

NIIN:00-285-4933

Status Code:A

MSDS Number: CJGBQ

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8

844

Emergency Phone Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBON (PER MSDS:CAS # 64742-89-8).

Fraction by Wt: 12.12%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM PER MFG

ACGIH TLV:300 PPM PER MFG

Ingred Name:TOLUENE (SARA

III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 2.89%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA, SOLVENT

CAS:8032-32-4

RTECS #:WJ8925000

Fraction by Wt: 11.62%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2900 MG/M3;500 PPM

ACGIH TLV:525 MG/M3;100 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogeni

city:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: PROLONGED/REPEATED CONTACT: MAY

CAUSE IRRITAITON, SENSITIZATION, OR DEFATTING. INHAL:EXCESSIVE

EXPOSURE: MAY LEAD TO HEADACHE, DIZZINESS, NAUSEA, & LOSS OF

CONSCIOUSNESS. SOME REPORTS HAVE ASSOC IATED REPEATED/PROLONGED

OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/ PERMANENT BRAIN & NERVOUS

SYSTEM DAMAGE. EYE: MAY BE EYE IRRITANT.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH

SAFE HAN

DLING INSTRUCTIONS.

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH W/ SOAP & WATER. REMOVE CONTAMINATED

CLOTHING IMMEDIATELY. EYES: FLUSH WITH WATER FOR 15 MINUTES,

LIFTING LIDS TO RINSE ENTIRE EYE. CALL DR IMMED. INGEST: DO NOT

INDUCE VOMITING. K EEP PERSON WARM & QUIET. SEE DR AT ONCE.

ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS

WHICH CAN BE FATAL. INHALATION: REMOVE TO FRESH AIR. IF

RESPIRATORY

SYMPTOMS DEVELOP, SEEK DR AT ONCE.

===== Fire Fighting Measures =====

Flash Point:50.0F,10.0C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,CO2,DRY CHEM,WATER FOG. USE THE ABOVE OR ANY CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE AS EXTINGUISHING MEDIUM, BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL.

Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPO TO VAP/PROD OF COMBUST SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS .EVACUATE

AREA OF UPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE IN AIR & MAY BE IGNITED BY SPARKS/PILOT LIGHT/ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB AREA W/ ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE, OR SAND AND PLACE MATERIAL INTO

A CLOSED CONTAINER. IF

LARGE SPILL, DIKE AREA TO PREVENT MATERIAL FROM ENTERING WATER SYSTEMS OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING VAPOR/SPRAY MIST. KEEP AWAY FROM HEAT & OPEN FLAME. MATERIAL MAY CAUSE SENSITIZATION. AVOID CONTACT W/ SKIN, EYES, & CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DO NOT WELD ON FULL OR EMPTY CONTNRS.

KEEP CONTNRS CLOSED WHEN NOT IN USE & PROPERLY LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANNISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT INHALATION OF VAPORS OR SPRAY MIST WHEN TLV/PEL IS EXCEEDED.

Ventilation:GENERAL VENTILATION IS REQUIRED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE LEVELS BELOW LIMITS LISTED.

Protective Gloves:NITRILE, NEOPRENE, OR RUBB

ER.

Eye Protection:FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYEWASH STATION & SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=96.1C, 205.F

B.P. Text:205F - 389 F

Vapor Pres:38 MM HG @ 20 C

Vapor Density:>AIR

VOC Pounds/Gallon:390

Viscosity:75-80 KU

Evaporation Rate

& Reference:SLOWER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:WHITE MEDIUM VISCOUS LIQUID WITH A MILD SWEET AROMATIC ODOR.

Percent Volatiles by Volume:51

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDENTS, ACIDS, BASES, AND EPOXY HARDENERS UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid:HEAT SPARKS AND OPEN FLAME. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOS

ED CONTAINERS WILL GENERATE

HYDROGEN GAS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods:IF DISCARDED, MATERIAL & CONTAINER SHOULD BE TREATED AS HAZ WASTE BASED ON CHARACTERISTICS OF IGNITABILITY PER RCRA (40 CFR 261). DISPOSAL OF MATERIAL/CONTAINERS REQUIRES COMPLIANCE W/ APPLICABLE LABE LING, PACKAGING, & RECORD KEEPING STANDAR

DS. DIPOSE IN ACCORDANCE W/ LOCAL/STATE/FED AGENCIES. GROUND HANDLING EQUIPMENT TO PREVENT SPARKS.

===== Regulatory Information =====

SARA Title III Information: THIS MATERIAL HAS BEEN CATEGORIZED AS HAVING THE FOLLOWING HAZARDS AS DEFINED BY SARA TITLE III REGULATIONS (40 CFR 370): ACUTE, FIRE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense

. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.