

FARWEST PAINT MFG CO -- YELLOW STENCIL PAINT 33538 -- 8010-00-285-4935
===== Product Identification =====

Product ID:YELLOW STENCIL PAINT 33538
MSDS Date:03/01/1998
FSC:8010
NIIN:00-285-4935
Status Code:A
MSDS Number: CJGBY
=== Responsible Party ===
Company Name:FARWEST PAINT MFG CO
Address:4522 S 133 ST
Box:68726
City:TUKWILA
State:WA
ZIP:98168-3251
Country:US
Info Phone Num:206-941-1619/206-244-8844
Emergency Phone Num:206-941-1619/206-244-8844
CAGE:6F266
=== Contractor Identification ===
Company Name:FARWEST PAINT MANUFACTURING CO
Address:4522 SOUTH 133RD ST
Box:City:TUKWILA
State:WA
ZIP:98168
Country:US
Phone:206-244-8844
CAGE:6F266
Company Name:GSA WORKFORCE
State:UK
Country:US
CAGE:SO023

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC HYDROCARBON
CAS:64742-89-8
Fraction by Wt: 10.56%
OSHA PEL:500PPM
OSHA STEL:300 PPM

Ingred Name:TOLUENE

CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 3%
OSHA PEL:200 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 12.26%
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:CHROME YELLOW PIGMENT
CAS:1344-37-2
Fraction by Wt: 9.50%

Ingred Name:LEAD (PERCENT WEIGHT OF PIGMENT)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 58%
OSHA PEL:0.05MG/M3
ACGIH TLV:0.15 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CHROMATE (PERCENT WEIGHT OF PIGMENT)
CAS:1333-82-0
Fraction by Wt: 25.50%
OSHA PEL:0.10MG/M3
ACGIH TLV:0.05MG/M3

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: IRRITATION & SENSITIZATION OR
DEFATTING. INHALATION: REPEATED/PROLONGED OVEREXPOSURE TO
VAPORS/SPRAY MISTS MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, AND LOSS

OF CONSCIOUSNESS. SOME REPORTS HAVE ASSOCIATED REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/ PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYES: IRRITANT.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH W/SOAP & WATER. REMOVE & WASH ANY CONTAMINATED CLOTHING BEFORE REUSE. EYES: FLUSH W/LARGE QUANTITIES OF WATER FOR

15 MINS. GET DR. INGESTION: DON'T INDUCE VOMITING.

KEEP PERSON WARM & QUIET. GET DR. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

INHALATION: REMOVE TO FRESH AIR IMMEDIATELY. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:50F

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, WATER FOG, CO2, ANY CLASS B EXTINGUISHING AGENT.

Fire Fighting P

rocedures:WATER MAY BE UNSUITABLE AS EXTINGUISHING

MEDIUM, BUT MAY BE HELPFUL IN KEEPING ADJACENT CONTAINERS COOL.

WEAR SCBA & PROTECTIVE CLOTHING. EVACUATE AREA.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR & MAY BE IGNITED BY SPARKS/PILOT LIGHTS. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES & VENTILATE AREA.

A

BSORB W/ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE/SAND &

PLACE IN A CLOSED CONTAINER. LARGE SPILL: DIKE AREA TO PREVENT

MATERIAL FROM ENTERING WATER SYSTEMS/SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEAN UP.

===== Handling and Storage =====

Other Precautions:AVOID PROLONGED/REPEATED INHALATION OF HEATED VAPORS/SPRAY MISTS. KEEP AWAY FROM HEAT/OPEN FLAMES. MATERIAL MAY CAUSE SENSITIZATION. DON'T GET IN EYES, ON SKIN/CLOTHING. DON'T

ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DON'T WELD ON FULL/EMPTY CONTAINERS. KEEP CONTAINERS CLOSED WHEN NOT IN USE & PROPERLY LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A CANISTER TYPE RESPIRATOR TO PREVENT INHALATION OF VAPORS/SPRAY MISTS WHEN TLV/PEL IS EXCEEDED.
Ventilation:GENERAL EXHAUST DURING NORMAL USE. LOCAL EXHAUST MAY BE REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE 1
VOC Pounds/Gallon:387

Viscosity:75-80KU
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:YELLOW MEDIUM VISCOUS LIQUID W/MILD SWEET AROMATIC ODOR.
Percent Volatiles by Volume:50

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS, ACIDS, BASES, EPOXY HARDENERS.
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES, OTHER IGNITION SOURCES. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS GENERATES HYDROGEN GAS.
Hazardous Decomposition Products:INCOMPLETE COMBUSTION PRODUCES CARBON MONOXIDE AND TOXIC VAPORS

===== Disposal Considerations =====

Waste Disposal Methods:IF DISCARDED THIS MATERIAL AND CONTAINERS SHOULD BE TREATED AS HAZ WASTE BASED ON IGNITIBILITY PER RCRA (40 CFR 361). DISPOSAL OF MATERIAL/CONTAINERS REQUIRES COMPLIANCE W/ APPLICABLE LABELING, PACKAGING, & RECORD KEEPING STANDARDS. DISPOSE OF IN ACCORDANCE W/ FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to t

heir
particular situation.