

FARWEST PAINT MANUFACTURING CO -- BLACK STENCIL PAINT 37038 -- 8010-00-297-2101  
===== Product Identification =====

Product ID:BLACK STENCIL PAINT 37038  
MSDS Date:03/01/1998  
FSC:8010  
NIIN:00-297-2101  
Status Code:A  
MSDS Number: CJGCB  
=== Responsible Party ===  
Company Name:FARWEST PAINT MANUFACTURING CO  
Address:4522 SOUTH 133RD STREET  
City:TUKWILA  
State:WA  
ZIP:98168  
Country:US  
Info Phone Num:206-244  
-8844  
Emergency Phone Num:206-941-1619  
CAGE:2F266  
=== Contractor Identification ===  
Company Name:FARWEST PAINT MANUFACTURING CO  
Address:4522 S 133RD ST  
City:TUKWILA  
State:WA  
ZIP:98168  
Country:US  
Phone:206-244-8844  
CAGE:2F266

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC HYDROCARBON  
CAS:64742-89-8  
Fraction by Wt: 13.98%  
OSHA PEL:500 PPM  
ACGIH TLV:300 PPM

Ingred Name:MINERAL SPIRITS  
CAS:8052-41-3  
Fraction by Wt: 14.11%  
OSHA PEL:300 PPM  
ACGIH TLV:300

PPM

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN: PROLONGED/REPEATED: MAY CAUSE IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN. INHAL:EXCESSIVE EXPOSURE TO VAPORS/SPRAY MISTS CAN LEAD TO HEADACHE, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS. SO ME REPORTS HAVE ASSOCIATED REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/ PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYES: MAY BE EYE IRRITANT.  
Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS.

=====  
===== First Aid Measures =====

First Aid:SKIN:PROMPTLY WASH W/SOAP & WATER. REMOVE CONTAM CLOTHING AND LAUNDRER BEFORE REUSE. EYES: FLUSH W/LRG AMOUNTS OF WATER FOR 15 MINUTES. GET MED AID. INGEST: DONT INDUCE VOMITING. KEEP WARM, QUIET, GET MED AID. ASPIRATION OF MATERIAL INTO LUNGS DUE TO VOMITING CAN CAUSE CHEM PNEUMONITIS WHICH CAN BE FATAL. INHAL: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP, GET MED AID AT ONCE.

=====  
===== Fire Fighting Measures =====

Flash Point:50.0F,10.0C  
Lower Limits:1.2  
Upper Limits:7.0  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG. ANY CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE AS EXTINGUISHING MEDIUM, BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL.  
Fire Fighting Procedures:FIRE FIGHTERS/OTHERS EXPOSED TO VAPORS/PRODUCTS OF COMBUSTION SHOULD WEAR SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONEL. WEAR PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITIED BY SPARKS, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====  
===== Accidental Release Measures =====

Spill Releas

Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB SPILL WITH ABORSENT MATERIAL SUCH AS SAWDUST, VERMICULITE, OR SAND, AND PLACE MATERIAL INTO CLOSED CONTAINER. LARGE SPILL: DIKE SPILL TO PREVENT MATERIAL FROM ENTERING WATER SYSTEMS/SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEAN UP.

==== Handling and Storage =====

Handling and Storage Precautions: AVOID PROLONGED/REPEATED INHALATION OF HEATED VAPORS/SPRAY MISTS. KEEP AWAY FROM HEAT/OPEN FLAME. MATERIAL MAY CAUSE SENSITIZATION. DO NOT GET IN EYES, ON SKIN/CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DO NOT WELD ON FULL/EMPTY CONTAINERS.

Other Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE & PROPERLY LABELED.

==== Exposure Controls/Personal Protection =====

Respiratory Protection: CANNISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT INHALATION OF VAPORS/SPRAY MISTS WHEN TLV/PEL IS EXCEEDED.

Ventilation: GENERAL VENTILATION IS REQUIRED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE LEVEL AIR

VOC Pounds/Gallon: 382

Viscosity: 75 KU

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: NIL

Appearance and Odor: BLACK MEDIUM VISCOUS LIQUID WITH A MILD SWEET AROMATIC ODOR.

Percent Volatiles by Volume: 48.5

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES, AND EPOXY HARDENERS UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid: KEEP AWAY FROM OPEN FLAMES, SPARKS, AND HEAT. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS GENERATES HYDROGEN GAS.

Hazardous Decomposition Products: INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

==== Disposal Considerations =====

Waste Disposal Methods: MATERIAL & CONTAINERS SHOULD BE TREATED AS HAZ

WASTE BASED ON IGNITABILITY PER RCRA (40 CFR 261). MATERIAL/CONTNR DISPOSAL REQUIRES COMPLIANCE W/ APPLICABLE LABELING, PACKAGING, & RECORD KEEPING STAND ARDS. DISPOSE IN ACCORDANCE W/ LOCAL/STATE/FED AGENCIES. GROUND HANDLING EQUIPMENT TO PREVENT SPARKS .

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or imp

lied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.