

CRC INDUSTRIES,INC. -- 2-26 BULK- 02006, 02007,02009, 02011 -- 6850-00-874-5847

=====
Product Identification
=====

Product ID:2-26 BULK- 02006, 02007,02009, 02011

MSDS Date:08/06/1996

FSC:6850

NIIN:00-874-5847

Status Code:A

MSDS Number: CJGLF

=== Responsible Party ===

Company Name:CRC INDUSTRIES,INC.

Address:885 LOUIS DR.

City:WARMINSTER

State:PA

ZIP:18974

Country:US

Info Phone Num:215-674-4300

E

mergency Phone Num:215-674-4300

Resp. Party Other MSDS Num.:02006

Preparer's Name:ADAM SELISKER

Chemtrec Ind/Phone:(800)424-9300

CAGE:023V4

=== Contractor Identification ===

Company Name:ABSCOA INDUSTRIES INC

Address:2000 ROBOTICS PL

Box:185369

City:FORT WORTH

State:TX

ZIP:76118-7129

Country:US

Phone:817-284-4449

Contract Num:SP0450-99-M-C837

CAGE:2N335

Company Name:CRC INDUSTRIES, INC.

Address:885 LOUIS DRIVE

Box:City:WARMINSTER

State:PA

ZIP:18974-2869

Country:US

Phone:215-674-4300/ 800-521-316

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATE
CAS:64742-47-8
RTECS #:OA5504000
Minumum % Wt:65.
Maxumum % Wt:73.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM

Ingred Name:INHIBITED PARAFFINIC OIL
Minumum % Wt:24.
Maxumum % Wt:30.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV FOR OIL MIST
IS 5 MG/M3.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS: EYE, SKIN, CENTRAL
NERVOUS SYSTEM (CNS) AND RESPIRATORY TRACT (HMIS). ACUTE - MAY
CAUSE IRRITATION/BURNING OF EYES. SKIN CONTACT WILL CAUSE DRYNESS.
INHALATION OF MISTS MAY CAUSE BREATH ING PROBLEMS, CNS EFFECTS. MAY
BE HARMFUL IN SWALLOWED. ASPIRATION HAZARD. CHRONIC- PROLONGED
EXPOSURE TO SKIN MAY CAUSE DEVEL
OPMENT DERMATITIS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, DROWSINESS, DIZZINESS, NAUSEA,
VOMITING, HEADACHE, REDNESS, TEARING, BLURRED VISION, DRY SKIN,
DEFATTING, DERMATITIS, FATIGUE

=====
First Aid Measures
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED: REMOVE TO
FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NEEDED. EYES: FLUSH WITH
LARGE AMOUNT OF WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN

:
REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION INTO LUNGS.

=====
Fire Fighting Measures
=====

Flash Point Method:COG
Flash Point:79.4C, 175.F
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL.
Unusual Fire/Explosion Hazard:TREAT AS A TYPICAL OIL FIRE.

=====
Accidental Release
Measures
=====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. VENTILATE AREA.
RECOVER IF POSSIBLE. PICK UP SPILL WITH INERT ABSORBENT SUCH AS SAND, EARTH AND PLACE IN A CLOSED CONTAINER. PREVENT SPILL FROM ENTERING SEWERS OR WATERWAYS.
Neutralizing Agent:NOT RELEVANT

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL, DRY AREA AWAY FROM STRONG OXIDIZING AGENTS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:ADDITIVES ARE PRIMARLY FATTY ACIDS AND FATTY ACID ESTERS. VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS. OSHA SHORT TERM EXPOSURE LIMIT (STEL) FOR OIL MIST IS 10 MG/M3. WASH THOROUGHLY AFTER HANDLING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPROVED RESPIRATORS ABOVE PEL.
Ventilation:ADEQUATE TO MAINTAIN OIL MIST BELOW PEL.
Protective Gloves:SOLVENT RESISTANT
Eye Protection:SAFETY GLASSES
Other Protective Equipment:OIL RESISTANT APRONS, BOOTS, ETC. SHOULD BE WORN IF POSSIBILITY OF BODY CONTACT EXISTS.
Work Hygienic Practices:GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V4
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:193.3C, 380.F
Vapor Pres:0.23
Vapor Density:>1
Spec Gravity:0.8167
VOC Pounds/Gallon:48
Evaporation Rate

& Reference:0.01 (TOLUENE = 1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:AMBER LIQUID - PLEASANT ODOR
Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products:CO2 AND CARBON MONOXIDE (FIRE)

===== Disposal Considerations =====

Waste Disposal Methods:ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED
OF IN C
ONFORMANCE WITH LOCAL, STATE, AND FEDERAL LAWS AND
REGULATIONS.

===== Regulatory Information =====

SARA Title III Information:THIS PRODUCT CONTAINS NO CHEMICALS THAT ARE
SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III
OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of D

efense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.