View NSN Online: https://aerobasegroup.kr/nsn/6685-00-242-2183

WEKSLER INSTRUMENTS CORP -- MERCURY IN GLASS THERMOMETER -- 6685-00-242-2183

Product ID:MERCURY IN GLASS THERMOMETER MSDS Date:06/23/1999 FSC:6685 NIIN:00-242-2183 Status Code:A MSDS Number: CJGQZ === Responsible Party === Company Name: WEKSLER INSTRUMENTS CORP Address:80 MILL ROAD Box:808 City:FREEPORT State:NY ZIP:11520-0808 Country:US Info Phone Num:516-623-010 0 Emergency Phone Num:516-623-0100/800-424-9300(CHEMTREC) Resp. Party Other MSDS Num.:NONE Preparer's Name:DSCR-VBA Chemtrec Ind/Phone:(800)424-9300 CAGE:64467 === Contractor Identification === Company Name:WEKSLERIGLASS THERMOMETER CORP Address:80 MILL ROAD Box:City:FREEPORT State:NY ZIP:11520 Country:US Phone:516-623-0100 CAGE:64467

Ingred Name:MERCURY (SARA III) CAS:7439-97-6 RTECS #:OV4550000 Fraction by Wt: 100% % Other REC Limits:NONE SPECIFIED OSHA PEL:S, C, 0.1 MG/M3 Code:F ACGIH TLV:S, 0.05 MG/M3; 9192 Code:F EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INHALATION OF HIGH LEVELS CAN LEAD TO SEVERE RESPIRATORY IRRITATION, CHEST PAINS, COUGHING AND

BREATHING DIFFICULTIES. CNS, KIDNEY AND/OR LIVER DAMAGE MAY OCCUR. CHRONIC: GUM, MOUTH INFLAMMATIO N, EXCESS SALIVATION, METALLIC TASTE, GINGIVITIS, IRRITABILITY, TREMORS, DEPRESSION, STOMATITIS, NERVOUSNESS

Explanation of Carcinogenicity: PRODUCT CONTAINS NO MATERIALS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:RESPIRATORY IRRITATION, CHEST PAINS, COUGHING, BREATHING DIFFICULTIES, CNS DAMAGE, KIDNEY/LIVER DAMAGE, GUM/ MOUTH INFLAM

MATION, EXCESS SALIVATION, METALLIC TASTE, GINGIVITIS, IRRITABILITY, TREMORS, D EPRESSION, STOMATITIS, NERVOUSNESS, PERSONALITY CHANGES.

Medical Cond Aggravated by Exposure:PERSONS WITH CHRONIC DISEASES SUCH AS TUBERCULOSIS, KIDNEY DISEASE, LIVER DISEASE AND ALCOHOLISM OR ARE IN POOR PHYSICAL CONDITION SHOULD BE EXCLUDED FROM CONTINUOUS EXPOSURE TO MERCURY VAPORS.

First Aid:CONTACT A QUALIFIED PHYSICIAN. I NHALATION: REMOVE TO FRESH

AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING DIFFICULT, GIVE OXYGEN. EYES: OCCASIONAL CONTACT USUALLY HARMLESS IF WASHED OUT IMMEDIATELY. FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH EXPOSED AREA WITH SOAP AND WATER. CAN BE ABSORBED THROUGH THE SKIN. INGESTION: USUALLY HARMLESS. DO NOT INDUCE VOMITING.

Flash Point:NONE Autoignition Temp:Autoignition Temp Text:

NONE Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media: APPROPRIATE FOR SURROUNDING FIRE Fire Fighting Procedures: APPROPRIATE FOR SURROUNDING FIRE
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.
Accidental Polococ Maccurac
======================================
Spill Release Procedures:USE APPROPRIATE RESPIRATORY PROTECTION AND PROTECTIVE CLOTHING. CLEAN UP SPILLS IMMEDIATELY WITH VACUUM EQUIPMENT THAT HAS A FILTERED EXHAUST. DO NOT DRY SWEEP. DECONTAMINATE WITH
A MERCURY DECONTAMIN ANT. REPORATBLE QUANTITY
(RQ) IS 1 POUND. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions: HANDLE AND STORE THERMOMETER WITH PROPER CARE.
Other Precautions:MERCURY WILL READILY FORM AMALGAMS WITH GOLD AND SILVER.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection: IF MERCURY SPILLAGE & PEL IS EXCEEDED. RESPIRATORY
PROTECTION SHOULD BE NIOSH-MESA CERTIFIED.
Ventilation: FOR MERCURY TO KEEP CONCENTRATIONS BELOW PEL. LOCAL EXHAUST AT THE POINT OF ORIGIN. MECHANICAL ALSO RECOMMENDED.
Protective Gloves: IMPERVIOUS
Eye Protection:GLASSES OR GOGGLES Other Protective Equipment:TIGHTLY WOVEN (IE, TYVEK) WORK CLOTHING FITTING CLOSELY ABOUT NECK, WRISTS AND ANKLES SHOULD BE WORN.
Work Hygienic Practices:NO FOO, FOOD STUFFS, OR TOBACCO PRODUCTS SHOULD BE PRESENT IN MERCURY AREAS. NO SMOKING OR EATING IN MER CURY AREAS.
Supplemental Safety and Health
CLOTHING SHOULD BE REMOVED AND WASHED FREQUENTLY.
======================================
HCC:Z2
Boiling Pt:B.P. Text:675F,357C
Melt/Freeze Pt:M.P/F.P Text:-38F39C

Vapor Pres:0.0012 Vapor Density:1.015 Spec Gravity:13.59 Evaporation Rate & amp; Reference:DEPENDS ON TEMP AND PRESS Appearance and Odor:SILVER METALLIC LIQUID, MOBILE AND ODORLESS

Stability

Indicator/Materials to Avoid:YES HALOGENS, NITRIC ACID, AMMONIA GAS, ALUMINUM, ACETYLENE AND ACETYLENE PRODUCTS. Stability Condition to Avoid:HIGH TEMPERATURES AND OPEN FLAMES. Hazardous Decomposition Products:MERCURY VAPORS

Waste Disposal Methods:REMOVE MERCURY AND MATERIALS THAT HAVE COME IN CONTACT WITH MERCURY TO PROPER DISPOSAL AREA. MERCURY IS RECYCLABLE. DO NOT PUT IN GARBAGE, FLUSH IN SEWER, OR INCINERATE. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and a

ssume responsibility for the suitability of this information to their particular situation.