

COUNTER ASSAULT -- COUNTER ASSAULT OC-10 -- 6850-01-444-1124

=====
Product Identification
=====

Product ID:COUNTER ASSAULT OC-10

MSDS Date:02/01/1999

FSC:6850

NIIN:01-444-1124

Status Code:A

MSDS Number: CJLSK

=== Responsible Party ===

Company Name:COUNTER ASSAULT

Address:120 INDUSTRY CT

City:KALISPELL

State:MT

ZIP:59901

Country:US

Info Phone Num:406-257-4740

Emergency Phone Num:800-695-3394

Prepar

er's Name:NOT LISTED

CAGE:082C9

=== Contractor Identification ===

Company Name:COUNTER ASSAULT

Address:120 INDUSTRY CT

Box:City:KALISPELL

State:MT

ZIP:59901

Country:US

Phone:406-257-4740

Contract Num:SP0450-99-M-NH92

CAGE:082C9

=====
Composition/Information on Ingredients
=====

Ingred Name:OLEORESIN CAPSICUM

Fraction by Wt: 10%

Ingred Name:HCFC 134A (DUPONT)

CAS:811-97-2

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:T

HIS PRODUCT IS AN EYE AND SKIN
IRRITANT.

Effects of Overexposure:TEARING, REDNESS AND ITCHING. SEVERE HEARTBURN
AND NAUSEA.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED: MOVE TO FRESH
AIR. EYES: FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SEE
PHYSICIAN. SKIN: WASH WITH SOAP & WATER. REMOVE CONTAMINATED
CLOTHING. ORAL: GIVE WATER TO DRINK. SEEK IMMEDIATE MEDICAL
ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Lower Limits:NOT ESTAB

Upper Limits:NOT ESTAB

Extinguishing Media:THIS MATERIAL IS NONFLAMMABLE. CARBON DIOXIDE,
ALCOHOL FOAM, DRY CHEMICALS OR WATER MAY BE INEFFECTIVE. USE WATER
TO DISPERSE FUMES AND TO DILUTE SPILL.

Fire Fighting Procedures:AS WITH ANY FIRE, WEAR PROTECTIVE CLOTHING AND
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS TO AVOID
INHALATION OF HAZARDOUS DECOMPOSTION PRODUCTS
OR SMOKE. USE WATER

SPRAY TO COOL NEARBY CONTAIN ERS AND STRUCTURES EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE MAY RELEASE TOXIC DECOMPOSITION
PRODUCTS. CANS MAY RUPTURE IN THE HEAT OF FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. AVOID PROLONGED BREATHING OF
VAPORS. CONFINE SPILL WITH INETR ABSORBERS. WEAR PROTECTIVE
EQUIPMENT DURING CLEAN UP. KEEP OUT OF SEWERS, STORM DRAINS,
SURFACE WATER AND S
OIL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA, AWAY FROM
HIGH TEMPERATURES. WHEN STORING LARGE QUANTITIES, STORE IN BUILDING
DESIGNED AND PROTECTED AGAINST FIRE.

Other Precautions:DO NOT STORE IN DIRECT SUNLIGHT OR ABOVE 120 F.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED CHEMICAL/MECHANICAL TYPE
FILTER SYSTEM TO REMOVE A COMBIN

ATION OF PARTICLES, GAS AND VAPORS.

USE AIR LINE, IF NECESSARY.

Ventilation:USE ADEQUATE VENTILATION IN VOLUME & PATTERN TO KEEP PEL/TLV BELOW RECOMMENDED LEVELE. GENERAL MECHANICAL VENTILATION SHOULD COMPLY WITH OSHA 1910.94.

Protective Gloves:USE RUBBER GLOVES.

Eye Protection:SAFETY GLASSES OR GOGGLES WITH SPLASH GUARDS OR SIDE SHIELDS.

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER

BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

DO NOT TAKE INTERNALLY. IF INGESTED, DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN.

===== Physical/Chemical Properties =====

HCC:V2

Vapor Pres:96 LBS @77F (PROPELLANT)

Spec Gravity: