View NSN Online: https://aerobasegroup.kr/nsn/3439-01-426-1320

PRAXAIR SURFACE TECHNOLOGIES INC -- CRO-131 (PRODUCT CODE 062018-10)

3439-01-426-1320

Product ID:CRO-131 (PRODUCT CODE 062018-10)

MSDS Date:03/23/1994

FSC:3439

NIIN:01-426-1320

Status Code:A

MSDS Number: CJTGZ === Responsible Party ===

Company Name: PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

City: INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

In

fo Phone Num:317-240-2650

Emergency Phone Num:317-240-2209

Preparer's Name: MICHELLE ALEXANDER

Chemtrec Ind/Phone:(800)424-9300

CAGE:0FGH2

=== Contractor Identification ===

Company Name: PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET Box:City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:0FGH2

Company Name: STARGHILL TECHNOLOGIES CORP

Address:3850 OAKMAN BLVD

Box:City:DETROIT

State:MI

ZIP:48204-1119

Country:US

Phone:313-933-4141

Contract Num:SP0490-95-D-4037

CAG

E:0VYG8
======= Composition/Information on Ingredients ========
Ingred Name:CHROMIUM OXIDE CAS:1308-38-9 RTECS #:GB6475000 > Wt:75.
======================================
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES   IARC:YES   OSHA:YES   Health Hazards Acute and Chronic:ACUTE- NO EVIDENCE OF ADVERSE EFFECTS. CHRONIC- NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE   INFORMATION. Explanation of Carc   inogenicity:CHROMIUM HAS BEEN DETERMINED TO CAUSE   CANCER IN EXPERIMENTAL ANIMALS (IARC, NTP). Medical Cond Aggravated by Exposure:BREATHING OF DUST MAY AGGRAVATE   ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE. MAY ALSO   AGGRAVATE AN EXISTING DERMATITIS.
======================================
First Aid:INGESTION: NO HARMFUL EFFECTS EXPECTED. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. INHALATION: NO EMERGENCY CARE ANTICIPATED. EYES: FLU SH THOROUGHLY WITH WATER. NOTES TO PHYSICIAN: THERE IS NO SP ECIFIC ANTIDOTE. TREATMENT OF OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE
CLINICAL CONDITION.  ===================================

Flash Point:NONE Lower Limits:NONE Upper Limits:NONE

Extinguishing Media: USE SPECIAL DRY POWDER METAL EXTINGUISHING MATERIAL TO EXTINGUISH METAL FIRES. USE APPROPRIATE EXTINGUISHER TO EXTINGUISH COMBUSTABLE MATERIALS THAT MAY BE I

GNITED BY THERMAL FLAME.

- Fire Fighting Procedures: CONSULT AND COMPLY WITH ANSI Z49.1 SAFETY IN WELDING AND CUTTING, NFPA51B STANDARD FOR FIRE PREVENTION IN USE OF CUTTING AND WELDING PROCESSES. NFPA51B OXYGEN-FUEL GAS SYSTEMS FOR WELDING AND CUTTING, AND NFPA58 STANDARD FOR THE STORAGE AND HANDLING OF LIQUIFIED PETROLEUM GASES.
- Unusual Fire/Explosion Hazard:AIRBORNE DUST PARTICLES, ESPECIALLY METAL DUST, AND ACCUMULATION OF SUCH SHOULD BE TREATED AS EXPLOSIVES. TO MI
- NIMIZE DANGER FROM DUST EXPLOSIONS, ADEQUATE VENTILATION SHOULD BE PROVIDED TO SPRAY BOOT H IN ACCORDANCE WITH AMERICAN WELDING SOCIETY PUBLICATION AWSC2.1-73, AND ACGIH PUBLICATION "INDUSTRIAL VENTILATION".

	Accidental	Release	Measures	
--	------------	---------	----------	--

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT TO PROTECT AGAINST HAZARDS AND DISPOSE OF PER WASTE DISPOSAL METHOD.

=======================================	Handling a	and Storage	

## Other Precaution

S:CAUTION: WHEN THERMAL SPRAYING - ELECTRICITY CAN
CAUSE FATAL SHOCK! DO NOT TOUCH LIVE ELECTRICAL PARTS! ARC RAYS CAN
BURN EYES AND SKIN! WEAR RECOMMENDED EYE AND BODY PROTECTION.
FUMES, GAS, & DUST CA N HARM YOUR HEALTH. PROVIDE ENOUGH
VENTILATION AND WEAR RESPIRATORS.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: DEPENDS UPON SPECIFIC USE, CONDITION, AND LOCATION. IF THERE IS DUSTINESS, WEAR RESPIRATOR SELECTED PER OSHA 1

910.134, AND OSHA 29 CFR 1910.252 AND ANSI Z49.1

Ventilation:LOCAL DUST PICK UP AND VENTILATION RECOMMENDED.

Protective Gloves: NOT REQUIRED.

Eye Protection: WHEN DUSTY USE GOGGLES PER OSHA 1910.13.

Other Protective Equipment: SEE ANSI Z49.1, ANSI Z87.1, ANSI Z88.2 FOR HELMETS, FACE SHIELDS AND GOGGLES.

Supplemental Safety and Health

CAUTION: WHEN THERMAL SPRAYING-ELECTRICITY CAN CAUSE FATAL SHOCK! DO NOT TOUCH LIVE ELECTRICAL PARTS! ARC RAYS CAN BURN EYES AND SKIN! WEAR RECOMMENDED EYE

RESPIRATORS.(OTHER INFO)
========== Physical/Chemical Properties ==========
HCC:N1 Boiling Pt:B.P. Text:NONE Vapor Density:N/VOLATILE Appearance and Odor:DUSTY DARK GREEN POWDER
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Produ cts:WHEN THERMAL SPRAYING, DECOMPOSITION PRODUCTS WILL VARY WITH OPERATING CONDITIONS. DECOMPOSITION PRODUCTS OF NORMAL OPERATION FROM THIS THERMAL SPRAY POWDER-OXIDES, SUB-OXIDES, ETC.
======== Disposal Considerations ==========
Waste Disposal Methods:DISPOSE OF WASTE PER LOCAL, STATE, AND FEDERAL REGULATIONS.
======== MSDS Transport Information ==========
Transport Information:PROPER SHIPPING NAME: METAL ALLOY POWDER NOI ITEM 136500 SUB 1.
======================================
SARA Title III Information:NONE State Regulatory Information:NONE
========== Other Information =============
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate a

ANDBODY PROTECTION. FUMES, GAS, AND DUST CAN HARM YOUR HEALTH. PROVIDE ENOUGH VENTILATION AND WEAR

nd disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.