

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3202 (PART B) -- 8030-00-275-8110

=====
Product Identification
=====

Product ID:CS 3202 (PART B)

MSDS Date:06/24/1996

FSC:8030

NIIN:00-275-8110

Status Code:A

MSDS Number: CJZPL

=== Responsible Party ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Info Phone Num:818-982-1650

Em

ergency Phone Num:(800)424-9300

Preparer's Name:HERBERT MOORE

Chemtec Ind/Phone:(800)424-9300

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

=====
Composition/Information on Ingredients
=====

Ingred Name:LIQUID POLYSULFIDE POLYMER

CAS:68611-50-7

= Wt:65.

Ingred Name:LEAD DIOXIDE

CAS:1309-60-0

RTECS #:OG0700000

= Wt:64.

OSHA PEL:0.05 MG/M3
ACGIH TLV:0.05 MG/M3

Ingred Name:LEAD OXIDE
CAS:1317-36-8
RTECS #:OG1750000
= Wt:6.
OSHA PEL:0.05 MG/M3
ACGIH TLV:0.05 MG/M3

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:WEAKNESS, STUPOR. CHRONIC: KIDNEY
DAMAGE, ANEMIA REPRODUCTIVE DEFECTS.
Effects of Overexposure:HEADACHE, MUSCLE AND NOINT PAIN, NEUROMUSCULAR
DYSFUNCTION.
Medical Cond Aggravated by Exposure:ANEMIA, KIDNEY DISEASE, PREGNANCY.

=====
===== First Aid Measures =====

First Aid:FIRST AID: INGESTION- INDUCE VOMITING, CONSULTA PHYSICIAN AT
ONCE. EYE CONTACT-FLUSH WITH LARGE AMOUNTS OF WATER.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=93.3C, 200.F
200F
Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER.
Fire Fighting Procedures:USE A SELF CONTAINED BREATHING APPARATUS WITH
FULL FACE PIECE IN CONFINED AREAS.
Unusual Fire/Explosion Hazar
d:FIRE HAZARDS EXISTS IF CONTACT WITH
OXIDIZABLE MATERIALS AT HIGH TEMPERATURES OCCURS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP AND TRANSFER TO A SAFETY CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL DRY AREA. KEEP
CONTAINERS CLOSED. WASH HANDS BEFORE EATING, SMOKING OR DRINKING
AFTER HANDLING THIS PRODUCT.

=====
===== Exposure Control

s/Personal Protection =====

Respiratory Protection:IF SOOT IS FORMED USE NIOSH APPROVED RESPIRATOR.
NONE

Ventilation:LOCAL EXHAUST: AIR HOOD. MECHANICAL: FAN.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT.

Work Hygienic Practices:TRAIN EMPLOYEES IN SAFE HANDLING OF THIS
PRODUCT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt.=340.C, 644.

F

B.P. Text:340C VEHICLE

Vapor Pres:NIL

Vapor Density:NIL

Spec Gravity:3

pH:6.8

Viscosity:11,000 POISES

Evaporation Rate & Reference:1

Solubility in Water:NEGLEGABLE

Appearance and Odor:BROWN PASTE, OILY ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS

Hazardous Decomposition Products:LEAD OXIDE DUST AND ORGANICS.

===== Disposal Considerations =====

Waste Disposal Methods:

RETURN TO SMELTER FOR RECLAMATION OR REACT WITH

BASE AND DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:APPLICABLE REGULATIONS: 49 CFR, IMO, IATA. UNIT
CONTAINER: 2 OZ PLASTIC JAR. US POSTAL SERVICE REGULATIONS: PARA
124.142 HARMFUL MATTER. DISPOSAL INFORMATION: RETURN TO SMELTER
FOR RECLAMATION O R REACTWITH BASE AND DISPOSE ACCORDING TO
REGULATIONS. HAZARDOUS WASTE

CHARACTERISTICS: SLUDGE-UNMIXED.

DISPOSAL METHODS: RETURN TO SMELTER FOR RECLAMTION OR REACT WITH BASE AND DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS. DISPOSE AS A HAZARDOUS MIXED SOLID WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.