

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3202 CLASS B (BLACK) (PART A) --
8030-00-537-7925

===== Product Identification =====

Product ID:CS 3202 CLASS B (BLACK) (PART A)
MSDS Date:06/24/1996
FSC:8030
NIIN:00-537-7925
Status Code:A
MSDS Number: CJZPP
=== Responsible Party ===
Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV
Address:11120 SHERMAN WAY
City:SUN VALLEY
State:CA
ZIP:91352-4949
Country:U
S
Info Phone Num:818-982-1650
Emergency Phone Num:(800)424-9300
Preparer's Name:HERBERT MOORE
Chemtrec Ind/Phone:(800)424-9300
CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV
Address:11120 SHERMAN WAY
Box:City:SUN VALLEY
State:CA
ZIP:91352-4949
Country:US
Phone:818-982-1650
CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:LIQUID POLYSULFIDE POLYMER
CAS:68611-50-7
= Wt:65.

===== Hazards Ide

ntification =====

Health Hazards Acute and Chronic:POSSIBLE SKIN IRRITATION AFTER PROLONGED CONTACT, WITH RESULTING DERMATITIS. NOT CONSIDERED TO BE A PRIMARY SKIN IRRITANT.

Effects of Overexposure:SKIN OR IRRITATION.

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH LARGE AMOUNTS OF WATER, CONSULT PHYSICIAN. SKIN-WASH WITH SOAP AND WATER. INGESTION- INDUCE VOMITING, CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=-93.3C, 200.F
200F
Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP AND TRANSFER TO CONTAINER FOR REACTION WITH CURING AGENT. CLEANUP RESIDUE WITH AEROMATIC NAPHTHA/SAND/SWEEPING COMPOUND. WASH AREA WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY AREA AWAY FROM STRONG ACIDS.
Other Precautions:WASH HANDS BEFORE EATING, SMOKING OR DRINKING AFTER HANDLING THIS PRODUCT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:LOCAL EXHAUST: AIR. MECHANICAL: FAN.
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES
Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT.
Work Hygienic Practices:TRAIN EMPLOYEES IN SAFE HANDLING OF TH

IS
PRODUCT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:NIL
Spec Gravity:1.45
pH:8.5
Viscosity:11,000 POISES
Evaporation Rate & Reference:1
Solubility in Water:NEGLEGABLE
Appearance and Odor:BLACK PASTE, POLYSULFIDE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS AND STRONG ACIDS
Stability Condition to Avoid:OPEN FLAME
Haza
rdous Decomposition Products:H2S, CO, CO2, SO2, SMOKE.

===== Disposal Considerations =====

Waste Disposal Methods:REACT WITH CURING AGENT AND DISPOSE AS HAZARDOUS
WASTE, NON-MIX , NON-HAZARDOUS.

===== MSDS Transport Information =====

Transport Information:SHIPPING NAME: ADHESIVE N.O.S. HAZARD CLASS:
NON-HAZARDOUS UNIT CAONTAINER: 12 OZ IN 16 OZ METAL CAN. US
POSTAL REGULATIONS: PARA 124.142 HARMFUL MATTER. DISP
OSAL INFO:
INCINERATION OR LAN D DISPOSAL, MIXED WITH PART B, HAZARDOUS WASTE,
NON-MIX, NON-HAZARDOUS. EPA CODE: CADO62064746. WASTE
CHARACTERISTICS: SLUDGE. DISPOSAL METHODS: INCINERATION OR LAND
DISPOSAL, DISPOSE WASTE ACCOR DING TO FEDERAL, STATE AND LOCAL
REGULATIONS. APPLICABLE REGULATIONS: 49 CFR, IMO, IATA.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. T

he United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.