

PULSAFEEDER INC -- PULSALUBE #5 -- 9150-01-470-2830

===== Product Identification =====

Product ID:PULSALUBE #5

MSDS Date:11/01/1997

FSC:9150

NIIN:01-470-2830

Status Code:A

MSDS Number: CKCTD

=== Responsible Party ===

Company Name:PULSAFEEDER INC

Address:2883 BRIGHTON-HENRIETTA TOWN LINE ROAD

City:ROCHESTER

State:NY

ZIP:14623

Country:US

Info Phone Num:716-292-8000

Emergency Phone Num:800-662-4525

Chemtec Ind/Phone:(800)424-9300

CAGE:TO515

=== Contractor Identification ===

Company Name:PULSAFEEDER INC

Address:2883 BRIGHTON-HENRIETTA TOWN LINE ROAD

Box:City:ROCHESTER

State:NY

ZIP:14623

Country:US

Phone:716-292-8000

CAGE:TO515

Company Name:PUMP & CORROSION TECHNOLOGIES

Phone:000-000-0000

CAGE:TO516

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENT

= Wt:100.

===== Hazards Identification =====

LD50

LC50 Mixture:LD50 > 2000 MG/KG (RAT)
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:NONE LISTED.

===== First Aid Measures =====

First Aid:EYE CONTACT:FLUSH THOROUGHLY WITH WATER.IF IRRITATION PERSISTS, CALL A PHYSICIAN. SKIN CONTACT:WASH CONTACT AREAS WITH SOAP AND WATER. INHALATION:REMOVE FROM FURTHER EXPOSURE. IF RESPIRATORY IRRITATION, DIZZINESS,NAUSEA, OR UNCONSCIOUSNESS OCCURS, SEEK IMMEDIATE MEDICAL ASSISTANCE AND CALL A PHYSICIAN. IF BREATHING HAS STOPPED, USE MOUTH TO MOUTH RESUSCITATION. INGESTION:NOT EXPECTED TO BE A PROBLEM WHEN INGESTED. IF UNCOMFORTABLE, SEEK MEDICAL ASSISTANCE.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>237.8C, 460.F
Lower Limits:.6%
Upper Limits:7.0%
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE. FOR FIRES IN ENCLOSED AREAS, FIREFIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS. PREVENT RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING STREAMS, SEWERS, OR DRINKING WATER
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST, DISTOMACEOUS EARTH, ETC. SHOVEL UP AND DISPOSE OF AT AN APPROPRIATE WASTE DISPOSAL FACILITY IN ACCORDANCE WITH CURRENT APPLICABLE LAWS AND REGULATIONS, AND PRODUCT CHARACTERISTICS AT TIME OF DISPOSAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.
Ventilation:USE IN WELL VENTILATED AREA.
Protective Gloves:NO SPECIAL EQUIPMENT REQUIRED.
Eye Protection:NORMAL INDUSTRIAL EYE PROTECT

ION PRACTICES SHOULD BE
EMPLOYED.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS
BE FOLLOWED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>316.C, 600.8F

Vapor Pres: