View NSN Online: https://aerobasegroup.kr/nsn/6830-01-424-2499

AIR LIQUIDE AMERICA CORP -- NON-FLAMMABLE GAS MIXTURE -- 6830-01-424-2499

Product ID:NON-FLAMMABLE GAS MIXTURE

MSDS Date:03/25/1997

FSC:6830

NIIN:01-424-2499

MSDS Number: CKFJJ === Responsible Party ===

Company Name: AIR LIQUIDE AMERICA CORP

Address:821 CHESAPEAKE DRIVE

City:CAMBRIDGE

State:MD ZIP:21613 Country:US

Info Phone Num:410-228-6400;713-868-0440

Emergency

Phone Num:1-800-424-9300

Resp. Party Other MSDS Num.:50009

Preparer's Name: CHEMICAL SAFETY ASSOC.

Chemtrec Ind/Phone:(800)424-9300

CAGE:04AA7

=== Contractor Identification ===

Company Name: AIR LIQUIDE AMERICA CORP

Address:821 CHESAPEAKE DRIVE

Box:City:CAMBRIDGE

State:MD ZIP:21613 Country:US

Phone:410-228-6400;713-868-0440

CAGE:04AA7

Company Name: GAS TECH INC. JOHNSON INSTRUMENT DIV

Address:8445 CENTRAL AVE

Box:City:NEWARK

State:CA

ZIP:94560-3431

Country:US

Phone:510-794-6200

CAGE:51906 Company

Name: NEW ERA CONTRACT SALES Address:2513 TACOMA AVE S Box:City:TACOMA State:WA ZIP:98402-1308 Country:US Phone:253-272-3553 Contract Num:SP0450-00-M-D755 CAGE:0FA68 ======= Composition/Information on Ingredients ======== Ingred Name: OXYGEN CAS:7782-44-7 RTECS #:RS2060000 Minumum % Wt:0. Maxumum % Wt:23.5 Ingred Name:METHANE CAS:74-82-8 RTECS #:PA1490000 Minumum % Wt:0. Maxumum % Wt:2.5 Ingred Name: HYDROGEN CAS:1333-74-0 RTECS #:MW8900000 Minumum % Wt:0. Maxumum % Wt:2. Ingred N ame:CARBON MONOXIDE CAS:630-08-0 RTECS #:FG3500000 < Wt:1. OSHA PEL:55 MG/M3;50 PPM ACGIH TLV:29 MG/M3;25 PPM Ingred Name: NITROGEN CAS:7727-37-9 RTECS #:QW9700000 Minumum % Wt:0. Code:F Maxumum % Wt:2.9 Code:F

=========== Hazards Identification =================

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS: RESPIRATORY SYSTEM,
BLOOD SYSTEM, CARDIOVASCULAR SYSTEM, REPRODUCTIVE SYSTEM. ACUTE:
DUE TO THE SMALL SIZE

- OF THE INDIVIDUAL CYLINDER, NO UNUSUAL HEALTH
 - EFFECTS FROM EXPOSURE TO THE PRO DUCT ARE ANTICIPATED UNDER ROUTINE CIRCUMSTANCES OF USE. HOWEVER, CARBON MONOXIDE IS TOXIC TO HUMANS. SYMPTOMS OF CARBON MONOXIDE POISONING CAN DEVELOP GRADUALLY, OR CAN ARISE SUDDENLY, DEPENDING ON THE CONCENTRATION AND DURATION OF EXPOSURE. OTHER SYMPTOMS OF OVER-EXPOSURE CAN INCLUDE RESPIRATORY DIFFICULTY, HEADACHES, SHORTNESS OF BREATH, WHEEZING, BLURRED VISION, MEMORY LOSS, DIZZINESS
- , INGESTI ON, NAUSEA, UNCONSCIOUSNESS & DEATH.
- Explanation of Carcinogenicity: THE COMPONENTS OF THIS GAS MIXTURE ARE NOT FOUND ON THE FOLLOWING LISTS: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, AND IARC; THEREFORE ARE NOT CONSIDERED TO BE, NOR SUSPECTED TO BE, CANCER CAUSING AGENTS THESE AGENCIES.
- Effects of Overexposure:ALLEXPOSURE LEVELS: OVEREXPOSURE TO CARBON MONOXIDE CAN BE INDICATED BY THE LIPS & FINGERNAILS TURNING BRIGHT RED. 200PPM: SLIGHT SYMPTOMS (HEADACHE, DISCOMF ORT) AFTER SEVERAL
 - HOURS OF EXPOSURE. 400PP M: HEADACHE & DISCOMFORT EXPERIENCED WITHIN 2-3 HOURS OF EXPOSURE. 1,000-2,000PPM: WITHIN 30 MINUTES, SLIGHT PALPITATION OF THE HEART OCCURS. WITHIN 1.5 HOURS, THERE IS A TENDENCY TO STAGGER. 200-2500 PPM: WITHIN 2 HOURS, THERE IS MENTAL CONFUSION, HEADACHES, & NAUSEA. UNCONSCIOUSNESS WITHIN 30 MINUTES. >25000 PPM: POTENTIAL FOR COLLAPSE & DEATH BEFORE WARNING SYMPTOMS ARE PRODUCED.

Medical Cond Aggravated by Exposure:PRE-E

XISTING RESPIRATORY CONDITIONS

MAY BE AGGRAVATED BY OVER-EXPOSURE TO THIS PRODUCT. CARBON MONOXIDE, A COMPONENT OF THIS GAS MIXTURE, CAN AGGRAVATE SOME DISEASES OF THE CARDIOVASCULAR SYSTEM.

 First Aid Measures	
 I II St / Na IVICASAI CS	

- First Aid:RESCUERS SHOULD WEAR PERSONAL PROTECTIVE EQUIPMENT. AT A MINIMUM, SELF-CONTAINED BREATHING APPARATUS MUST BE WORN. NO UNUSUAL HELTH EFFECTS ARE ANTICIPATED AFTER EXPOSURE TO THIS PRODUCT, DUE TO THE S MAL
- L CYLINDER SIZE. IF ANY ADVSERSE SYMPTOM
 DEVELOPS AFTER OVER-EXPOSURE TO THIS PRODUCT, REMOVE VICTIM(S) TO
 FRESH AIR AS QUICKLY AS POSSIBLE. ONLY TRAINED PERSONNEL SHOULD
 ADMINISTER SUPPLEMENTAL OX YGEN AND/OR CARDIO-PULMONARY
 RESUSCITATION IF NECESSARY. VICTIM(S) WHO EXPERIENCE ANY ADVERSE
 EFFECT AFTER OVER-EXPOSURE TO THIS PRODUCT MUST BE TAKEN FOR
 MEDICAL ATTENTION. RESCUERS SHOULD BE TAKEN F OR MEDICAL ATTENTION
 IF NEEDED.

====== Fire Fighting Mea

CHILDE	

- Extinguishing Media:NON-FLAMMABLE GAS MIXTURE. USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.
- Fire Fighting Procedures: STRUCTURAL FIREFIGHTERS MUST WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.
- Unusual Fire/Explosion Hazard:THIS GAS MIXTURE IS NOT FLAMMABLE; HOWEVER, CONTAINERS, WHEN INVOLVED IN FIRE, MAY RUPTURE OR BURST IN THE HEAT OF THE FIRE.

======== Accidental Release Measures ===========

Spill Release Procedures:DUE TO THE SMALL SIZE AND CONTENT OF THE CYLINDER, AN ACCIDENTAL RELEASE OF THIS PRODUCT PRESENTS SIGNIFICANTLY LESS RISK OF AN OXYGEN DEFICIENT ENVIRONMENT AND OTHER SAFETY HAZARDS THAN A SIMILAR REL EASE FROM A LARGER CYLINDER. HOWEVER, AS WITH ANY CHEMICAL RELEASE, EXTREME CAUTION MUST BE USED DURING EMERGENCY RESPONSE PROCEDURES.

========== Handling and Storage ============

Handling and Storage Precautions: CYLINDERS SHOUL

D BE FIRMLY SECURED &

KEPT AT ROOM TEMPERATURE (~21C, 70F). CYLINDERS SHOULD BE STORED IN DRY, WELL-VENTILATED AREAS, AWAY FROM SOURCES OF HEAT, IGNITION & DIRECT SUNLIGHT. PROTECT CYLI NDERS AGAINST PHYSICAL DAMAGE. FULL AND EMPTY CYLINDERS SHOULD BE SEGREGATED.

Other Precautions:FOR HANDLING GAS CYLINDERS: WARNING! COMPRESSED GASES CAN PRESENT SIGNIFICANT SAFETY HAZARDS. DURING CYLINDER USE, USE EQUIPMENT DESIGNED FOR THESE SPECIFIC CYLINDERS. ENSURE ALL LINES AND E

QUIPMENT A RE RATED FOR PROPER SERVICE PRESSURE.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:NO SPECIAL RESPIRATORY PROTECTION IS REQUIRED UNDER NORMAL CIRCUMSTANCES OF USE. USE SUPPLIED AIR RESPIRATORY PROTECTION IF CARBON MONOXIDE LEVEL EXCEEDS LIMITS & OXYGEN LEVELS ARE BELOW 19.5% OR UNKN OWN DURING EMERGENCY RESPONSE TO RELEASE OF THIS PRODUCT. IF RESPIRATORY PROTECTION IS REQUIRED FOR EMERGENCY RESPONSE TO THIS PRODUCT, F

OLLOW 29 CFR 1910.134.

Ventilation:NO SPECIAL VENTILATION SYSTEMS OR ENGINEERING CONTROLS ARE NEEDED UNDER NORMAL CIRCUMSTANCES OF USE. AS WITH ALL CHEMICALS, USE THIS PRODUCT IN WELL-VENTILATED

Protective Gloves: NO SPECIAL PROTECTION IS NEEDED UNDER NORMAL CIRCUMSTANCES OF USE.

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: NO SPECIAL PROTECTION IS NEEDED UNDER NORMAL CIRCUMSTANCES OF USE.

Work Hygienic Practices:BE AWARE OF ANY SIGNS OF DIZZINESS OR FATIGUE; EXPO

SURES TO FATAL CONCENTRATIONS OF THIS PRODUCT COULD OCCUR WITHOUT ANY SIGNIFICANT WARNING SYMPTOMS, DUE TO OXYGEN DEFICIENCY.

Supplemental Safety and Health

HYGIENE: DO NOT ATTEMPT TO REPAIR, ADJUST, OR IN ANY OTHER WAY MODIFY THE CYLINDERS CONTAINING CARBON MONOXIDE. IF THERE IS A MALFUNCTION OR ANOTHER TYPE OF OPERATIONAL PROBLEM, CONTACT NEAREST DISTRIBUTOR IMMEDIATELY. ***DOCUMENT NUMBER: 50009

HCC:G3

Boi

ling Pt:=-195.6C, -320.4F

Melt/Freeze Pt:=-209.7C, -345.8F

M.P/F.P Text:@10 PSIG

Spec Gravity: 0.906@70F(21.1C)(AIR=1)

Solubility in Water: 0.023

Appearance and Odor: COLORLESS, ODORLESS GAS MIXTURE

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

TITANIUM WILL BURN IN NITROGEN (THE MAIN COMPONENT OF THIS PRODUCT). LITHIUM REACTS SLOWLY WITH NITROGEN AT AMBIENT TEMPS. COMPONENTS OF THIS PRODUCT (HYDROGEN, CARBON MONOXIDE, METHA

NE) ARE ALSO

INCOMPATIBLE WITH STRONG OX

Stability Condition to Avoid: NORMALLY STABLE IN GASEOUS STATE.

Hazardous Decomposition Products:THE THERMAL DECOMPOSITION PRODUCTS OF METHANE INCLUDE CARBON OXIDES. THE OTHER COMPONENTS OF THIS GAS MIXTURE DO NOT DECOMPOSE, PER SE, BUT CAN REACT WITH OTHER COMPOUNDS IN THE HEAT OF A FIRE.

Conditions to Avoid Polymerization:CONTACT WITH INCOMPATIBLE MATERIALS.

CYLINDERS EXPOSED TO HIGH TEMPERATURES OR DIRECT FLAME CAN RUPTURE
OR BUR

======== Toxicological Information ==========

Toxicological Information:CARBON MONOXIDE: TCL0 (INHALATION, MOUSE) = 65 PPM/24 HOURS. LC50 (INHALATION, RAT) = 1811 PPM/4 HOURS. LC50 (INHALATION, WILD BIRD) = 1334 PPM. NITROGEN, HYDROGEN & METHANE: THERE ARE NO SPECIFIC TOX ICOLOGICAL DATA FOR NITROGEN, HYDROGEN & METHANE IS A SIMPLE ASPHYXIANT, WHICH ACTS TO DISPLACE OXYGEN IN THE ENVIRONMENT. OXYGEN: OXYGEN IS THE VITAL ELEMENT IN THE ATMOSPHERE

IN WHICH WE LIVE & BREA THE. TOXICOLOGICAL DATA ARE AVAILABLE FOR OXYGEN, BUT DUE TO THE SMALL CYLINDER SIZE & SUBSEQUENT SMALL TOTAL AMOUNT OF OXYGEN IN THIS MIXTURE, NO EFFFECTS ARE ANTICIPATED.

=======================================	Ecologica	I Information	=======================================
---	-----------	---------------	---

Ecological: ENVIRONMENTAL STIBILITY: THE COMPONENTS OF THIS GAS MIXTURE OCCUR NATURALLY IN THE ATMOSPHERE. THE GAS WILL BE DISSIPATED RAPIDLY IN WELL-VENTILATED AREAS. EFFECT OF MATERIAL ON PLANT OR ANIMALS:

NO EVIDENCE IS CURRENTLY AVAILABLE ON THIS PRODUCT'S
EFFECTS ON PLANT AND ANIMAL LIFE. CARBON MONOXIDE CAN BE DEADLY TO
EXPOSED ANIMAL LIFE. CARBON MONOXIDE MAY ALSO BE HARMFUL TO PLANT
LIFE. EFFECT OF C HEMICAL ON AQUATIC LIFE: THE PRESENCE OF MORE
THAN A TRACE OF CARBON MONOXIDE IS A HAZARD TO FISH.

=======================================	Disposal (Considerations	=======================================
---	------------	----------------	---

Waste Disposal Methods:WASTE DISPOSAL MUST BE IN ACCORDANCE WITH APPROPRIATE FEDERAL, STATE, AND LOCAL RE GULATIONS. CYLINDERS WITH UNDESIRED RESIDUAL PRODUCT MAY BE SAFELY VENTED OUTDOORS WITH THE PROPER REGULATOR.

======== MSDS Transport Information ===========

Transport Information:PROPER SHIPPING NAME: COMPRESSED GASES, N.O.S. (NITROGEN, OXYGEN). HAZARD CLASS: 2.2 (NON-FLAMMABLE GAS). UN IDENTIFICATION NUMBER: UN 1956. DOT LABEL: NON-FLAMMABLE GAS. NOTE: DOT 39 CYLINDERS SHIP IN A STRONG OUTER CARTON (OVERPACK). PERTINENT SHIPPING INFORMATION GOES

ON THE OUTSIDE OF THE OVERPACK.

DOT 39 CYLINDERS DO NOT HAVE TRANSPORTATION INFORMATION ON THE CYLINDER ITSELF. CYLINDERS SHOUL D BE TRANSPORTED IN A SECURE POSITION, IN A WELL-VENTILATED VEHICLE. THE TRANSPORTATION OF COMPRESSED GAS CYLINDERS IN AUTOMOBILES OR IN CLOSED-BODY VEHICLES CAN PRESENT SEROUS SAFETY HAZARDS.

========== Regulatory Information =====================

SARA Title III Information: NOT APPLICABLE.

Federal Regulatory Information: TSCA INVENTORY

STATUS: THE COMPONENTS OF

THIS GAS MIXTURE ARE LISTED ON THE TSCA INVENTORY. CARBON MONOXIDE IS SUBJECT TO THE REPORTING REQUIREMENTS OF CFR 29 1910.1000. CARBON MONOXIDE IS LISTED ON T ABLE Z.1.

State Regulatory Information: CARBON MONOXIDE IS ON THE CALIFORNIA PROPOSITION 65 LISTS AS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. ALASKA - DESIGNATED TOXIC AND HAZARDOUS SUBS TANCE: CARBON MONOXIDE. CALIFORNIA - PERMISSI

BLE EXPOSURE LIMITS FOR CHEMICAL

CONTAMINANTS: CARBON MONOXIDE. FLORIDA - SUBSTANCE LIST: CARBON MONOXIDE. ILLINOIS - TOXIC SUBSTANCE LIST: CARBON MONO XIDE. MASSACHUSETS - SUBSTANCE LIST: CARBON MONOXIDE. OTHER STATES ARE: MINESOTA, MISSOURI, NEW JER SEY, NORTH DAKOTA, PENNSYLVANIA, RHODE ISLAND, TEXAS, WEST VIRGINIA, WISCONSIN.

========== Other Information ===============

Disclaimer (provided with this information by the compiling agencies):

is information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.