

JTM PRODUCTS INC -- MURPHY'S LIQUID TIRE MOUNTING COMPOUND -- 2640-00-256-5527

=====
Product Identification
=====

Product ID:MURPHY'S LIQUID TIRE MOUNTING COMPOUND

MSDS Date:02/01/1996

FSC:2640

NIIN:00-256-5527

Status Code:A

MSDS Number: CKFWJ

=== Responsible Party ===

Company Name:JTM PRODUCTS INC

Address:9505 CASSIUS AVE

City:CLEVELAND

State:OH

ZIP:44105

Country:US

Info Phone Num:216-341-2212

E

mergency Phone Num:800-255-3924

Resp. Party Other MSDS Num.:VEMDOR'S P/N: 46-643, 46-644, 46-647

Preparer's Name:B. NORAGON

CAGE:0T190

=== Contractor Identification ===

Company Name:JTM PRODUCTS INC

Address:9505 CASSIUS AVE

Box:City:CLEVELAND

State:OH

ZIP:44105

Country:US

Phone:216-341-2212

CAGE:0T190

Company Name:MYERS INDUSTRIES.

Box:UNKNOW

Contract Num:DAAE07-00-P-T195

CAGE:2U930

=====
Composition/Information on Ingredients
=====

Ingred Name:BLEND OF SOAP, WATER AND RUST

INHIBITORS.

= Wt:100.

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE IRRITANT, SLIGHT SKIN IRRITANT IF ALLOWED TO REMAIN IN CONTACT.

Explanation of Carcinogenicity:IARC, NTP, AND OSHA DO NOT LIST MURPHY'S LIQUID TIRE MOUNTING COMPOUND AS A CARCINOGEN.

Effects of Overexposure:EYE EFFECTS: EYE IRRITANT, SKIN EFFECTS: SLIGHT SKIN IRRITANT IF ALLOWED TO REMAIN IN CONTACT.

=

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH COPIOUS VOLUMES OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN CONTACT: WASH WITH WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:>104.4C, 220.F

Extinguishing Media:WATER, WATER FOG, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL ARE ALL SUITABLE.

Fire Fighting Procedures:DO NOT RELEASE RUNOFF FROM FIRE CONTROL

METHODS TO SEWERS OR WATERWAYS. BECAUSE FIRE MAY PRODUCE TOXIC THERMAL DECOMPOSITION PRODUCTS, WEAR A SELF-CONTAINED BREATHING APPARATUS(SCBA)WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR POSITIVE-PRESSURE MODE.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:THIS PRODUCT IS A BIODEGRADABLE SOAP. FOR LARGE SPILLS, DIKE FAR AHEAD OF LIQUID SPILL FOR LATER DISPOSAL.

CLEAN UP: PLACE THE BULK OF ANY SPILLED MATERIAL INTO DRUMS, THEN RINSE ANY REMAINING MATERIAL TO SEWAGE TREATMENT FACILITY, IN ACCORDANCE WITH ANY APPLICABLE REGULATIONS. REGULATORY REQUIREMENTS: FOLLOW APPLICABLE OSHA REGULATIONS(29 CFR 1910.120).

=====
===== Handling and Storage =====

Handling and Storage Precautions:HANDLING PRECAUTIONS: NO SPECIAL PRECAUTIONS ARE REQUIRED. STORAGE REQUIREMENTS: NO SPECIAL PRECAUTIONS ARE REQUIRED. REGULATORY

LATORY REQUIREMENTS: NO KNOWN
REGULATORY REQUIREMENT FOR HANDLING AND STORAGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF RESPIRATORS ARE USED, OSHA REQUIRES A WRITTEN RESPIRATORY PROTECTION PROGRAM THAT INCLUDES AT LEAST: MEDICAL CERTIFICATION, TRAINING, FIT-TESTING, PERIODIC ENVIRONMENTAL MONITORING, MAINTENANCE, INSPECTING, CLEANING AND CONVENIENT, SANITARY STORAGE AREAS.

Ventilation:PROVIDE GENERAL OR LOCAL EXHAUST VENTILATION SYSTEMS.

Protective Gloves:WEAR CHEMICALLY PROTECTIVE GLOVES TO PREVENT PROLONGED OR REPEATED SKIN CONTACT

Eye Protection:WEAR PROTECTIVE EYEGASSES OR CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:MAKE EMERGENCY EYEWASH STATIONS, SAFETY/QUICK-DRENCH SHOWERS AND WASHING FACILITIES AVAILABLE IN WORK AREA. CONTAMINATED EQUIPMENT: LAUNDER BEFORE REUSE. REMOVE THIS MATERIAL FROM YOUR SHOES AND CLEAN

Work Hygienic Practices:NEVER EAT, DRINK OR SMOKE IN WORK AREAS.

PRACTICE GOOD PERSONAL HYGIENE AFTER USING THIS MATERIAL. ESPECIALLY BEFORE EATING, DRINKING, SMOKING USING THE TOILET, OR APPLYING COSMETICS.

Supplemental Safety and Health

EYE-PER OSHA EYE AND FACE PROTECTION REGULATIONS(29 CFR 1910.133) CONTACT LENSES ARE NOT EYE PROTECTIVE DEVICES. APPROPRIATE EYE PROTECTION MUST BE WORN INSTEAD OF, OR IN CONJUNCTION WITH CONTACT LENSES.

===== Physical/Chemical Properties =====

HCC:B3

Boiling Pt:>104.4C, 22

O.F

Melt/Freeze Pt: