

DYLON INDUSTRIES INC. -- GRADE E-855; LEAK DETECTOR -- 6850-00-543-7692

=====  
Product Identification  
=====

Product ID:GRADE E-855; LEAK DETECTOR

MSDS Date:12/06/1999

FSC:6850

NIIN:00-543-7692

Status Code:A

MSDS Number: CKGPK

=== Responsible Party ===

Company Name:DYLON INDUSTRIES INC.

Address:7700 CLINTON RD

City:CLEVELAND

State:OH

ZIP:44144

Country:US

Info Phone Num:216-651-1300(800)237-8246

Eme

rgency Phone Num:800-535-5053 (INFOTRAC)

Resp. Party Other MSDS Num.:GRADE E-855

Preparer's Name:ROBERT M.HUMRICK

CAGE:64040

=== Contractor Identification ===

Company Name:DYLON INDUSTRIES INC

Address:7700 CLINTON ROAD

Box:City:CLEVELAND

State:OH

ZIP:44144

Country:US

Phone:216-651-1300

CAGE:64040

Company Name:MEXPAR INTL, INC

Address:532 W. FOOTHILL BLVD

Box:City:AZUSA

State:CA

ZIP:91702

Country:US

Phone:626-812-6211

Contract Num:SP0450-00-M-D882

CAGE:0P0U1

=====  
Composition/Informatio

n on Ingredients =====

Ingred Name:1,3,5-TRIAZINE-1,3,5(2H,4H,6H)-TRIETHANOL OR BIOCID  
CAS:4719-04-4  
RTECS #:XZ1600000  
&lt; Wt:.1

===== Hazards Identification =====

LD50 LC50 Mixture:TLV=10MG/M3(TOTAL DUST),5MG/M3(RESPIRABLE DUST)  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE EXPOSURE: CONTACT MAY CAUSE EYE  
OR SKIN IRRITATION. CHRONIC EXPOSURE: UNKNOWN

Explanation of Carcinogenicity:CHEMICAL LISTED AS CARCINOGEN OR  
POTENTIAL CARCINOGEN: NONE.  
Effects of Overexposure:SKIN/EYE IRRITATION.  
Medical Cond Aggravated by Exposure:UNKNOWN.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IF  
NECESSARY. EYES: FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR 15  
MINUTES. CONSULT PHYSICIAN. SKIN: WASH WITH WARM SOAPY WATER. WASH  
CONTAMINATED CLOTHES BEFORE REUSE. INGESTION: DO NOT INDUCE  
VOMITING! OBTAIN MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:MATERIAL NOT FLAMMABLE. DLA-HMIS: USE EXTINGUISHING  
AGENT SUITABLE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:NONE. DLA-HMIS SUGGESTS TO USE A  
SELF-CONTAINED BREATHING APPARATUS WHENEVER FIGHTING A CHEMICAL  
FIRE.  
Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures

=====

Spill Release Procedures:TREAT AS A LUBRICATING OIL SPILL. ABSORB WITH CLAY OR DIATOMACEOUS EARTH.

Neutralizing Agent:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING.KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.AVOID CONTAMINATION WITH DIRT AND OTHER FOREIGN MATTER.

Other Precautions:RESPIRATORY PROTECTION SHOULD BE USED WHEN ENTERING AREAS CONTAINING RESPIRABLE DUST/MIST IN CONCENTRATIONS ABOVE THE THRESHOLD LIMIT VALUE (TLV) FOR NUISANCE DUSTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED DUST/MIST MASK IN AREA WHERE RESPIRABLE PARTICLES EXCEED TLV FOR NUISANCE DUST.

Ventilation:NORMAL PLANT VENTILATION. LOCAL EXHAUST/MECHANICAL (GENERAL): NOT NORMALLY NEEDED.

Protective Gloves:WORK GLOVES, RUBBER, NEOPRENE.

Eye Protection:SAFETY GOGGLES.

Other Protective Equipment

:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Work Hygienic Practices:LAUNDRY WORK CLOTHES BEFORE REUSE.

Supplemental Safety and Health

NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Boiling Pt:=100.C, 212.F

Vapor Density:>1

Spec Gravity:1

pH:8-10

Evaporation Rate & Reference: