

OPTIMA BATTERIES INC -- 34/78-1050 ENGINE STARTING BATTERIES (GROUP 34) --
6140-01-457-4339

=====
===== Product Identification =====

Product ID:34/78-1050 ENGINE STARTING BATTERIES (GROUP 34)

MSDS Date:12/09/1999

FSC:6140

NIIN:01-457-4339

Status Code:A

MSDS Number: CKGPM

=== Responsible Party ===

Company Name:OPTIMA BATTERIES INC

Address:17500 E 22ND AVENUE

City:AURORA

State:CO

ZIP:80011

Country:US

Info

Phone Num:303-448-8899/448-8899

Emergency Phone Num:(800)424-9300

Resp. Party Other MSDS Num.:OBI-0001D

Chemtrec Ind/Phone:(800)424-9300

CAGE:0UJ55

=== Contractor Identification ===

Company Name:OPTIMA BATTERIES INC

Address:17500 E 22ND AVENUE

Box:City:AURORA

State:CO

ZIP:80011

Country:US

Phone:303-448-8899 OR 800-292-4359

CAGE:0UJ55

=====
===== Composition/Information on Ingredients =====

Ingred Name:LEAD COMPOUNDS

CAS:7439-92-1

RTECS #:OF7525000

Minimum % Wt:63.

Maximum % Wt:81.

ACGIH TLV:0.15 MG/M3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:SULFURIC ACID ELECTROLYTE

CAS:7664-93-9

RTECS #:WS5600000

Minumum % Wt:17.

Maxumum % Wt:25.

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3

ACGIH STEL:3 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:POLYPROPYLENE CASE MATERIAL

CAS:9003-07-0

RTECS #:UD1842000

Minumum % Wt:2.

Maxumum % Wt:6.

Ingred Name:SEPARATOR/PASTER PAPER FIBROUS GLASS

CAS:65997-17-3

Code:F

Minumum % Wt:1.

Maxumum % Wt:4.

=====
entification =====

LD50 LC50 Mixture:NONE STATED BY MANUFACTURER

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONE EXPECTED FOR FINISHED PRODUCT

UNDER NORMAL CONDITIONS OF USE. IN ITS MANUFACTURED AND SUPPLIED STATE, THE PRODUCT IS CONSIDERED NON-HAZARDOUS. KEEP AWAY FROM FLAMES DURING AND IMMEDIATELY AFTER C HARGE. NO SIGNIFICANT HEALTH EFFECTS ARE ASSOCIATED WITH THE

PRODUCT.

Explanation of Carcinogenicity:NOT APPLICABLE FOR FINISHED PRODUCT

UNDER NORMAL CONDITIONS OF USE.

Effects of Overexposure:NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE.

Medical Cond Aggravated by Exposure:NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE.

=====
First Aid Measures =====

First Aid:NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE. INHALED-IF ACID VAPOR RELEASED, R

REMOVE PERSON TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER ARTIFICIAL RESPIRATION/ OXYGEN. SEE K MEDICAL ATTENTION. EYES-IF ELECTROLYTE ENTERS EYES, FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK PROMPT MEDICAL ATTENTION. SKIN-IF ELECTROLYTE CONTACTS SKIN, FLUSH WITH MILD SOAP & WATER. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS. INGESTION- SEEK PROMPT MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Extinguishing Media:MU

LTI PURPOSE DRY CHEMICAL OR MULTIPURPOSE CARBON DIOXIDE (CO2).

Fire Fighting Procedures:BATTERY WILL BURN IF INVOLVED IN A FIRE.

EVACUATE AREA. SELF-CONTAINED BREATHING APPARATUS MUST BE WORN TO PREVENT POSSIBLE INHALATION OF ACID MISTS, SMOKE AND DECOMPOSITION PRODUCTS IN A FIRE. REMOVE ALL IGNITION SOURCES. COOL BATTERY (S) TO PREVENT RUPTURE.

Unusual Fire/Explosion Hazard:HYDROGEN GAS MAY BE PRODUCED AND MAY EXPLODE IF IGNITED. REMOVE ALL IGNITION SOURCES. VENTILATE AREA.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID CONTACT WITH ACID MATERIALS. USE SODA ASH, BAKING SODA OR LIME TO NEUTRALIZE ACID IF RELEASED.

Neutralizing Agent:SODA ASH, BAKING SODA, LIME.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT CARRY BATTERY BY TERMINALS. DO NOT DROP BATTERY, PUNCTURE OR ATTEMPT TO OPEN BATTERY CASE. KEEP AWAY FROM FLAMES DURING AND IMMEDIATELY AFTER CHARGE. AVOID

PROLONGED OVERCHARGES IN CONFINED AREAS. STORE AT AMBIENT ROOM

TEMPERATURE. DO NOT SUBJECT PRODUCT TO OPEN FLAME OR FIRE.

Other Precautions:AVOID CONDITIONS WHICH COULD CAUSE ARCING BETWEEN BATTERY TERMINALS. WASH HANDS THOROUGHLY BEFORE EATING OR SMOKING AFTER HANDLING BATTERIES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Ventilation:

NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Protective Gloves:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Eye Protection:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Other Protective Equipment:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Work Hygienic Practices:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Supplemental Safety and Health

THE OPTIMA SEALED LEAD ACID BATTERY IS CONSIDERED AN ARTICLE AS DEFINED

BY 29 CFR 1910.1200 (C) OSHA HAZCOM. THE INFORMATION ON THIS SHEET IS SUPPLIED AT THE CUSTOMER'S REQUEST FOR INFORMATION ONLY.

BY 29 CFR 1910.1200 (C) OSHA HAZCOM. THE INFORMATION ON THIS SHEET IS SUPPLIED AT THE CUSTOMER'S REQUEST FOR INFORMATION ONLY.

===== Physical/Chemical Properties =====

HCC:Z4

Appearance and Odor:SEALED LEAD ACID BATTERY.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE STATED BY MANUFACTURER.

Stability Condition to Avoid:AVOID SHORTING, USE ONLY APPROVED CHARGING

METHODS. DO NOT PUNCTURE BATTERY CASE.

Hazardous Decomposition Products:NONE STATED BY MANUFACTURER.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Toxicological Information =====

Toxicological Information:THRESHOLD LIMIT VALUE: NONE APPLICABLE FOR FINISHED PRODUCT. ROUTE OF ENTRY: NONE APPLICABLE FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE. SIGNS OF SYMPTOMS OF ACUTE EXPOSURE: NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL

CONDITIONS OF USE. CHRONIC EXPOSURE: NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE. EFFECTS OF OVEREXPOSURE, CONDITIONS TO AVOID: NO EXPOSURE EXPECTED FOR FINISHED PRODUCT.HOWEVER, DO NOT PUNCTURE OR OPEN BATTERY CASE. ACID ELECTROLYTE MAY BE RELEASED, WHICH IS CORROSIVE..

===== Ecological Information =====

Ecological:NONE STATED BY MANUFACTURER.

===== Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS. SEND TO A LEAD RECYCLING FACILITY WHICH FOLLOWS APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS FOR ROUTINE DISPOSAL OF SPENT OR DAMAGED BATTERIES. THE DISTRIBUTOR/USER IS RESPONSIBLE FOR ROUTINE DISPOSITION OF SPENT OR DAMAGED BATTERIES.

===== MSDS Transport Information =====

Transport Information:SEALED LEAD ACID BATTERY IS NOT A US DOT

HAZARDOUS MATERIAL. UNDER DANGEROUS GOODS REGULATIONS, 38TH EDITION, EFFECTIVE JANUARY 1, 1997, PRODUCED BY INTERNATIONAL AIR TRANSPORTATION ASSOCIATION (IATA) : OPTIMA BATTERIES ARE CLASSIFIED AS NON-REGULATED BY SPECIAL PROVISIONS A-48 AND A-67 FOR UN2800. UNDER 49 CFR, MARCH 1, 1998 EDITION, OPTIMA BATTERIES ARE CLASSIFIED AS AN EXCEPTION FROM ALL OTHER REQUIREMENTS OR CONDITIONS AS STATED IN: BATTERIES WET, 173.159 (D)(3(I)[VIBRATION TEST], & (D)(3(II)[PRESSURE DIFFERENTIAL TEST]. THESE CONDITIONS HAVE BEEN TESTED & CERTIFIED.

===== Regulatory Information =====

SARA Title III Information:NONE STATED BY MANUFACTURER.

Federal Regulatory Information:ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD, SEALED LEAD ACID BATTERY IN ITS MANUFACTURED AND SUPPLIED STATE IS CONSIDERED NON-HAZARDOUS.

State Regulatory Information:NONE STATED BY MANUFACTURER.

===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their parti

cular situation.