

PARKER-HANNIFIN CORP SEAL GROUP O-RING DIVISION -- 884-4 PARKER O-LUBE --
9150-01-081-8788

===== Product Identification =====

Product ID:884-4 PARKER O-LUBE

MSDS Date:02/01/1996

FSC:9150

NIIN:01-081-8788

Status Code:A

MSDS Number: CKHJW

=== Responsible Party ===

Company Name:PARKER-HANNIFIN CORP SEAL GROUP O-RING DIVISION

Address:2360 PALUMBO DRIVE

Box:11751

City:LEXINGTON

State:KY

ZIP:40509

Coun

try:US

Info Phone Num:606-269-2351

Emergency Phone Num:606-269-2351

CAGE:02697

=== Contractor Identification ===

Company Name:PARKER-HANNIFIN CORP SEAL GROUP O-RING DIVISION

Address:2360 PALUMBO DRIVE

Box:11751

City:LEXINGTON

State:KY

ZIP:40509

Country:US

Phone:606-269-2351

CAGE:02697

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC OR
PETROLEUM NAPHTHENIC OIL

CAS:64742-52-5

RTECS #:PY8035000

Minimum % W

t:70.
Maxumum % Wt:75.

Ingred Name:BARIUM, ACETATE TALLOW FATTY ACIDS COMPLEXES OR BARIUM
SOAP-INSOLUBLE
CAS:68201-19-4
Minumum % Wt:25.
Maxumum % Wt:30.

=====
Hazards Identification
=====

LD50 LC50 Mixture:NO DATA PROVIDED BY RESPONSIBLE PARTY.
Health Hazards Acute and Chronic:EYES: MODERATE IRRITATION, REDNESS,
TEARING. SKIN: SLIGHT IRRITATION. SWALLOWING: GASTRIC INTESTINAL
IRRITATION, NAUSEA, VOMITING & DIARRHEA. INHALATION: NONE KNOWN.
Explan
ation of Carcinogenicity:NO DATA PROVIDED BY RESPONSIBLE PARTY.
Effects of Overexposure:EYES: MODERATE IRRITATION, REDNESS, TEARING.
SKIN: SLIGHT IRRITATION. SWALLOWING: GASTRIC INTESTINAL IRRITATION,
NAUSEA, VOMITING & DIARRHEA
Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY RESPONSIBLE
PARTY.

=====
First Aid Measures
=====

First Aid:INGESTION: IMMEDIATELY DRINK 2 GLASSES WATER. SEEK MEDICAL
ATTENTION. EYES: FLUSH WITH LARGE AMOUNT
S OF WATER, LIFT EYELIDS
OCCAISIONALLY. SEEK MEDICAL ATTENTION. SKIN: WASH EXPOSED AREA WITH
SOAP AND WATER. INHALATION: N/A.

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:=223.9C, 435.F
Extinguishing Media:CARBON DIOXIDE, FOAM AND DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER
OR FOAM MAY CAUSE FROTHING, WHICH CAN BE VIOLENT, ESPECIALLY IF
SPRAYED INTO CONTAINERS OF HOT BURING LIQU
ID.
Unusual Fire/Explosion Hazard:NEVER USE WELDINGOR CUTTING TORCH ON OR
NEAR (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE
EXPLOSIVELY.

=====
Accidental Release Measures
=====

Spill Release Procedures:SMALL SPILL: COLLECT IN BEAKER. LARGE SPILL:
PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM
SPILL AREA. SHOVEL MATERIAL INTO CONTAINER. REMAINING MATERIAL
TAKEN UP WITH ABSORBENT MAT ERIAL.
Neutralizing Agent:NO DAT

