

U.S. DEPARTMENT OF LABOR -- AGE-MASTER #1 (TM) RUBBER PROTECTANT

=====
MSDS Safety Information
=====

FSC: 8030
NIIN: 01-314-2215
MSDS Date: 01/01/1996
MSDS Num: CKHXC
Product ID: AGE-MASTER #1 (TM) RUBBER PROTECTANT
MFN: 04
Responsible Party
Cage: 62692
Name: U.S. DEPARTMENT OF LABOR
Address: 9215 HILLVIEW DR. CLARENC
E, NEW YORK 14031
Box: 213
City: CLARENCE NY 14031
Info Phone Number: 716-741-2079
Emergency Phone Number: 716-741-2079
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: DO116
Name: CHEM-PRO MANUFACTURING CO,INC
Address: 9215 HILLVIEW DRIVE
City: CLARENCE NY 14031
Phone: 716-741-2079
Cage: 62692
Name: U.S. DEPARTMENT OF LABOR
Address: 9215 HILLVIEW DR. CLARENCE,
NEW YORK 14031
Box: 213
City: CLARENCE NY 14031
Phone: 716-741-2079

=====
Item Description Information
=====

Item Name: PRESERVATIVE COATING,RUBBER
Specification Number: MIL-P-11520
Type of Container: CAN

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards Data
=====

Effects of Exposure: INGESTION: NAUSEA, VOMITING, DIARRHEA, GASTROINTESTINAL IRRITATION. EYES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DERMATITIS TO CERTAIN INDIVIDUALS. INHALATION: RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, HEADACHE, FATIGUE.

Explanation Of Carcinogeni

city: NOT LISTED AS A POTENTIAL CARCINOGEN IN OSHA, EPA, RCRA, NTP, OR IARC.

Signs And Symptions Of Overexposure: HEADACHE, DIFFICULTY OF BREATHING, NAUSEA, FATIGUE, NOSE AND THROAT IRRITATION, DIZINESS.

First Aid: INHALATION: REMOVE PERSON TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM. SKIN CONTACT: REMOVE PRODUCT FROM SKIN WITH WATERLESS SOAP, WIPE OFF CLEAN, THEN FOLLOW WITH WARM WATER AND REGULAR SOAP. EYES: FLUSH AFFECTED EYE WITH WATER FOR 15 MINUTES
. OBTAIN MEDICAL CARE.

=====
Handling and Disposal
=====

Spill Release Procedures: STANDARD PROCEDURES FOR HYDROCARBON SPILLS APPLY TO THIS PRODUCT. USE OIL ABSORBENT MATERIAL TO CLEAN SPILLAGE. REMOVE ALL SOURCES OF IGNITION. WORK FROM UP-WIND SIDE OF SPILLAGE AREA. THTRANSFER W ET ABSORBENT INTO CONTAINER FOR DISPOSAL. PREVENT FLOW OF LIQID INTO WATERWAY OR SEWER. USE FLOATING ABSOR BENT TO REMOVE LIQUID FROM WATER.

Waste Disposal Methods: INCINERATE AS SOLID WASTE AT APPROVED STATE WASTE DISPOSAL PLANTS. THE SAME FOR EMPTY DRUMS. REMOVE LIQUID FROM DRUMS WITH ABSORBENT, THEN DISPOSE AS SOLID WASTE.

Handling And Storage Precautions: KEEP FROM HEAT, SPARKS AND OPEN FLAMES. STORE TIGHTLY CLOSED IN WELL VENTILATED AREA. FOLLOW ESTABLISHED PLANT SAFETY REGULATIONS AND PROCEDURES FOR HANDLING COMBUSTIBLES (OSHA 1910)

Other Precautions: DO NOT USE NEAR WELDING EQUIPMENT , FLAMES AND SPARKS. USE ADEQUATE VENTILATION. IF ADEQUATE VENTILATION IS NOT AVAILABLE, PROVIDE FANS OR AIR SUPPLYING EQUIPMENT.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point: >61.7C, 143.F

Flash Point Text: 143-146F

Extinguishing Media: REGULAR FOAM, CARBON DIOXIDE OF DRY CHEMICAL

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS

WHEN FIGHTING

FIRES. VAPORS ARE HEAVIER THAN AIR AND MAY BE MOVED BY VENILATION AND IGNITED BY HEAT, PILOT LIGHTS, SPARKS OR FLAMES.

Unusual Fire/Explosion Hazard: LIQUID MAY DECOMPOSE TO POISONOUS GASSES OF CO, CO2, NOX AND SMOKE. (TM) INDICATES REGISTERED U.S. PATENT OFFICE & TRADE MARK OF CHEM-PRO INC.

Control Measures

Respiratory Protection: ORGANIC VAPOR RESPIRATOR A PPROVAL TC-23C-107 OR EQUIVALENT.

Ventilation: LOCAL EXHAUST: RECOMMENDED MECHANICAL (GENERAL) RECOMMENDED FOR CONFINED AREAS

Protective Gloves: NITRILE RUBBER-HEAVY DUTY.

Eye Protection: CHEMICAL WORKER'S GOGGLES OR FACE SHIELD.

Other Protective Equipment: CLOTHING OR EQUIPMENT: COVERALLS OR APRON. REMOVE STAINS FROM CLOTHING OR STAINED SURFACES USING CLEANING SOLVENT OR KEROSENE. FOLLOW WITH DILUTED CLOXOX TO REMOVE STAINS.

Work Hygienic Practices: WASH HANDS BEFORE EATING AND AT C OMPLETION OF WORK.

USE WATERLESS SOAP AND WIPE OFF HANDS. FOLLOW WITH REGULAR SOAP AND WARM WATER. DISPOSE SOILED CLOTHING.

Physical/Chemical Properties

Boiling Point: =204.4C, 400.F

B.P. Text: 204C

Vapor Pres: 2.6 @ 20'C

Vapor Density: 5.4

Spec Gravity: 16/16 C 0.8236

Evaporation Rate & Reference: SLOWER

Solubility in Water: INSOLUBLE/NIL

Appearance and Odor: DARK REDISH

- BROWN

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: MAY FORM TOXIC MATERIALS: CO, CO2, NOX, VARIOUS HYDROCARBONS.

Hazardous Polymerization Indicator: NO

Toxicological Information

Toxicol

ogical Information: THE PRODUCT AND ITS INGREDIENTS ARE NOT LISTED IN THE HAZARDOUS MATERIALS LIST AND ARE NOT LISTED AS POTENTIAL CARCINOGENS IN OSHA REGULATIONS 29 CFR 1910, TITLE III OF SARA , EPA, RCRA,NTP,IARC, OR EXTREMELY HAZARDOUS SUBSTANCE OR TOXIC CHEMICAL AS DEFINED IN SECTION 302 (A) (2) AND 313 (C) OF FEDERAL REGISTER 52 FR (13378-12410 AND 347983). COMPLIES WITH CLEAN AIR QUALITY REGULATIONS TITLE 6 OF N.Y., AND SCAQMD RULES 442 AND 66. IMDG PROPER SHIPPING NAME: PETROLEUM DISTILLATE N.O.S. - UN-1268 LTD/QTY V.O.C : 0.8 GM/L ; 0.01 LB/GL

MSDS Transport Information

Transport Information: IMDG PROPER SHIPPING NAME: PETROLEUM DISTILLATE N.O.S. - UN- 1268 LTD/QTY DOT PROPER SHIPPING NAME: COMBUSTIBLE LIQUID N.O.S. NA-1993 (NOT A RED LABEL ITEM)

Regulatory Information

Sara Title III Information: THE PRODUCT AND ITS INGREDIENTS ARE NOT LISTED IN THE HAZARDOUS MATERIALS LIST AND ARE NOT LISTED AS POTENTIAL CARCINOGENS IN OSHA REGULATIONS 29 CFR 1910, TITLE III OF SARA , EPA, RCRA,NTP,IARC, OR EXTREMELY HAZARDOUS SUBSTANCE OR TOXIC CHEMICAL AS DEFINED IN SECTION 302 (A) (2) AND 313 (C) OF FEDERAL REGISTER 52 FR (13378-12410 AND 347983). COMPLIES WITH CLEAN AIR QUALITY REGULATIONS TITLE 6 OF N.Y., AND SCAQMD RULES 442 AND 66.

Other Information

Other Information: RATING: HEALTH: 2, FLAMMABILITY: 2, REACTIVITY: 0

HAZCOM Label

Product ID: AGE-MASTER #1 (TM) RUBBER PROTECTANT

Cage: 62692

Company Name: U.S. DEPARTMENT OF LABOR

Street: 9215 HILLVIEW DR. CLARENCE, NEW YORK 14031

PO Box: 213

City: CLARENCE NY

Zipcode: 14031

Health Emergency Phone: 716-741-2079

Label Required IND: Y

Date Of Label Review: 04/18/2000

Status Code: A

Origination Code: G

Hazard And Precautions: INGESTION: NAUSEA, VOMITING, DIARRHEA, GASTROINTESTINAL IRRITATION. EYES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DERMATITIS TO CERTAIN INDIVIDUALS. INHALATION: RESPIRATORY IRRITATION, DIZZINE

SS, NAUSEA, HEADACHE, FATIGUE.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or person

s contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.