

GRYPHIN COMPANY, INC -- DARK WALNUT TT-S-711C STAIN, OIL TYPE, WOOD INTERIOR --
8010-00-281-2076

===== Product Identification =====

Product ID:DARK WALNUT TT-S-711C STAIN, OIL TYPE, WOOD INTERIOR

MSDS Date:08/09/1994

FSC:8010

NIIN:00-281-2076

Status Code:A

MSDS Number: CKJMZ

=== Responsible Party ===

Company Name:GRYPHIN COMPANY, INC

Address:RICHMOND AND TIOGA STREETS

City:PHILADELPHIA

State:PA

Z

IP:19134

Country:US

Info Phone Num:215-739-6172

Emergency Phone Num:215-426-5976

CAGE:0E5W3

=== Contractor Identification ===

Company Name:GRYPHIN COMPANY, INC

Box:5910

City:PHILADELPHIA

State:PA

ZIP:19119

Country:US

Phone:800-482-1886

Contract Num:8S-10F-52833

CAGE:0E5W3

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC HYDROCARBON (VAPOR PRESSURE 2 MM HG)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 50-75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL

:100 PPM
ACGIH TLV:100 PPM

Ingred Name:LINSEED OIL VAPOR PRESSURE: 0
CAS:67746-08-1
Fraction by Wt: 5-20%

Ingred Name:RAW UMBER
CAS:12713-03-0
Fraction by Wt: 1-5%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: BREATHING OF VAPORS MAY CAUSE
NOSE, THROAT, RESP TRACT IRRITATION. PROLONGED EXPOSURE: HEADACHE,
NAUSEA,
DIZZINESS, LOSS OF COORDINATION. CONCENTRATING & INHALING
VAPORS MAY BE HARMFUL OR FAT AL. SKIN: EXPOSURE TO MATERIAL LIQUID
OR VAPOR: SKIN IRRITATION. PROLONGED/REPEATED EXPOSURE: BURNING,
REDNESS, DRYING, DERMATITIS. INGESTION: DIGESTIVE TRACT IRRITATION,
& CAN ENTER LUNGS CAUSING VOM ITING & LUNG DAMAGE. EYE: IRRITATION,
INCLUDING BURNING, TEARING, REDNESS.

=====
First Aid Measures
=====

First Aid:INHAL: IF OVERCOME BY VAPOR REMOVE
INTO FRESH AIR. CALL DR
IMMED. IF BREATHING IRREGULAR OR HAS STOPPED, START RESUCITATION &
GIVE OXYGEN. SKIN: REMOVE ANY CONTAMINATED CLOTHING & WASH SKIN
WITH MILD SOAP & WATER IMMED. CONSULT DR IF IRRITATION PERSISTS.
INGEST: DO NOT INDUCE VOMITING. CALL DR & POISON CTR IMMED. EYE:
FLUSH WITH CLEAR WATER FOR 15 MIN OR UNTIL IRRITATION SUBSIDES. IF
IRRITATION PE RSISTS, CALL DR.

=====
Fire Fighting Measures
=====

Flash Point Method:T
CC
Flash Point:=37.8C, 100.F
Lower Limits:0.9
Extinguishing Media:WATER FOG, FOAM, CARBON DIOXIDE, DRY CHEMICAL
Fire Fighting Procedures:SCBA,COMPLETE PERSONAL PROTECTIVE EQUIPMENT &
CLOTHING. AVOID SPREADING BURNING LIQUID W/H2O. FIGHT FIRE FROM
SAFE DISTANCE. CLOSE ALL VALVES TO AREA. SHUT OFF ALL POWER TO
AREA. TURN ON EMERGENCY LIG HTS. COOL CTNR W/H2O SPRAY. USED
SUPPLIED AIR BREATHING EQUIPMENT FOR ENCLOSED AREAS. LIQUID
IRRITATING TO EYES/SKIN.
Unusual Fire/Explosion H

azard:VAPOR/DUST MAY FORM EXPLOSIVE MIXTURE IN
AIR. VAPOR>AIR; MAY TRAVEL, IGNITE/FLASH BACK. DANGEROUS WHEN
HEATED. CLOSED CNTNR MAY EXPLODE W/HEAT. EMPTY PRODUCT CNTR RETAIN
PRODUCT RESIDUE. DONT WELD, CU T,EXPOSE EMPTY CNTNR TO FLAME OR
SPARK-MAY EXPLODE CAUSING INJURY OR DEATH. EXTREMELY FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH SAND & DISPOSE OF IN APPROVED
MANNER. REMOVE ALL SOURCES OF IGNITION.
DIKE AREA WITH SAND TO
CONTAIN SPILLED LIQUID. WEAR PROTECTIVE CLOTHING. KEEP SOURCES OF
IGNITION & HOT, METAL SURFACE S ISOLATED FROM SPILL OR PRODUCT
CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:OVERHEATING MAY CAUSE CONTAINER TO
RUPTURE. USE EXPLOSION-PROOF ELECTRICAL EQUIPMENT. MUST BE KEPT IN
COVERED AREA. AVOID CONTACT WITH SKIN OR CLOTHES

Other Precautions:KEEP CNTNR CLSD. CHECK CNTNRS FOR LEAK. WEA
R PROTECT

CLOTHING. DON'T STACK CNTNR >2 HIGH. AVOID PROLONGED
BREATHING/CONTACT W/ SKIN. GROUND CNTNRS WHEN POURING/TRANSFERRING.
CHANGE CLOTHES & WASH HANDS BEFORE EATING, DRINKING, SMOKING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED GAS MASK OR RESPIRATOR.

Ventilation:USE WITH ADEQUATE VENTILATION. EXHAUST AT POINT OF USE.

Protective Gloves:GLOVES IMPERVIOUS TO SOLVENTS

Eye Protection:SAFETY OR SPLASH GOGGLES, FA
CE SHIELD

Other Protective Equipment:EYEWASH STATION, EMERGENCY SHOWER,
IMPERMEABLE APRONS.

Work Hygienic Practices:CHANGE CLOTHES AND WASH HAND THOROUGHLY BEFORE
EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:277 - 410 F

Melt/Freeze Pt:M.P/F.P Text:WILL NOT FREEZE

Vapor Density:> AIR

Spec Gravity:0.88

VOC Grams/Liter:4.46

Viscosity:10 - 25 SEC. #4FORD CUP

Evaporation Rate & Refe

rence: SLOWER THAN N-BUTYL ACETATE

Solubility in Water: