

DURANT PAINTS INC -- TT-E-2784A, ACRILIC EMUNSION, ENAMEL, COLOR 11105, RED --  
8010-01-333-9813

=====  
===== Product Identification =====

Product ID:TT-E-2784A, ACRILIC EMUNSION, ENAMEL, COLOR 11105, RED

MSDS Date:03/01/1998

FSC:8010

NIIN:01-333-9813

Status Code:A

MSDS Number: CKJPC

=== Responsible Party ===

Company Name:DURANT PAINTS INC

Address:112 RAILROAD ST

City:REVERE

State:MA

ZIP:02151-4007

Count

ry:US

Info Phone Num:781-289-8415

Emergency Phone Num:781-289-8415

CAGE:3F338

=== Contractor Identification ===

Company Name:DURANT PAINTS INC

Address:112 RAILROAD ST

Box:City:REVERE

State:MA

ZIP:02151-4007

Country:US

Phone:781-289-8415

CAGE:3F338

=====  
===== Composition/Information on Ingredients =====

Ingred Name:GLYCOL ETHER \* PERCENT BY VOL.: 4.34; LEL: 1.4; VAPOR PRES:  
.25

RTECS #:GE1008782

= Wt:3.35

Ingred Name:GLYCOL ETHER; \* PERCENT BY VOL: 1.20; LEL: .7; VAPOR PRES:

.01  
CAS:770-35-4  
= Wt:1.03

Ingrd Name:PROPYLENE GLYCOL \* PERCENT BY VOL: 2.35; LEL: NA; VAPOR  
PRESS: .55  
CAS:57-55-6  
RTECS #:TY2000000  
= Wt:1.61  
OSHA PEL:NA

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Effects of Overexposure:EYES: LIQUID OR VAPOR CONTACT CAN CAUSE PAINFUL  
EYE IRRITATION. SKIN; CONTACT CAN BE MILDLY IRRITATING, AVOID  
EXCESSIVE CONTACT. INHALATION: VAPORS CAN BE IRRITATING TO NOSE  
AND THROAT. SYMPTOMES OF OVEREXPOSURE MAY INCLUDE HEADACHE,  
NAUSEA, VOMITING.  
Medical Cond Aggravated by Exposure:HEART CONDITION, ASTHMA.

=====  
===== First Aid Measures =====

First Aid:5. === Fire Fighting Measures ===  
Extinguishing Media:CO2 FOAM.  
Fire Fighting Procedures:DO NOT ENTER CONCINED FIRE SPACE WITHOUT FULL  
PROTECTIVE GEAR.  
Unusual Fire/Explosion Hazard:COOL CONTAINRS WITH WATER STREAM IN THE  
EVENT OF FIRE.

=====  
===== Accidental Release Measures =====

Neutralizing Agent:

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL DRY PLACE, PROTECT  
FROM FREEZING.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:PROTECTION, REQUIRED.  
Ventilation:REQUIRED.  
Protective Gloves:REQUIRED  
Eye Protection:REQUIRED  
Other Protective Equipment:APRON  
Work Hygienic Practices:WASH AFTER HANDLING  
Supplemental

## Safety and Health

### ===== Physical/Chemical Properties =====

Boiling Pt:=100.C, 212.F

B.P. Text:212F

Vapor Density:>AIR

VOC Grams/Liter:1.61

Solubility in Water:100%

Appearance and Odor:LIQUID

Percent Volatiles by Volume:59.69

### ===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID HEAT, SPARKS, AND OPEN FLAME.

Hazardous Decomposition Products:CARBON MO

NOXIDE AND UNIDENTIFIED

ORGANIC COMPOUNDS.

### ===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN APPROVED FACILITY.

### ===== MSDS Transport Information =====

Transport Information:OSHA; NONFLAMABLE. DOT: NONFLAMABLE

### ===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of t

he Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.