

ROBERT MCKEOWN CO. -- 730 SOLVENT RESISTANT SEALANT -- 8030-00-251-2312

=====  
Product Identification  
=====

Product ID:730 SOLVENT RESISTANT SEALANT

MSDS Date:04/26/1994

FSC:8030

NIIN:00-251-2312

Status Code:A

MSDS Number: CKMPC

==== Responsible Party ====

Company Name:ROBERT MCKEOWN CO.

Address:111 CHAMBERS BROOK RD.

City:BRANCHBURG

State:NJ

ZIP:08876

Country:US

Info Phone Num:908-218-9000

Emergenc

y Phone Num:(800)424-9300

Chemtrec Ind/Phone:(800)424-9300

CAGE:7B953

==== Contractor Identification ====

Company Name:MCKEOWN ROBERT CO. INC.

Address:111 CHAMBERS BROOK RD.

Box:City:SOMERVILLE

State:NJ

ZIP:08876

Country:US

Phone:908-218-9000

CAGE:7B953

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VINYLTRIACETOXYSILANE

CAS:4130-08-9

= Wt:6.

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

= Wt:7.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:

TRIMETHYLATED SILICA

CAS:68909-20-6

= Wt:7.

Ingred Name:ACETIC ANHYDRIDE

CAS:108-24-7

RTECS #:AK1925000

= Wt:.2

OSHA PEL:5 PPM

ACGIH TLV:5 PPM CEILING

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TRIFLUOROPROPYLMETHYLCYCLOTTRISILOXANE

CAS:002374-14-3

= Wt:2.

=====  
===== Hazards Identification =====

Health Hazards Acute and Chronic:EYE: DIRECT CONTACT IRRITATES  
MODERATELY WITH REDNESS AND SWELLING. SKIN: A SINGLE SHORT EXPOSURE  
(LESS THAN 24 HOURS)

MAY IRRITATE. REPEATED OR PROLONGED CONTACT  
(24 TO 48 HOURS) MAY IRRITATE MODERATELY. REPEATED SKIN CONTACT  
MAY CAUSE ALLERGIC SKIN SENSITIZATION. INHALATION: VAPOR  
OVEREXPOSURE MAY IRRITATE EYES, NOSE AND THROAT. ORAL: SMALL AMOUNTS  
TRANSFERRED TO MOUTH BY FINGERS DURING USE ETC. SHOULD NOT INJURE.  
SWALLOWING LARGE AMMOUNTS MAY INJURE SLIGHTLY.

Effects of Overexposure:ORAL: SMALL AMOUNTS TRANSFERRED TO MOUTH BY  
FINGERS DURING USE ETC. SHOULD NOT INJURE. SWALLOWING LARG

E  
AMMOUNTS MAY INJURE SLIGHTLY.

=====  
===== Fire Fighting Measures =====

Flash Point:>101.1C, 214.F

Extinguishing Media:CARBON DIOXIDE (CO2), WATER, WATER FOG (OR SPRAY),  
DRY CHEMICAL, FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING  
CHEMICALS. EVACUATE AREA IN CASE OF OVERHEATING OR FIRE.

Unusual Fire/Explosion Hazard:THIS MATERIAL MAY FORM HIGHLY TOXIC  
VAPORS OF

TRIFLUOROPROPIONALDEHYDE IF HEATED IN AIR ABOVE 300F.

PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE. PRODUCT EVOLVES ACETIC ACID (HOAC) WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL HOAC WITHIN EXPOSURE GUIDELINES.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP AND CONTAIN FOR SALVAGE OR DISPOSAL. OBSERVE ALL PERSONALPROTECTION EQUIPMENT RECOMMENDED. LOCAL, STATE AND FEDERAL REPORTING RE QUIRMENTS MAY APPLY TO SPILLS OR RELEASE OF THIS MATERIAL INTO THE ENVIORMENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED AND STORE AWAY FROM WATER OR MOISTURE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE ORGANIC VAPOR TYPE RESPIRATOR WHEN ADEQUATE VENTILATION IS NOT PROVIDED

Ventilation:LOCAL EXHAUST AND GENERAL VENTILATION RECOMMENDED

Protective Glov

es:CHEMICAL PROTECTIVE GLOVES RECOMMENDED

Eye Protection:SAFTEY GLASSES AS A MINIMUM

Work Hygienic Practices:WASH AT MEALTIME AND AT ENE OF SHIFT.

CONTAMINATED CLOTHING AND SHOES SHOULD BE REMOVED AS SOON AS PRATICAL AND THROUGHLY CLEANED BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:1.41

Solubility in Water:NONE

Appearance and Odor:WHITE PASTE ACETIC ACID ODOR

Percent Volatiles by Volume: