View NSN Online: https://aerobasegroup.com/nsn/8010-01-242-8160

CAAP CO INC -- CAAPCOAT 5-294 COLOR MATCHED LUSTERLESS POLYURTHANE TOPCOAT, -- 8010-01-242-8160

Product ID:CAAPCOAT 5-294 COLOR MATCHED LUSTERLESS POLYURTHANE TOPCOAT, MSDS Date:02/01/1994 FSC:8010 NIIN:01-242-8160 Status Code:A **MSDS Number: CKNNC** === Responsible Party === Company Name: CAAP CO INC Address:152 PEPE'S FARM RD City:MILFORD State:CT ZIP:06460 Countr y:US Info Phone Num:203-877-0375 Emergency Phone Num:202-483-7616 Chemtrec Ind/Phone:(800)424-9300 CAGE:60922 === Contractor Identification === Company Name: CAAP CO INC Address:152 PEPE'S FARM RD Box:City:MILFORD State:CT ZIP:06460 Country:US Phone:203-877-0375 CAGE:60922

Ingred Name:XYLENE CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 51% Other REC Limits:150PPM STEL OSHA PEL:100 PPM ACGIH TLV:100 PPM EPA Rpt Qty:1000 LB S DOT Rpt Qty:1000 LBS

Ingred Name: METHYL ISOBUTYL KETONE CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: 17% Other REC Limits:75PPM STEL OSHA PEL:50 PPM ACGIH TLV:50 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: RESIDUAL METHYLENE BIS (4-CYCLOHEXYLISOCYANATE) CAS:5124-30-1 RTECS #:HQ9250000 Fraction by Wt: 116.1C, 241.F B.P. Text:241-281F Vapor Pres:8 Vapor Density:3.66 Volatile Org Content %:652 Spec Gravity:0.996 Evaporation Rate & amp; Reference: 0.85 Solubility in Water: INSOLLU ABLE CO Appearance and Odor:LIGHT2DARK GRY, GRN LIQUID, AROMATIC SOLVENT ODOR

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:IGNITION SOURCES, HOT SURFACES, AND TEMPERATURES ABOVE 100 F (38 C).
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, AS WELL AS TRACES OF HCN MAY BE RELEASED DURING COMBUSTION.

Toxicological Information:FOR MORE COMPLETE HEALTH AND SAFETY INFORMATION ON THE USE OF COATINGS CONTAINING RESIFUAL ISOCYANATE PLEASE CONSULT MOBAY'S HELATH AND SAFETY INFORMATION BROCHURE. *CONTAIN THE SPILL WITH DIKES OF A BSORBENT MATERIAL AND SOAK UP THE SPILL WITH THE ABSORBENT MATERIAL. CLEAN UP THE ABSORBENT AND CONTAIN SECURELY. SWEEP AND WET MOP THE AFFEECTED AREA WITH SOAP AND WATER. VENTILATE THE AREA AS WEL L AS P OSSIBLE.

Ecological:**THE USER MUST BE FULLY PROTECTED FROM EXPOSURE TO THE MATERIAL DURING MIXING AND SPRAY APPLICATION. IF EXPOSURE MIGHT OCCUR A FULL PERMEATION RESISTANT PROTECTIVE SUIT INCLUDING HEAD COVERING, FA CE SHIELD, GLOVES, AND OVERSHOES IS

Waste Disposal Methods: INCINERATION IN AN APPROPRIATELY DESIGNED &LICENSED INCINERATOR

IS PREFERRED; THIS IS A RCRA HAZARDOUS IGNITABLE WASTE. REGULATIONS MAY VARY FROM STATE DISPOSE OF ACCORDING TO STATE, LOCAL, &FEDERAL REGULATIONS. WHEN THE 5-294-L &CURING AGENT ARE MIXED &THE SOLVENT IS ALLOWED TO EVAPORATE, THE SOL ID END PRODUCT IS A NON-HAZARDOUS LAND-ITEM.

Transport Information: PAINT RELATED MATERIAL DOT CLASSIFICATION: 3. (FLAMMABLE LIQUID).

====== Regulatory In

SARA Title III Information:XYLENE METHYLISOBUTYLKETONE; MBK GREEN CHROMIUM (III) OXIDE. COPPER PHTHALOCYANINE BLUE.

State Regulatory Information:THE FOLLOWING CHEMICAS ARE SPECIFICALLY LISTED BY INDIVIDUAL STATES: OTHER PRODUCT SPECIFIC HEALTH AND SAFETY DATA IN OTHER SECTIONS IN THIS MSDS MAY ALSO BE APPLICABLE FOR STATE REQUIREMNETS. FOR DET AILS ON YO9UR REGULATORY REQUIREMENTS, YOU SHOULD CONTACT THE APPROPRIATE AGENCY IN YOUR STATE.

MBK: MA, PA RIGHT TO KNOW. XYLENE: MA, PA, RIGHT TO KNOW. METHYLENE BIS(4-CYCLOHEXYLISOCYANATE): MA, NJ, PA RIGHT TO KNOW.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek compet ent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.