

PRC-DESOTO INTERNATIONAL,INC. -- PR 944F PART B -- 8030-01-279-9888

===== Product Identification =====

Product ID:PR 944F PART B

MSDS Date:02/16/1999

FSC:8030

NIIN:01-279-9888

Status Code:A

Kit Part:Y

MSDS Number: CKQPZ

=== Responsible Party ===

Company Name:PRC-DESOTO INTERNATIONAL,INC.

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-206

0

Emergency Phone Num:800-228-5635

Resp. Party Other MSDS Num.:MS2677A00

Chemtrec Ind/Phone:(800)424-9300

CAGE:92108

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

Contract Num:NOO1O4-98-D-A001

CAGE:83574

Company Name:PRC-DESOTO INTL INC

Address:5454 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91203

Country:US

Phone:818-240-2060/800-

228-5635
CAGE:92108

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE
CAS:1330-20-7
RTECS #:ZE2100000
< Wt:5.
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:651 MG/M3;150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:DIMERCAPTO DIOXAOCCTANE
CAS:14970-87-7
< Wt:5.

Ingred Name:CALCIUM CARBONATE LIMESTONE
CAS:1317-65-3
RTECS #:EV9580000
= Wt:40.
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:ISOPROPYL ALCOHOL
CAS:67-63-0
RTECS #:NT8050000
= Wt:5
. OSHA PEL:980 MG/M3;400 PPM
ACGIH TLV:983 MG/M3;400 PPM
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:2-PROPANOL, 1-METHOXY-, ACETATE
CAS:108-65-6
RTECS #:AI8925000
< Wt:5.

Ingred Name:MERCAPTAN TERMIN. POLYMER
CAS:119147-89-6

Ingred Name:DIISODECYL PHTHALATE
CAS:68515-49-1

Ingred Name:STEARIC ACID
CAS:57-11-4
RTECS #:WI2800000

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:ISOPROPYL ALCOHOL: EYES-IRRITANT.
SKIN-IRRITANT. INHALATIO

N-MAY CAUSE NOSE & THROAT IRRITATION.

INGESTION-MAY CAUSE COMA.

Effects of Overexposure:ISOPROPYL ALCOHOL: INHALATION-MAY CAUSE FLUSHING, HEADACHE, DIZZINESS, MENTAL DEPRESSION, NAUSEA, VOMITING, NARCOSIS ANESTHESIA AND COMA. INGESTION-MAY CAUSE HEADACHE, DIZIZNESS, MENTAL DEPRESSION, NA USEA, VOMITING, NARCOSIS, ANESTHESIA AND COMA.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSIST, CONSULT PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SYM PTOMS ARE PRESENT, CONSULT PHYSICIAN. INGESTION: CONSULT PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC

Flash Point:=22.2C, 72.F

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG

Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:HIGH TEMPERATURE MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINERS.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. WEAR AIR-SUPPLIED RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER WITH ABSORBANT. SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH A SUITABLE SOLVENT. CERCLA RQ FOR XYLENE IS 1 ,000 LBS.

=====
Handling and Storage
=====

Handling and Storage

Precautions:KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. DO NOT STORE ABOVE 120F.

Other Precautions:EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM. VAPORS OF THIS PRODUCT ARE HEAVIER THAN AIR AND MAY COLLECT IN LOW OR CONFINED AREAS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WHEN SPRAYING OR APPLYING IN ANY CIRCUMSTANCES LIK

ELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE AN ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL.

Protective Gloves:SOLVENT-RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:AVOID SKIN CONTACT BY USE OF OTHER PROTECTIVE CLOTHING. SAFETY SHOWERS, EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE.

Supplemental Safety and Health

ITEM IS A KIT: 3 PAIL 5 GAL PART A;

55 GAL DRUM GAL PART B (CONT 46.5

GAL). QUALITY ASSURANCE TESTED FOR SURFACE OR SUBMARINE USE SEALING COMPOUND: A CHEMICAL COMPOSITION FORMULATED FOR COATING OR FIL LING VOIDS, CRACK, JOINTS, SEAMS OF OBJECTS &/OR MATERIALS TO EXCLUDE FOREIGN MATTER &/OR PREVENT TRANSMISSION OF FLUID.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:180-527F

Vapor Density:>AIR

Spec Gravity:1.285

VOC Pounds/Gallon:180

Evaporation Rate & Referen

ce:UNAVAILABLE

Appearance and Odor:WHITE LIQUID

Percent Volatiles by Volume:14.5%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NOT KNOWN.

Stability Condition to Avoid:NOT KNOWN.

Hazardous Decomposition Products:OXIDES OF CARBON.

===== Toxicological Information =====

Toxicological Information:1,8-DIMERCAPTO-3,6-DIOXAOCANE: INGESTION:
MEDIAN ORAL LD50(RAT): 835 MG/KG.

===== Dis

posal Considerations =====

Waste Disposal Methods:EPA NO. D-001 HAZARDOUS WASTE. DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

===== MSDS Transport Information =====

Transport Information:D.O.T. HAZARD CLASS: NONE. PROPER SHIPPING NAME: NOT REGULATED UNDER 49 CFR.

===== Regulatory Information =====

SARA Title III Information:XYLENE: THESE ITEMS ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.

Federal Regulatory Information:ALL INGREDIENTS IN THIS PRODUCT ARE LISTED IN THE T.S.C.A. INVENTORY. CALCIUM CARBONATE LIMESTONE: THESE ITEMS ARE LISTED AS REQUIRED BY 29 CFR 1910:1200 BECAUSE THEY APPEAR ON AIRBORNE CONTAMINANTS LIST. HOWEVER, IN THIS PRODUCT THEY ARE IN FULLY ENCAPSULATED FORM & THEREFORE ARE NOT HAZARDOUS TO USERS UNDER NORMAL CIRCUMSTANCES.

IF THE CURED PRODUCT IS SANDED OR GROUNDED SO AS TO RELEASE RESPIRABLE PARTICLES, SUITABLE RESPIRATORY PROTECTION SHOULD BE USED.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.