

CENTURY LUBRICANTS CO -- AIRLUBE NR (ALL GRADES) -- 9150-01-180-2295

=====
Product Identification
=====

Product ID: AIRLUBE NR (ALL GRADES)

MSDS Date: 02/06/1998

FSC: 9150

NIIN: 01-180-2295

MSDS Number: CKRRB

=== Responsible Party ===

Company Name: CENTURY LUBRICANTS CO

Address: 2140 S 88TH STREET

City: KANSAS CITY

State: MO

ZIP: 66111-8701

Country: US

Info Phone Num: 800-800-6457

Emergency Phone Num: 800-80

0-6457

Resp. Party Other MSDS Num.: 475004-13

Preparer's Name: M.D. HART

CAGE: 12905

=== Contractor Identification ===

Company Name: CENTURY LUBRICANTS CO

Address: 2140 S 88TH STREET

Box: City: KANSAS CITY

State: MO

ZIP: 66111-8701

Country: US

Phone: 913-422-4022 / 800-800-6457

CAGE: 12905

Company Name: DYNAMIC CHEMICALS INC

Address: 415 LAWRENCE BELL DRIVE SUITE 5

Box: City: BUFFALO

State: NY

ZIP: 14221

Country: US

Phone: 716-633-0361

Contract Num: SP0450-00-M-C685

CAGE: 0VZV9

Company Name: SDB CONSULTANTS LTD

Address

:401 WHITNEY AVE SUITE 120
Box:City:GRETNA
State:LA
ZIP:70056
Country:US
Phone:504-366-9105
Contract Num:SP0450-01-M-LG44
CAGE:0PGK2

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OILS
ACGIH TLV:5 MG/M3 MIST

Ingred Name:PERFORMANCE ADDITIVES
< Wt:5.
Other REC Limits:TWA 0.5 PPM

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:EYES-MAY CAUSE IRRITATION.
SKIN-HARMFUL IF ABSORBED THUR SKIN MAY
CAUSE IRRITATION.
INHALATION-MIST MAY CAUSE IRRITATION. INGESTION-NONE EXPECTED.
CHRONIC: MAY CAUSE ALLERGIC SKIN REACTION.
Effects of Overexposure:MAY CAUSE EYES AND SKIN IRRITATION.
INHALATION-MIST MAY CAUSE IRRITATION. INGESTION-NONE EXPECTED.

=====
First Aid Measures
=====

First Aid:EYES-FLUSH WITH WATER. SEE PHYSICIAN. SKIN- WASH WITH SOAP
AND WATER. IF HIGH PRESSURE, GET IMMEDIATE MEDICAL ATTENTION.
INHALATION- REMOVE FROM CONTA
MINATED AREA.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:=148.9C, 300.F
EST
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:DRY CHEMICAL, CO2, FOAM.
Fire Fighting Procedures:AVOID BREATHING VAPORS. USE BREATHING APPATUS
IN CONFINED AREAS. COOL EXPOSED CONTAINERS WITH WATER SPRAY
Unusual Fire/Explosion Hazard:HAZARDOUS THERMAL DECOMPOSITION PRODUCT:
CARBON MONOXIDE, CARBON DIOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS.

===

===== Accidental Release Measures =====

Spill Release Procedures:ADDABSORBENT TO SPILL AREA. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATERWAYS. ADVISE AUTHORITIES IF THEY DO ENTER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE NEAR HEAT, FLAMES, SPARKS. DO NOT WELD OR HEAT EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE ORGANIC VAPOR RESPIRATOR IF TWA IS EXCEEDED.
Ventilation:GENERAL ADEQUATE. USE LOCAL MECHANICAL TO INSURE TWA NOT SURPASSED WHERE APPLICABLE.
Protective Gloves:CHEMICALLY RESISTANT.
Eye Protection:GOGGLES OR FACE SHIELD DESIRABLE.
Other Protective Equipment:NONE NORMALLY NEEDED.
Supplemental Safety and Health
PRODUCT: AIRLUBE NR (ALL GRADES). P/N: 10W/NR .

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:>3
15.6C, 600.F
Vapor Pres:1.0
Spec Gravity: