

MOBIL OIL CORP -- MOBILGREASE 28 -- 9150-00-944-8953

=====
Product Identification
=====

Product ID:MOBILGREASE 28

MSDS Date:03/17/2000

FSC:9150

NIIN:00-944-8953

Status Code:A

MSDS Number: CKSPJ

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLOWS RD

City:FAIRFAX

State:VA

ZIP:22037

Country:US

Info Phone Num:800-662-4525 OR 703-849-3451

Emergency Phone Num:609-737-4411

Resp. P

arty Other MSDS Num.:530626-00

Chemtrec Ind/Phone:(800)424-9300

CAGE:6G112

=== Contractor Identification ===

Company Name:MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV.

Address:RT 27 AND VINEYARD RD.

Box:250

City:EDISON

State:NJ

ZIP:08818-0250

Country:US

Phone:609-737-4411 OR 800-424-9300

CAGE:77988

Company Name:MOBIL OIL CORP

Address:3225 GALLOWS RD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525, 856-224-4644

CAGE:6G112

Company Name:RADIAN INTL LLC

Address:8501 N MOPAC BLVD

Box:2

01088
City:AUSTIN
State:TX
ZIP:78720-1088
Country:US
Phone:512-419-5224
Contract Num:SP0450-00-D-4021
CAGE:29913

=====
Composition/Information on Ingredients
=====

Ingred Name:PENTAERYTHRITOL
CAS:115-77-5
RTECS #:RZ2490000
Minumum % Wt:1.
Maxumum % Wt:5.
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:NO SIGNIFICANT EFFECTS EXPECTED.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH THOROUGHLY WITH WATER. IF IRRITATION OCCURS, CALL A PHYSICIAN. SKIN: WASH CONTACT AREAS WITH SOAP AND WATER. HIGH PRESSURE ACCIDENTAL INJECTION THROUGH THE SKIN REQUIRES IMMEDIATE MEDICAL ATTENTION FOR POSSIBLE INCISION, IRRIGATION AND/OR DEBRIDEMENT. INHALATION: NOT EXPECTED TO BE A PROBLEM. INGESTION: NOT EXPECTED TO BE A PROBLEM. HOWEVER, IF GREATER THAN 1/2 LITER(PINT) INGESTED, IMMEDIATELY GIVE 1 TO 2 GLASSES OF WATER AND CALL A PHYSICIAN, HOSPITAL EMERGENCY ROOM OR POISON CONTROL CENTER FOR ASSISTANCE. DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
Fire Fighting Measures
=====

Flash Point:232.C, 449.6F
EST. (OIL COC)
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.
WATER OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WATER

R TO

KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE. PREVENT RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING STREAMS, SEWERS, OR DRINKING WATER SUPPLY. FOR FIRES IN ENCLOSED AREAS, FIRE FIGHTERS MUST USE SCBA.

Unusual Fire/Explosion Hazard:HAZARDOUS DECOMPOSITION PRODUCTS: NITROGEN OXIDES. PHOSPHORUS OXIDES. CARBON MONOXIDE.

===== Accidental Release Measures =====

Spill Release Procedures:SHOVEL

UP AND DISPOSE OF AT AN APPROPRIATE

WASTE DISPOSAL FACILITY IN ACCORDANCE WITH CURRNT APPLICABLE LAWS AND REGULATIONS, AND PRODUCT CHARACTERISTICS AT TIME OF DISPOSAL. PREVENT SPILLS FROM ENTER ING STORM SEWERS OR DRAINS AND CONTACT WITH SOIL.

===== Handling and Storage =====

Handling and Storage Precautions:HIGH PRESSURE INJECTION UNDER THE SKIN MAY OCCUR DUE TO THE RUPTURE OF PRESSURIZED LINES. ALWAYS SEEK MEDICAL ATTENTION. DO NOT S

TORE IN OPEN OR UNLABELED CONTAINERS.

STORE AWAY FROM STRONG OXIDIZING AGENTS OR COMBUSTIBLE MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Protective Gloves:OIL IMPERVIOUS GLOVES SHOULD BE WORN.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL TYPE GOGGLES SHOULD BE WORN.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS BE FOLLOWED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>316.C, 600.8F

Vapor Pres:MMHG 20C: