

e:SODIUM CHROMATE (SARA 313) (CERCLA)
CAS:7775-11-3
RTECS #:GB2955000
Fraction by Wt: 1.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:0.05 MG/M3
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SKIN/EYES: CAUSES SEVERE BURNS,
NS DEPRESSION. CHRONIC: MAY AFFECT HE
ART/LIVER/KIDNEYS.
Explanation of Carcinogenicity:NTP: SODIUM CHROMATE. IARC: SODIUM
FILMATE, GROUP 1, METHYLENE CHLORIDE, LISTED 2B.
Effects of Overexposure:HIGH VAPOR CONCENTRATIONS IRRITATE
EYES/NOSE/THROAT/RESP TRACT. MAY CAUSE HEADACHE/DIZZINESS/LOSS
CONSCIOUSNESS. CAUSES IRRIT &/OR BURNS TO EYES. INGEST: MAY LEAD TO
PULMINARY INJURY.
Medical Cond Aggravated by Exposure:PREEXISTING LIVER/KIDNEY DISEASE.
CARDIAC DISORDERS. RESPIRATORY LUNG DISEASE.

=====
== First Aid Measures =====

First Aid:SEEK MEDICAL AID IN ALL CASES. INHAL: GET TO FRESH AIR. GIVE
ARTIF RESPIRATION IF BREATHING STOPS. EYES: FLUSH W/WATER >15 MIN
W/IN 1 MIN PERIOD OF CONTACT. SKIN: REMOVE CONTAM CLOTHES. WASH
W/WATER. INGESTION: DON'T INDUCE VOMITING. GIVE PLENTY WATER.
SMALL AMTS MAY BE LETHAL.

=====
===== Fire Fighting Measures =====

Flash Point:NONE TO BOIL

=====
===== Accidental Release Measures

=====

Spill Release Procedures:OUTDOORS: ADD SAND/EARTH/OTHER SUITABLE
ABSORBENT. KEEP OUT OF SEWERS/WATER SOURCES BY DIKING/IMPOUNDING.
INDOORS: ELIMINATE ALL IGNIT SOURCES, REMOVE W/ABSORBENT MATERIAL.
Neutralizing Agent:NA

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE >80F OR