

3M GENERAL OFFICES -- S-W 2216 B/A PART A GRAY EPOXY ADHV 32

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 00-145-0530
MSDS Date: 04/18/1995
MSDS Num: CKTMK
Product ID: S-W 2216 B/A PART A GRAY EPOXY ADHV 32
MFN: 01
Responsible Party
Cage: 04963
Name: 3M GENERAL OFFICES
Address: 3M CENTER
City: ST. PAUL MN 5
5144-1000
Info Phone Number: 651-737-6501/1-800-364-3577
Emergency Phone Number: 0000000000
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 04963
Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV
Address: 3M CTR
City: SAINT PAUL MN 55144-1000
Phone: 800-364-3577/651-737-6501(24 HOURS)

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ADHESIVE
Unit of Issue: KT
UI Container Qty: B
Type of Container: METAL

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====
Health Hazards Data
=====

Route Of En

try Inds - Inhalation: NO
Skin: NO
Ingestion: NO
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO

Effects of Exposure: EYE CONTACT:CHEM RELATED EYE BURNS SYMPTOMS INCLUDE CLOUDY APPEARANCE OF THE CORNEA,CHEM BURNS,PAIN,TEARING,ULCERS,IMPAIRED VISION OR LOSS OF VISION.VAPORS FROM HEATED MATERIAL MAY CAUSE EYE IRRITATION .DUST CREATED BY SANDING,CUTTING,GRINDING OR MACHINING MAY CAUSE EYE IRRITATION.SKIN CONTACT:ALLERGIC SKIN REACTION SYMPTOMS INCLUDE REDNESS,SWELLING,BLISTERING AND ITCHING.INHALATION: IRRITATION SYMPTOMS INCLUDE SORENESS OF THE NOSE AND THROAT COUGHING AND SNEEZING.IF SWALLOWED INGESTION CAN CAUSE IRRITATION OF THE GASTROINTESTINAL TISSUES,SYMPTOMS INCLUDE PAIN,VOMITING,ABDOMINAL TENDERNESS,NAUSEA,BLOOD IN VOMITUS, AND BLOOD IN FECES.

First Aid: EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN CONTACT: IMMEDIATELY WASH SKIN WITH SOAP AND LARGE AMOUNTS OF WATER. REMOVE CONTAMINATED CLOTHING. IF SYMPTOMS PERSIST CALL A PHYSICIAN. WASH CONTAMINATED CLOTHING BEFORE REUSE AND DISPOSE OF CONTAMINATED SHOES. INHALATION: IF SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR. IF SYMPTOMS CONTINUE CALL A PHYSICIAN. IF SWALLOWED: DO NOT INDUCE VOMITING. DRINK TWO GLASSES OF WATER CALL A PHYSICIAN.

=====
Handling and Disposal
=====

Spill Release Procedures: COVER WITH ABSORBENT MATERIAL. PLACE IN A U.S. DOT APPROVED CONTAINER AND SEAL.

Waste Disposal Methods: CURE PRODUCT ACCORDING TO PRODUCT INSTRUCTIONS. INCINERATE UNCURED WASTE IN AN INDUSTRIAL OR COMMERCIAL INCINERATOR. DISPOSE OF COMPLETELY CURED MATERIAL IN A SANITARY LANDFILL.

Handling And Storage Precautions: STORE AWAY FROM HEAT. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER TIGHTLY CLOSED.

=====
Fire and Explosion Hazard Information
=====

=====
Extinguishing Media: WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM
Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING, INCLUDING HELMET,
SELF-CONTAINED POSITIVE PORESSURE OR PRESURE DEMAND BREATHING APPARATUS,
BUNKER COAT AND PANTS, BANDS AROUND ARM, WAIST AND LEGS, FACE MASK, AND
PROTEC TIVE COVERING FOR EXPOSED AREAS OF THE HEAD.
Unusual Fire/Explosion Hazard: NONE KNOWN.
=====

Control Measures

=====
Respiratory Protection: SELECT ONE OF THE FOLLOWING NOISH APPROVED RESPIRATORS
BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS AND IN ACCORDANCE WITH OSHA
REGULATIONS: HALF MADK DUST RESPIRATOR.

Ventilation: LOCAL EXHAUST

Protective Gloves: POLYETHYLENE/ETHYLENE VINYL ALCOHOL

Eye Protection: VENTED GOGGLES. SAFTEY GLASSES WITH SIDE SHIELDS

Work Hygienic Practices: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.
WASH EXPOSED AREA

S THROUGHLY WITH SOAP AND WATER.DO NOT EAT, DRINK OR SMOKE
WHEN USING THIS PRODUCT. WASH EXPOSED AREAS THROUGHLY WITH SOAP AND WATER.

=====
Physical/Chemical Properties

=====
Spec Gravity: 1.26

Viscosity: 40000-80000 CPS

Solubility in Water: NIL

Appearance and Odor: PASTE GRAY PUNGENT ODOR

Percent Volatiles by Volume: 0
=====

Reactivity Data

==

=====
Stability Indicator: YES

Stability Condition To Avoid: HEAT IS GENERATED DURING CURE. DO NOT CURE A MASS
LARGER THAN 50 GRAMS IN A CONFINED SPACE TO PREVENT A PREMATURE REACTION WITH
PRODUCTION OF INTENSE HEAT AND SMOKE.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE, OXIDES OF
NITROGEN, AMINE COMPOUNDS, TOXIC VAPORS, GASES OR PARTICULATES.

Hazardous Polymerization Indicator: NO
=====

=====
MSDS Transport Information
=====

=====
Other Information
=====

Other Information: THE INFORMATION ON THIS DATA SHEET REPRESENTS OUR CURRENT DATA AND BEST OPINION AS TO THE PROPPER USE IN HANDELING OF THIS PRODUCT UNDER NORMAL CONDITIONS. ANY USE OF THE PRODUCT WHICH IS NOT IN CONFO RMANCE WITH THIS DATA SHEET OR WHICH IN VOLVES USING THE PRODUCT IN COMBINATION WITH ANY OTHER PRODUCT OR ANY OTHER PROCESS IS THE RESPONSIBILITY OF THE USER.

=====
Transportation Information
=====

Responsible Party Cage: 04963
Trans ID NO: 154808
Product ID: S-W 2216 B/A PART A GRAY EPOXY ADHV 32
MSDS Prepared Date: 04/18/1995
Review Date: 08/19/2000
MFN: 1
Multiple KIT Number: 0
Unit Of Issue: KT
Container QTY: B
Type Of Container:
METAL

=====
Detail DOT Information
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
HAZCOM Label
=====

=====

Product ID: S-W 2216 B/A PART A GRAY EPOXY ADHV 32

Cage: 04963

Company Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Street: 3M CTR

City: SAINT PAUL MN

Zipcode: 55144-1000

Health Emergency Phone: 0000000000

Label Required IND: Y

Date Of Label Review: 09/29/2000

Status Code: A

Origination Code: G

Hazard And Precautions: EYE CONTACT:CHEM RELATED EYE BURNS SYMPTOMS INCLUDE CLOUDY APPERANCE OF THE CORNES,CHEM BURNS,PAIN,TEARING,ULCERS,INPAIRED VISI ON

OR LOSS OF VISION.VAPORS FROM HEATED MATERIAL MAY CAUSE EYE IRRITATION .DUST CREATED BY SANDING,CUTTING,GRINDING OR MACHINING MAY CAUSE EYE IRRITATION.SKIN CONTACT:ALLERGIC SKIN REACTION SYMPTOMS INCLUDE REDNESS,SWELLING,BLISTERING AND ITCHING.INHALATION: IRRITATION SYMP TOMS INCLUDE SORENESS OF THE NOSE AND THROAT COUGHING AND SNEEZING.IF SWALLOWED INGESTION CAN CAUSE IRRITATION OF THE GASTROINTESTINAL TISSUES,SYMPTOMS INCLUDE PAIN,VOMITING,ABDOMINAL TENDERNESS,NAUS EA,BLOOD I

N VOMITUS, AND BLOOD IN FECES.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or pers

ons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.