

DISTEC, INC -- TFL 50 DRY LUBE, 60132(5 OZ); 60133(10 OZ) -- 9150-01-339-6225

=====
Product Identification
=====

Product ID:TFL 50 DRY LUBE, 60132(5 OZ); 60133(10 OZ)

MSDS Date:06/19/1997

FSC:9150

NIIN:01-339-6225

Status Code:A

MSDS Number: CKTMY

=== Responsible Party ===

Company Name:DISTEC, INC

Address:914 ARCTIC STREET, BLDG #777

City:BRIDGEPORT

State:CT

ZIP:19804

Country:US

Info Phone Num:800-

643-6735

Emergency Phone Num:800-424-9300

Chemtrec Ind/Phone:(800)424-9300

CAGE:UO041

=== Contractor Identification ===

Company Name:DISTEC, INC

Address:914 ARCTIC STREET, BLDG #777

Box:City:BRIDGEPORT

State:CT

ZIP:19804

Country:US

Phone:800-643-6735

CAGE:UO041

Company Name:WET'N DRY LUBES INC

Address:242 N JAMES ST #106

City:WILMINGTON

State:DE

ZIP:19804

Phone:(201) 943-1130

CAGE:PO155

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM)

, LIGHT ALIPH.
CAS:64742-89-8
< Wt:30.

Ingred Name:FLUOROCARBON TELOMER
< Wt:10.

Ingred Name:PROPELLANT (CONSIST OF PROPANE, CAS 74-98-6 {20%} AND
ISOBUTANE, CAS 75-28-5 {80%})
< Wt:70.

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:SHORT TERM: INHALATION: MAY CAUSE
IRRITATION OF RESPIRATORY TRACT. INTENTIONAL MISUSE OF THIS PRODUCT
BY DELIBERATELY CONCENTRATING AND INHALING CAN BE HARMFUL OR FATAL.
INGESTION: MAY CAUSE GASTROINTESTINAL IRRITATION AND DEPRESSION OF
CENTRAL NERVOUS SYSTEM. SKIN/EYE: MAY CAUSE IRRITATION. LONG TERM:
PROLONGED OR REPEATED CONTACT MAY CAUSE DERMATITIS. MAY CAUSE SKIN
IRRITATION ON PROLONGED OR REPEATED CONTACT.
Medical Condition Aggravated by Exposure:NONE RECOGNIZED.

=====
First Aid Measures
=====

First Aid:INHALATION: IF USER EXPERIENCES DIFFICULTY, MOVE TO AIR FREE
OF VAPORS. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION UNTIL
MEDICAL ASSISTANCE CAN BE RENDERED. INGESTION: DO NOT INDUCE
VOMITING. CALL POISON CONTROL CENTER, HOSPITAL EMERGENCY ROOM OR
PHYSICIAN IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. EYE: FLUSH
WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. IF
IRRITATION FROM CONTACT PERSISTS, GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Extinguishing Media:USE CARBON DIOXIDE, DRY POWDER OR FOAM
Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY PROTECTION SHOULD
BE PROVIDED FOR FIREFIGHTERS FIGHTING FLAMES IN BUILDINGS OR
CONFINED AREAS. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT
COOL WITH WATER SPRAY TO PREVENT PRESSURE BUILDUP.
Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. DO NOT PUNCTURE,
INCINERATE OR STORE ABOVE 120 F. EXPOSURE TO HEAT OR PROLONGED
EXPOSURE TO SUN MAY CAUSE BURSTING. ISOLATE FROM HEAT, ELECTRICAL
E

QUIPMENT, SPARKS, OPEN FLAMES AND HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures: AVOID BREATHING VAPORS. VENTILATE AREA. FLUSH LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS WITH LARGE QUANTITIES OF WATER. SMALL SPILL CAN BE ABSORBED BY APPROPRIATE INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE NEAR FLAMES OR AT

ELEVATED TEMPERATURES.

Other Precautions: READ CAREFULLY ALL CAUTIONS AND DIRECTIONS ON PRODUCT LABEL BEFORE USE. SINCE EMPTY CONTAINER RETAINS RESIDUE, FOLLOW ALL LABEL WARNING EVEN AFTER CONTAINER IS EMPTY. DISPOSE OF EMPTY CONTAINER ACCORDING TO LOCAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: FOR OSHA CONTROLLED WORK PLACE, USE ONLY WITH ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED TO PROVIDE

MAXIMUM APPROPRIATE TLV. FOR OCCASIONAL USE WHERE ENGINEERED AIR CONTROL IS NOT FEASIBLE, USE NIOSH APPROVED RESPIRATORS. FOR OCCASIONAL CONSUMER USE, USE ONLY WITH ADEQUATE VENTILATION.

Ventilation: ADEQUATE VENTILATION MUST BE PROVIDED. SEE RESPIRATORY PROTECTION ABOVE.

Protective Gloves: USE IMPERMEABLE GLOVES TO PREVENT SKIN CONTACT.

Eye Protection: SAFETY GLASSES, CHEMICAL GOGGLES AND/OR FACESHIELD

Other Protective Equipment: USUALLY NONE REQUIRED.

Work Hygienic Practices:

WASH HANDS THOROUGHLY AFTER USE. BEFORE REUSE, THOROUGHLY CLEAN ANY CLOTHING OR PROTECTIVE EQUIPMENT WHICH HAS BEEN CONTAMINATED BY PRIOR USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: V3

Boiling Pt: B.P. Text: 185-230F

Vapor Density: >AIR

VOC Grams/Liter: 7.06

Evaporation Rate & Reference: