

U.S. DEPARTMENT OF LABOR -- AGE-MASTER #1 (TM) RUBBER PROTECTANT

=====  
MSDS Safety Information  
=====

FSC: 8030  
NIIN: 01-314-2213  
MSDS Date: 01/01/1996  
MSDS Num: CKVFF  
Product ID: AGE-MASTER #1 (TM) RUBBER PROTECTANT  
MFN: 02  
Responsible Party  
Cage: 62692  
Name: U.S. DEPARTMENT OF LABOR  
Address: 9215 HILLVIEW DR. CLARENC  
E, NEW YORK 14031  
Box: 213  
City: CLARENCE NY 14031  
Info Phone Number: 716-741-2079  
Emergency Phone Number: 716-741-2079  
Proprietary Ind: Y  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 62692  
Name: U.S. DEPARTMENT OF LABOR  
Address: 9215 HILLVIEW DR. CLARENCE, NEW YORK 14031  
Box: 213  
City: CLARENCE NY 14031  
Phone: 716-741-2079

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: PRESERVATIVE COATING,RUBBER  
Specification Number: MIL-P-11520  
Type/Grade/Class: NONE  
Unit of Issue: QT  
UI Container Qty: 0  
Type of Container: CAN

=====  
Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----  
=====

==

Health Hazards Data

=====

Effects of Exposure: INGESTION: NAUSEA, VOMITING, DIARRHEA, GASTROINTESTINAL IRRITATION. EYES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DERMATITIS TO CERTAIN INDIVIDUALS. INHALATION: RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, HEADACHE, FATIGUE.

Explanation Of Carcinogenicity: NOT LISTED AS A POTENTIAL CARCINOGEN IN OSHA, EPA, RCRA, NTP, OR IARC.

First Aid: REMOVE PERSON TO FRESH AIR. DO NOT INDUCE VOMITING. KEEP PERSON WARM. REMOVE PRODUCT FROM SKIN WITH WATERLESS SOAP, WIPE OFF CLEAN, THEN FOLLOW WITH WARM WATER AND REGULAR SOAP. EYES: FLUSH AFFECTED EYE WITH WATER FOR 15 MINUTES. OBTAIN MEDICAL CARE.

=====

Handling and Disposal

=====

Spill Release Procedures: STANDARD PROCEDURES FOR HYDROCARBON SPILLS APPLY TO

THIS PRODUCT. USE OIL ABSORBENT MATERIAL TO CLEAN SPILLAGE. REMOVE ALL SOURCES OF IGNITION. WORK FROM UP-WIND SIDE OF SPILLAGE AREA. TRANSFER WET ABSORBENT INTO CONTAINER FOR DISPOSAL. PREVENT FLOW OF LIQUID INTO WATERWAY OR SEWER. USE FLOATING ABSORBENT TO REMOVE LIQUID FROM WATER.

Waste Disposal Methods: INCINERATE AS SOLID WASTE AT APPROVED STATE WASTE DISPOSAL PLANTS. THE SAME FOR EMPTY DRUMS. REMOVE LIQUID FROM DRUMS WITH ABSORBENT, THEN DISPOSE AS SOLID WASTE.

Handling And Storage Precautions: KEEP FROM HEAT, SPARKS AND OPEN FLAMES. STORE TIGHTLY CLOSED IN WELL VENTILATED AREA. FOLLOW ESTABLISHED PLANT SAFETY REGULATIONS AND PROCEDURES FOR HANDLING COMBUSTIBLES (OSHA 1910)

Other Precautions: DO NOT USE NEAR WELDING EQUIPMENT, FLAMES AND SPARKS. USE ADEQUATE VENTILATION. IF ADEQUATE VENTILATION IS NOT AVAILABLE, PROVIDE FANS OR AIR SUPPLYING EQUIPMENT.

=====

Fire and Explosion Hazard Information

=====

Flash Point Method: TCC  
Flash Point: =63.C, 145.4F  
Flash Point Text: 63C

Extinguishing Media: REGULAR FOAM, CARBON DIOXIDE OF DRY CHEMICAL

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES. VAPORS ARE HEAVIER THAN AIR AND MAY BE MOVED BY VENTILATION AND IGNITED BY HEAT, PILOT LIGHTS, SPARKS OR FLAMES.

Unusual Fire/Explosion Hazard: LIQUID MAY DECOMPOSE TO POISONOUS GASSES OF CO, CO2, NO

X AND SMOKE. (TM) INDICATES REGISTERED U.S. PATENT OFFICE & TRADE MARK OF CHEM-PRO INC.

=====  
Control Measures  
=====

Respiratory Protection: ORGANIC VAPOR RESPIRATOR APPROVAL TC-23C-107 OR EQUIVALENT.

Ventilation: LOCAL EXHAUST: RECOMMENDED MECHANICAL (GENERAL) RECOMMENDED FOR CONFINED AREAS

Protective Gloves: NITRILE RUBBER-HEAVY DUTY.

Eye Protection: CHEMICAL WORKER'S GOGGLES OR FACE SHIELD.

Other Protective Equipment: CLOTHING OR EQUIPMENT: COVERALLS OR APRON. REMOVE STAINS FROM CLOTHING OR STAINED SURFACES USING CLEANING SOLVENT OR KEROSENE. FOLLOW WITH DILUTED CLOXOX TO REMOVE STAINS.

Work Hygienic Practices: WASH HANDS BEFORE EATING AND AT COMPLETION OF WORK. USE WATERLESS SOAP AND WIPE OFF HANDS. FOLLOW WITH REGULAR SOAP AND WARM WATER. DISPOSE SOILED CLOTHING.

=====  
Physical/Chemical Properties  
=====

Boiling Point: =204.4C, 400.F

B.P. Text: 204C

Vapor Pres: MM HG @ 20 C (68 F)

Vapor Density: 5.4

Spec Gravity: 16/16 C 0.8236

Evaporation Rate & Reference: SLOWER

Solubility in Water: INSOLUBLE/NIL

Appearance and Odor: DARK REDISH - BROWN

=====  
Reactivity Data  
=====

Stability Indicator: YES

Stability Condition To Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: MAY FORM TOXIC MATERIALS: CO, CO2, NOX, VARIOUS HYDROCARBONS.

Hazardous Polymerization Indicator: NO

=====  
Toxicological Information  
=====

Toxicological Information: THE PRODUCT AND ITS INGREDIENTS ARE NOT LISTED IN THE HAZARDOUS MATERIALS LIST AND ARE NOT LISTED AS POTENTIAL CARCINOGENS IN OSHA REGULATIONS 29 CFR 1910, TITLE III OF SARA , EPA, RCRA,NTP,IA

RC, OR E

XTREMELY HAZARDOUS SUBSTANCE OR TOXIC CHEMICAL AS DEFINED IN SECTION 302 (A) (2) AND 313 (C) OF FEDERAL REGISTER 52 FR (13378-12410 AND 347983). COMPLIES WITH CLEAN AIR QUALITY REGULATIONS TITLE 6 OF N.Y., AND SCAQMD RULES 442 AND 66. IMDG PROPER SHIPPING NAME: PETROLEUM DISTILLATE N.O.S. - UN-1268 LTD/QTY V.O.C : 0.8 GM/L ; O.O1 LB/GL

=====  
MSDS Transport Information  
=====

==  
Transport Information: IMDG PROPER SHIPPING NAME: PETROLEUM DISTILLATE N.O.S. - UN- 1268 LTD/QTY DOT PROPER SHIPPING NAME: COMBUSTIBLE LIQUID N.O.S. NA-1993 ( NOT A RED LABEL ITEM)

=====  
Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Cage: 62692  
Trans ID  
NO: 155041  
Product ID: AGE-MASTER #1 (TM) RUBBER PROTECTANT  
MSDS Prepared Date: 01/01/1996  
Review Date: 08/11/1999  
MFN: 2  
Multiple KIT Number: 0  
Unit Of Issue: QT  
Container QTY: 0  
Type Of Container: CAN

=====  
Detail DOT Information  
=====

DOT PSN Code: LKX  
DOT Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. OR PETROLEUM PRODUCTS, N.O.S.  
Hazard Class: 3  
UN ID Num: UN1268  
DOT Packaging Group:  
II  
Label: FLAMMABLE LIQUID  
Special Provision: T8,T31  
Packaging Exception: 150  
Non Bulk Pack: 202  
Bulk Pack: 242  
Max Qty Pass: 5 L  
Max Qty Cargo: 60 L  
Vessel Stow Req: B

=====  
Detail IMO Information  
=====

IMO PSN Code: LMD  
IMO Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. o  
IMDG Page Number: 3271  
UN Number: 1268  
UN Hazard Class: 3.2  
IMO Packaging Group: I/II  
Subsidiary Risk Label: -  
EMS Numb

er: 3-07  
MED First Aid Guide NUM: 311

=====  
Detail IATA Information  
=====

IATA PSN Code: TIW  
IATA UN ID Num: 1268  
IATA Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S.  
IATA UN Class: 3  
IATA Label: FLAMMABLE LIQUID  
UN Packing Group: II  
Packing Note Passenger: 305  
Max Quant Pass: 5L  
Max Quant Cargo: 60L  
Packaging Note Cargo: 307  
=====

=====  
Detail AFI  
Information  
=====

AFI PSN Code: TIW  
AFI Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S.  
AFI Hazard Class: 3  
AFI UN ID NUM: UN1268  
AFI Packing Group: II  
Special Provisions: P5  
Back Pack Reference: A7.3  
=====

=====  
HAZCOM Label  
=====

Product ID: AGE-MASTER #1 (TM) RUBBER PROTECTANT  
Cage: 62692  
Company Name: U.S. DEPARTMENT OF LABOR  
Street: 9215 HILLV  
IEW DR. CLARENCE, NEW YORK 14031  
PO Box: 213  
City: CLARENCE NY  
Zipcode: 14031  
Health Emergency Phone: 716-741-2079  
Label Required IND: Y  
Date Of Label Review: 10/19/2000  
Status Code: A  
Origination Code: G  
Hazard And Precautions: INGESTION: NAUSEA, VOMITING, DIARRHEA,  
GASTROINTESTINAL IRRITATION. EYES: CAN CAUSE SEVERE IRRITATION, REDNESS,  
TEARING AND BLURRED VISION. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE  
MODERATE IRRITATION, DERMATITIS TO CERTAIN INDIVIDUALS. INHALATION:  
RE

SPIRATORY IRRITATION, DIZZINESS, NAUSEA, HEADACHE, FATIGUE.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defen

se

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.