View NSN Online: https://aerobasegroup.kr/nsn/9150-00-190-0923

Product ID:LUBRISEAL CAS NO. 68425-13-8 MSDS Date:01/04/1997 FSC:9150 NIIN:00-190-0923 Status Code:A MSDS Number: CKVWY === Responsible Party === Company Name: THOMAS SCIENTIFIC COMPANY Address:99 HIGH HILL ROAD AT 1-295 City:SWEDESBORO State:NJ ZIP:08085-0099 Country:US Info Phone Num:8 00-424-9300/609-467-2000 Emergency Phone Num: (800) 424-9300 Chemtrec Ind/Phone:(800)424-9300 CAGE:59728 === Contractor Identification === Company Name: THOMAS SCIENTIFIC COMPANY Address:99 HIGH HILL ROAD AT I-295 Box:City:SWEDESBORO State:NJ ZIP:08085-0099 Country:US Phone:856-467-2000 CAGE:59728

Ingred Name:PETROLATUM CAS:8009-03-8 RTECS #:SE6780000 OSHA PEL:NA ACGIH TLV:NA

Ingred Name:RUBBER LATEX CAS:9003-55-8 RTECS #:WL647 Ingred Name:1,3-BUTADIENE, 2-METHYL-, HOMOPOLYMER, OF CIS-1,4-CONFIGURATION, DEPOLYMD. CAS:68425-13-8 LD50 LC50 Mixture: NO DATA PROVIDED BY MANUFACTURER Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE OR SKIN CONTACT OR VAPOR INHALATION MAY CAUSE IRRITATION, INGESTION MAY ACT AS A LAXATIVE. Explanation of Carcinoge nicity:NONE ESTABLISHED. Effects of Overexposure: IRRITATION - SEE "HEALTH HAZARD" (ACUTE-CHRONIC). Medical Cond Aggravated by Exposure: SENSITIVITY TO PETROLEUM PRODUCTS. First Aid:EYE CONTACT: FLUSH THOROUGHLY WITH WATER: SKIN CONTACT: WASH WITH SOAP AND WATER; VAPOR INHALATION: REMOVE TO FRESH AIR. Flash Point Method:CC Flash Point:>95.C, 203.F Lo wer Limits:NA Upper Limits:NA Extinguishing Media: FOAM, WATER SPRAY, CO2, DRY CHEMICAL. Fire Fighting Procedures:NONE. Unusual Fire/Explosion Hazard:NONE. Spill Release Procedures: CLEAN UP AND CONTAINERIZE FOR PROPER DISPOSAL. Neutralizing Agent:NO DATA PROVIDED BY MANUFACTURER 

8000

Handling and Storage Precautions:DO NOT STORE NEAR IGNITION SOURCES. AVOID CO

## NTACT WITH EYES. Other Precautions:NO DATA PROVIDED BY MANUFACTURER

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:SELF CONTAINED IF BEING OVERHEATED. Ventilation:LOCAL EXHAUST: IF BEING OVERHEATED. Protective Gloves:IF LARGE QUANTITIES ARE BEING HANDLED. Eye Protection:SAFETY GLASSES OR GOGLES. Other Protective Equipment:NO DATA PROVIDED BY MANUFACTURER Work Hygienic Practices:AVOID EYE OR SKIN CONTACT, BREATHING VAPORS, IGNITION SOURCES OR OZID IZERS. Supplemental Safety and Health

NO DATA PROVIDED BY MANUFACTURER

HCC:V4 Boiling Pt:>340.C, 644.F Melt/Freeze Pt:>50.C, 122.F Vapor Pres:NA Vapor Density:NA Spec Gravity:0.85 - 0.95 Solubility in Water:NOT SOLUBLE Appearance and Odor:PALE YELLOW TO LIGHT BROWN GREASE - NO ODOR

Stability Indicator/Materials to Avoid:YES PURE OXYGEN OR OXIDIZERS. Stabili ty Condition to Avoid:NO DATA PROVIDED BY MANUFACTURER Hazardous Decomposition Products:CARBON MONOXIDE, VARIOUS HYDROCARBONS. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Toxicological Information:NO DATA PROVIDED BY MANUFACTURER

Ecological:NO DATA PROVIDED BY MANUFACTURER

Waste Dis

posal Methods:TO BE PERFORMED IN COMPLIANCE WITH ALL CI	URRENT
LOCAL, STATE AND FEDERAL REGULATIONS.	

Transport Information:NO DATA PROVIDED BY MANUFACTURER

SARA Title III Information:NO DATA PROVIDED BY MANUFACTURER Federal Regulatory Information:NO DATA PROVIDED BY MANUFACTURER State Regulatory Information:NO DATA PROVIDED BY MANUFACTURER

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suit ability of this information to their particular situation.