View NSN Online: https://aerobasegroup.com/nsn/8030-01-159-1583

HERNON MANUFACTURING -- DRIPSTOP 943 -- 8030-01-159-1583

Product ID:DRIPSTOP 943 MSDS Date:02/01/1994 FSC:8030 NIIN:01-159-1583 Status Code:A MSDS Number: CKWWF === Responsible Party === Company Name: HERNON MANUFACTURING Address:121 TECH DR City:SANFORD State:FL ZIP:32771 Country:US Info Phone Num:407-322-4000/800-255-3924 Emergency Phone Num:00000000000 CAGE:6 1603 === Contractor Identification === Company Name: HERNON MANUFACTURING Address:121 TECH DRIVE Box:City:SANFORD State:FL ZIP:32771 Country:US Phone:407-322-4000/800-255-3924 CAGE:61603 Ingred Name: POLYGLYCOL DIMETHACRYLATE CAS:25322-68-3 RTECS #:TQ3500000 Minumum % Wt:45. Maxumum % Wt:48. Ingred Name: POLYMERIC PLASTICIZER CAS:9016-87-9 RTECS #:TR0350000 Minumum % Wt:25. Maxumum % Wt:30.

Ingred Name:DIBUTYL DIXANTHOGENATE C AS:105-77-1 RTECS #:XM6860000 Minumum % Wt:20. Maxumum % Wt:25. OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3

Ingred Name:CUMENE HYDROPEROXIDE CAS:80-15-9 RTECS #:MX2450000 Minumum % Wt:3. Maxumum % Wt:5. EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:SACCHARIN CAS:81-07-2 RTECS #:DE4200000 Minumum % Wt:.1 Maxumum % Wt:1. EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:N,N-DIALKYLTOLUIDINES CAS:4456-80-8 RTECS #:MO1500000 Minumum % Wt:.1 Maxumum % Wt:1.

======= Hazards Identificat

Health Hazards Acute and Chronic:MAY CAUSE DERMITITIS ON PROLONGED IN SENITIVE INDIVIDUALS. Medical Cond Aggravated by Exposure:

First Aid:INGESTION: DO NOT INDUCE VOMITING. KEEP INDIVIDUALS CALM. OBTAIN MEDICAL ATTENTION. SKIN CONTACT: WASH WITH SOAP AND WATER. EYE CONTACT: FLUSH WITH WATER FOR AT LEAST 15 MINITUES. OBTAIN MEDICAL ATTEN TION.

======================== Fire Fighting M

| Flash Point Method:TCC Flash Point:>93.3C, 200.F MORE THAN 200 F Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL |
|---|
| |
| Spill Release Procedures:SOAK UP IN AN INERT ABSORBENT STORE IN PARTLY FILLED. CLOSED CONTAINER UNTIL DISPOSAL. |
| ====================================== |
| Handling and Storage Precautions:STORE AT 110 F TO PRESERVE SHELF LIFE. AVOID PROLONGED SKIN CONTACT. |
| ====================================== |
| Protective Gloves:RUBBER OR PLASTIC Eye Protection:SAFETY GLASSES OR GOGGLES Supplemental Safety and Health |
| ====================================== |
| Boiling Pt:>148.9C, 300.F B.P. Text:MORE THAN 300F Vapor Pres:< 5MM AT 80F Spec Gravity:1.087 AT 80F VOC Pounds/Gallon:164 Solubility in Water:SLIGHT Appearance and Odor:YELLOW LIQUID MILD ODOR |
| ====================================== |
| y Data ================= |
| Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:IRRITATING ORGANIC VAPORS. |
| ====================================== |
| Toxicological Information:ESTIMATEED ORAL LD50 MORE THAN 5000 MG/KG. ESTIMATED DERMAL LD50 MOR THAN 2000 MG/MK. |
| ====================================== |
| Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH EPA AND LOCAL REGULATIONS. |

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of thi s information to their particular situation.