

FISKE BROS REFINING CO -- LUBRIPLATE RG-62-A -- 9150-00-754-0063

=====
Product Identification
=====

Product ID:LUBRIPLATE RG-62-A

MSDS Date:01/01/1999

FSC:9150

NIIN:00-754-0063

Status Code:A

MSDS Number: CKYFT

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:800-255-

3924 (CHEM-TEL)

Preparer's Name:JAMES R KONTAK

CAGE:73219

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT

Address:2275 TUCKER INDUSTRIAL RD

Box:City:TUCKER

State:GA

ZIP:30084

Country:US

Phone:770-938-4513/FAX 770-938-3966

Contract Num:SP0450-01-M-C910

CAGE:1MDA6

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

=====
Composition/Information on Ingredients
=====

=====

Ingred Name:NONHAZARDOUS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.
SKIN: REMOVE ANY CONTAMINATED CLOTHING AND WASH WITH SOAP AND WARM WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF THE APPEARANCE OR ITS SIZE, CONTACT A PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION. VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE AND CALL A PHYSICIAN. INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY, DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:210.C, 410.F
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).
Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRA

PE UP GREASE, WASH REMAINDER WITH SUITABLE
PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF
SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED
OR MAY ENTER SEWER S AND WATER COURSES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT HANDLE OR STORE NEAR HEAT, SPRAKS, FLAME OR STRONG
OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LA
UNDER BEFORE REUSE.
CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:LOCAL EXHAUST: USED TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES, IF NEEDED.

Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES.

Other Protective Equipment:USE OIL-RESISTANT APRON, IF NEEDED.

Supplemental Safety and Health

PRODUCT NAME OR NUMBER: LUBRIPLATE RG-62-A. GENERIC/CHEMIC
AL NAME:

PETROLUM LUBRICATING GREASE. FORMULA: CALCIUM SOAP, MINERAL OIL AND
ADDITIVES. USDA AUTHORIZATION: N/A.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5(AIR=1)

Spec Gravity:0.96 (H2O=1)

Evaporation Rate & Reference:< 0.01 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:SMOOTH, TAN GREASE WITH MINERAL OIL ODOR.

===== Stability and React
ivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDANTS LIKE LIQUID CHLORINE, CONCENTRATED
OXYGEN.

Hazardous Decomposition Products:HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY FORM SO2. IF INCOMPLETE COMBUSTION, CARBON MONOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR

===== Toxicological Information =====

Toxicological Information:THRESHOLD LIMIT VALUE: 5 MG/M3 FOR OIL MIST
IN AIR. OSHA REGULA

TION 29 CFR 1910.1000.

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED WASTE DISPOSAL FACILITY OR SITE.

===== Regulatory Information =====

SARA Title III Information:SARA/TITLE III, SECTION 313-ZINC COMPOUNDS -