

DYNAMOLD SOLVENTS, INC. -- MR-502 MAGNETIC RUBBER INSPECTION MATERIAL (CATALYST) --
6850-01-037-9015

===== Product Identification =====

Product ID:MR-502 MAGNETIC RUBBER INSPECTION MATERIAL (CATALYST)

MSDS Date:05/01/2000

FSC:6850

NIIN:01-037-9015

Status Code:A

MSDS Number: CKYNB

=== Responsible Party ===

Company Name:DYNAMOLD SOLVENTS, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

Stat

e:TX

ZIP:76107

Country:US

Info Phone Num:817-335-0862

Emergency Phone Num:800-255-3924 (CHEMTEL)

Preparer's Name:MICHAEL PECK

CAGE:30256

=== Contractor Identification ===

Company Name:DYNAMOLD SOLVENTS, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

State:TX

ZIP:76107

Country:US

Phone:817-335-0862

Contract Num:SPO450-01-M-D679

CAGE:30256

===== Composition/Information on Ingredients =====

Ingred Name:DIBUTYLTIN DILAURATE

CAS:77-58-7

RTECS #:WH7000000

Minumum % Wt:.05

Maxumum % Wt:2.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG SN/M3 SKIN
ACGIH TLV:0.1 MG SN/M3

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN CONTACT IS NOT KNOWN TO CAUSE
IRRITATION. EYE CONTACT MAY CAUSE TRANSIENT EYE IRRITATION.
Explanation of Carcinogenicity:PER MSDS:
CHEM/COMPONENT LISTED AS
CARCINOGEN OR POTENTIAL CARCINOGEN:NONE.
Effects of Overexposure:TRANSIENT EYE IRRITATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION: IF INHALED, REMOVE TO FRESH AIR AND CONSULT
PHYSICIAN. EYES: IN CASE OF CONTACT, FLUSH WITH WATER FOR 15
MINUTES AND CONSULT PHYSICIAN. SKIN: FLUSH WITH WATER, OBTAIN
MEDICAL ATTENTION IF IRRITATION OCCURS.
INGESTION: IF SWALLOWED,
DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:=129.4C, 265.F
Autoignition Temp:Autoignition Temp Text:NP
Lower Limits:NP
Upper Limits:NP
Extinguishing Media:DRY CHEMICAL, CO2, WATER SPRAY.
Fire Fighting Procedures:DO NOT ENTER FIRE AREA WITHOUT PROTECTION.
FIGHT FIRE FROM SAFE DISTANCE/PROTECTED LOCATION. HEAT MAY BUILD
PRESSURE AND RUPTURE CLOSED CONTAIN
ERS, SPREADING FIRE. USE WATER
SPRAY FOR COOLING. DRY CHE MICAL, CO2 IS PERMISSABLE. NOTIFY
AUTHORITIES IF LIQUID ENTERS SEWER/PUBLIC WATERS.
Unusual Fire/Explosion Hazard:NONE, AVOID EXTREME HEAT OR FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:UTILIZE PERSONAL PROTECTIVE EQUIPMENT. LIMIT
ACCESS TO QUALIFIED PERSONNEL. SOAK UP SPILL WITH INERT SOLIDS AND
PLACE IN A LABELED, SEALED CONTAINER. PREVENT FLOW TO SEWERS.
NOTIF

