

RED DEVIL, INCORPORATED -- FILLER, WOOD, PLASTIC #X-552 -- 8030-00-664-7077  
===== Product Identification =====

Product ID:FILLER, WOOD, PLASTIC #X-552  
MSDS Date:01/07/1996  
FSC:8030  
NIIN:00-664-7077  
Status Code:A  
MSDS Number: CKYTD  
=== Responsible Party ===  
Company Name:RED DEVIL, INCORPORATED  
Address:ONE WEBB STREET  
Box:A  
City:PRYOR  
State:OK  
ZIP:74361  
Country:US  
Info Phone Num:918-825-5744  
Emergen  
cy Phone Num:918-825-5744  
Preparer's Name:ERNEST CARTER  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:23577

=== Contractor Identification ===  
Company Name:RED DEVIL, INCORPORATED  
Address:ONE WEBB STREET  
Box:A  
City:PRYOR  
State:OK  
ZIP:74361  
Country:US  
Phone:918-825-5744  
CAGE:23577

===== Composition/Information on Ingredients =====

Ingred Name:ISO-PROPYL ALCOHOL  
CAS:67-63-0  
RTECS #:NT8050000  
&lt; Wt:2.  
OSHA PEL:980 MG/M3;400 PPM  
ACGIH TLV:983 MG/M3;400 PPM  
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:ACETONE  
CAS:67-64-1  
RTECS #:AL3150000  
> Wt:25.  
OSHA PEL:2400 MG/M3;1000 PPM  
ACGIH TLV:1780 MG/M3;750 PPM  
ACGIH STEL:2380 MG/M3;1000 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE  
CAS:123-86-4  
RTECS #:AF7350000  
< Wt:4.  
OSHA PEL:710 MG/M3;150 PPM  
ACGIH TLV:713 MG/M3;150 PPM  
ACGIH STEL:950 MG/M3;200 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:WOOD FLOUR-(AS WOOD DUST)  
< Wt:10.

=====  
===== Hazards Identification =====  
=====

Effects of Overexposure:DUST GENERATED FROM DRIED PRODUCT MAY CAUSE  
EYE, SKIN, AND RESPIRATORY IRRITATION  
AND MAY CAUSE LUNG DAMAGE. VAPORS MAY PRODUCE HEADACHE, DIZZINESS AND  
NAUSEA. EYE  
CONTACT CAUSES BURNING AND IRRITATIO N. MAY CAUSE MINOR REVERSIBLE  
EFFECTS ON LIVER  
AND KIDNEYS.

=====  
===== First Aid Measures =====  
=====

First Aid:EYES: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR  
AT LEAST 15 MINUTES  
WHILE HOLDING EYELIDS OP

EN. SKIN: WIPE MATERIAL FROM SKIN WITH CLOTH OR PAPER TOWEL, THEN WASH EXPOSED AREA WITH SOAP AND WATER. INHALATION: MOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. INGESTION: CONTACT LOCAL POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY!

=====  
===== Fire Fighting Measures =====

Flash Point Method:CALC  
Flash Point:=-4.4C, 40.F  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM.  
Fire Fighting Procedures:USE WATER SPRAY OR FOG TO COOL FIRE-EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:VAPORS CAN FLOW TO IGNITION SOURCES AND FLASHBACK.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP SPILLED MATERIAL, WASH AREA WITH DETERGENT.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF OVEREXPOSURE, WEAR A NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS.  
Ventilation:LOCA  
L EXHAUST MAY BE NECESSARY UNDER SOME HANDLING/USE CONDITIONS .  
Protective Gloves:WEAR CHEMICAL-RESISTANT GLOVES AND CLOTHING AS NEEDED TO PREVENT SKIN CONTACT.  
Eye Protection:IF POTENTIAL FOR EYE CONTACT EXISTS, WEAR CHEMICAL GOGGLES.  
Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Vapor Density:(AIR=1)  
Spec Gravity:(H2O=1)  
Evaporation Rate & Reference: