

GE SILICONES -- POLYSILOXANE COMPOUND -- 8040-00-181-8380

===== Product Identification =====

Product ID:POLYSILOXANE COMPOUND

MSDS Date:06/10/1998

FSC:8040

NIIN:00-181-8380

Status Code:A

Kit Part:Y

MSDS Number: CKZJH

=== Responsible Party ===

Company Name:GE SILICONES

Address:260 HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergency Phone Num:518-237

-3330

Preparer's Name:HENRY SIMMONS

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:METHYLTRIACETOXYSILANE

CAS:4253-34-3

RTECS #:VV4500000

Minumum % Wt:1.

Maxumum % Wt:5.

Ingred Name:POLYDIMETHYLSILOXANE SILANOL/STPD

CAS:70131-67-8

C

ode:F
Minumum % Wt:60.
Maxumum % Wt:80.

Ingred Name:SILANOL/STPD SILOXANE W/ME SLSQXNS
CAS:68554-67-6
Code:F
= Wt:8.75

Ingred Name:D4 & HMDZ TREATED SILICON DIOXIDE
CAS:68937-51-9
Minumum % Wt:10.
Maxumum % Wt:30.

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:NONE KNOWN
Explanation of Carcinogenicity:THIS PRODUCT OR ONE OF ITS INRGEDIENTS
PRESENT 0.1 % OR MORE IS NOT LISTED AS A CARCINOGEN OR SUSPECTED
CARCINOGEN BY NTP, IARC, O

R OSHA

Effects of Overexposure:INGESTION: MAY BE HARMFUL IF SWALLOWED. SKIN
CONTACT: UNCURED PRODUCT CONTACT WILL IRRITATE LIPS, GUMS, AND
TONGUE. UNCURED PRODUCT MAY IRRITATE THE SKIN. INHALATION: CAUSES
IRRITATION OF THE MOUTH, N OSE, AND THROAT. APPLIES ONLY IN UNCURED
STATE. EYE CONYACT: UNCURED PRODUCT CONTACT IRRITATES EYES.

Medical Cond Aggravated by Exposure:NONE KNOWN.

=====
===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. SLOWLY DILUTE WITH 1-2
GLASSES OF WATER OR MILK AND SEEK MEDICAL ATTENTION. NEVER GIVE
ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SKIN: TO CLEAN FROM
SKIN, REMOVE COMPLETELY WITH A DRY CLOTH OR PAPER TOWEL. BEFORE
WASHING WITH DETEREGENT AND WATER. INHALATION: MOVE PERSON TO FRESH
AIR. EYES: IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY
OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION IF
IRRITATION PERSITS.

=====
===== F

Fire Fighting Measures =====

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.
Fire Fighting Procedures:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE TO REDUCE SLIPPING HAZZARD. WEAR PROPER PROTECTIVE EQUIPMENT AS SPECIFIED IN THE PROTECTIVE EQUIPMENT SECTION.

=
===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH SKIN AND EYES. REMOVE CONTACT LENSES BEFORE USING SEALANT. DO NOT HANDLE LENSES UNTIL ALL SEALANT HAS BEEN CLEANED FROM THE FINGER-TIPS, NAILS AND CUTICLES. RESIDUAL SEALANT MAY REM AIN ON FINGERS FOR SEVERAL DAYS AND TRANSFER TO LENSES AND CAUSE SEVERE EYE IRRITATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:
USE IN A WELL VENTILATED AREA. USE APPROVED NIOSH RESPIRATORY IF TLV EXCEEDED?OR OVER EXPOSURE IS LIKELY.
Ventilation:USE ONLY IN WELL VENTILATED AREA. MECHANICAL VENTILATION.
Protective Gloves:RUBBER GLOVES . CLOTH GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:NONE KNOWN
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:1.1
VOC Pounds/Gallon:42
Evaporation Rate & Reference:535
RAT SILANOL/STPD SILOX
ANE W/ME SLSQXNS: ACUTE ORAL LD50 (MG/KG):
(RAT) >40 G/KG ACUTE DERMAL LD50 (MG/KG): NF ACUTE INHALATION LC50 (MG/L) >535 (RAT) D4 & HMDZ TREATED SILICON DIOXIDE: ACUTE ORAL LD50 (MG/KG) 3160 (RAT) ACUTE DERMAL LD50 (MG/KG): NF ACUTE INHALATION LC50 (MG/L): NF

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

===== Regulatory Informati

on =====

SARA Title III Information:SARA SECTION 302: NONE FOUND SARA (311,312)
HAZARD CLASS: ACUTE HAZARD HAZARD SARA (313) CHEMICALS: NONE
Federal Regulatory Information:WHMIS HAZARD CLASS: D2A VERY TOXIC
MATERIALS D2B TOXIC MATERIALS WHMIS TRADE SECRET: NONE EXPORT:
SCHDLE B/HTSUS 3910.00 SILICONES IN PRIAMRY FORM ECCN: EAR99 HAZARD
RATING SYSTEMS HMIS FLAMMABILITY 0 , REACTIVITY 0, HEALTH 2, NFPA
FLAMMABILITY 0, REACTIVITY 0, HEALTH 2.

State Regulatory I
nformation:CALIFORNIA PROPOSITION 65: NONE

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional
advice to verify and
assume responsibility for the suitability of this information to their
particular situation.