

CHEMENCE INC -- RITE-LOK EC100-28 -- 8040-00-142-9193

=====
===== Product Identification =====

Product ID:RITE-LOK EC100-28
MSDS Date:05/01/1998
FSC:8040
NIIN:00-142-9193
Status Code:A
MSDS Number: CKZJM
=== Responsible Party ===
Company Name:CHEMENCE INC
Address:6425 INDUSTRIAL WAY
City:ALPHARETTA
State:GA
ZIP:30201
Country:US
Info Phone Num:404-664-6624
Emergency Phone Num:(800)424-9300
Preparer's Name:HENRY SIMMONS
Chemtrec Ind/Phone:(800)424-9300
CAGE:0ZDS4

==== Contractor Identification ====
Company Name:CHEMENCE INC
Address:6425 INDUSTRIAL WAY
City:ALPHARETTA
State:GA
ZIP:30201
Country:US
Phone:404-664-6624
CAGE:0ZDS4

=====
===== Composition/Information on Ingredients =====

Ingred Name:ETHYL CYANOACRYLATE
CAS:7085-85-0
RTECS #:UD3330000
Minumum % Wt:95.
Maxumum % Wt:100.

Ingred Name:HYDROQUINONE
CAS:123-31-9
RTECS #:MX3500000
Minumum % Wt:.1
Maxumum % Wt:.5
OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:POLY(METHYL METHACRYLATE)

CAS:9011-14-7

RTECS #:TR0400000

Minumum % Wt:3.

Maxumum % Wt:5.

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:VAPOR IS IRRITATING TO EYES & MUCOUS MEMBRANES.
PROLONGED & REPEATED OVERXPOSURE TO VAPORS MAY PRODUCE ALLERGIC
REACTIONS WITH ASTHMA-LIKE SYMPTOMS IN SENSITIVE INDIVIDUALS.

=====
===== First Aid Measures =====

First Aid:SKIN: IMMERSE BONDED SURFACE IN WARM SOAPY WATER. PEEL OR
ROLL SURFACE APART WITH AID OF BLUNT EDGE. DO NOT PULL PART WITH
DIRECT OPPOSING ACTION. EYE: FLUSH WITH WARM WATER AND APPLY CAUSE
PATCH. EYE WILL OPEN WITHIN 1-4 DAYS. MOUTH. APPLY WARM WATER TO
MOUTH. PEEL OR ROLL LIPS APART. BURNS. SHOULD BE TREATED NORMALLY
NORMALLY AFTER THE LUMP OF CYANOACRYLATE IS RELEASED FROM THE
TISSUE. INHALATIO N: REMOV
E TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=85.C, 185.F

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:POSSIBLE EXOTHERMIC REACTION WITH
SUBSTRATE AND/OR IGNITION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLOOD WITH WATER TO POLYMERIZE/NEUTRALIZE.
SOAK UP WIT

