

PABCO INSULATION -- PABCO SUPER CALTEMP GOLD -- 5640-00-809-6315

=====
Product Identification
=====

Product ID:PABCO SUPER CALTEMP GOLD
MSDS Date:12/15/1995
FSC:5640
NIIN:00-809-6315
Status Code:A
MSDS Number: CLBKK
=== Responsible Party ===
Company Name:PABCO INSULATION
Address:9800 NORTHWEST FREEWAY - SUITE 503
City:HOUSTON
State:TX
ZIP:77092
Country:US
Info Phone Num:713-681-8173
Emergency Phone Num:000000000
CAGE:0TUC0
=== Contractor Identification ===
Company Name:PABCO INSULATION
Address:9800 NORTHWEST FREEWAY - SUITE 503
Box:City:HOUSTON
State:TX
ZIP:77092
Country:US
Phone:713-681-8173
CAGE:0TUC0

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM SILICATE
CAS:1344-95-2
RTECS #:VV9150000
OSHA PEL:15/5
ACGIH TLV:10

Ingred Name:SODIUM SILICATE
CAS:1344-09-8
ACGIH TLV:10

Ingred Name:INORGANIC FIBER
CAS:1332-21-4
RTECS #:CI6475000
EPA Rpt Qty:

1 LB
DOT Rpt Qty:1 LB

Ingred Name:CELLULOSE
CAS:9004-34-6
RTECS #:FJ5691460
OSHA PEL:15/5
ACGIH TLV:10

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7400000
OSHA PEL:5
ACGIH TLV:5

Ingred Name:QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
OSHA PEL:0.1
ACGIH TLV:0.1

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:SKIN CONTACT MAY CAUSE ITCHING AND
TEMPORARY IRRITATION. EYE CONTACT WITH
DUST MAY CAUSE IRRITATION.
INHALATION OF DUST GENERATED BY CUTTING OR SAWING MAY RESULT IN
IRRITATION OF THE UPPER RESPIRATORY TRACT.
Effects of Overexposure:CAN CAUSE DRYING OF SKIN.

=====
===== First Aid Measures =====

First Aid:FOR DUST IN EYES, FLUSH WITH WATER UNTIL CLEAR. IF IRRITATION
PERSISTS SEE A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:>200F,>93C
Lower Limits:NOT GIVEN
Upper Limits:NOT

GIVEN

Extinguishing Media:WATER, DRY CHEMICAL, CARBON DIOXIDE, FOAM

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP. WET DOWN TO AVOID DUST. USE PROPER DUST RESPIRATOR WHENEVER DUST IS GENERATED.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN DRY PLACE.

Other Precautions:ORGANICALLY CONTAMINATED INSULATION SHOULD NOT BE INSTALLED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NUISANCE DUST RESPIRATORS.

Ventilation:MECHANICAL

Protective Gloves:GLOVES OR BARRIER CREAM FOR SENSITIVE SKIN

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Solubility in Water:NEGLIGABLE

Appearance and Odor:YELLOW OR WHITE CHALKY SOLID NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALINITY OF WET CALCIUM SILLICATE CORRODES ALUMINUM

===== Disposal Considerations =====

Waste Disposal Methods:NOT REGULATED UNDER THE RCRA HAZARDOUS WASTE REGULATIONS. DISPOSE TO A DRY DUMP AREA IN ACCORDANCE WITH LOCAL AND FEDERAL REGULATIONS.

===== Other Information =====

Disclaimer

(provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.