

STIC-ADHESIVE PRODUCTS CO, INC -- ENAMEL, INTERIOR, NONFLAMING (DRY), CHLORINATED ALKYD RESIN, -- 8010-01-344-5093

=====  
Product Identification  
=====

Product ID:ENAMEL, INTERIOR, NONFLAMING (DRY), CHLORINATED ALKYD RESIN,

MSDS Date:08/01/2000

FSC:8010

NIIN:01-344-5093

Status Code:A

MSDS Number: CLFXT

=== Responsible Party ===

Company Name:STIC-ADHESIVE PRODUCTS CO, INC

Address:3950 MEDFORD STREET

City:LOS ANGELES

State:CA

ZIP:90063

Info Phone Num:213-268-2956

Emergency Phone Num:999-999-9999

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:DO670

=== Contractor Identification ===

Company Name:STIC-ADHESIVE PRODUCTS CO, INC

Address:3950 MEDFORD STREET

Box:City:LOS ANGELES

State:CA

ZIP:90063

Phone:213-268-2956

CAGE:DO670

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

= Wt:21.

OSHA PEL:1

5 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:ZINC PHOSPHATE  
= Wt:16.

Ingred Name:BARIUM METABORATE  
= Wt:15.

Ingred Name:CHLORENDIC ALKYD  
= Wt:35.

Ingred Name:PAINT THINNER  
CAS:8052-41-3  
Code:F  
RTECS #:WJ8925000  
= Wt:9.  
OSHA PEL:2900 MG/M3;500 PPM  
ACGIH TLV:525 MG/M3;100 PPM

Ingred Name:DRIVERS LEVELING AGENT  
CAS:136-52-7  
Code:F  
= Wt:3.

Ingred Name:ANTISKINNING AGENT THIXATROPIC AGENT  
= Wt:1.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES S  
kin:YES Ingestion:YES

Health Hazards Acute and Chronic:INGESTION: KEEP PERSON WARM, QUIET AND GET IMMEDIATE MEDICAL ATTENTION. EYE CONTACT: CAUSES SEVERE EYE IRRITATION. SKIN CONTACT: CAUSED PRIMARY SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. INHALATION: VAPOR AND SPRAY MIST HARMFUL IF INHALED. VAPOR IRRITATES EYES, NOSE, THROAT. MAY IRRITATE LUNGS. AVOID LONG TERM AND REPEATED CONTACT. PRODUCT CONTAINS TITANIUM DIOXIDE.

Effects of Overexposure:EYE

WATERING, HEADACHES, NAUSEA, DIZZINESS, AND  
LOSS OF COORDINATION ARE INDICATION THAT SOLVENT LEVELS ARE TOO  
HIGH. REDNESS, ITCHING, BURNING SENSATION AND VISUAL DISTURBANCES  
MAY INDICATE EXCESSIVE EYE CONTACT, DRYNESS, ITCHING, CRACKING,  
BURNING, REDNESS, AND SWELLING ARE CONDITIONS ASSOCIATED WITH  
EXCESSIVE SKIN CONTACT.

===== First Aid Measures =====

First Aid:INGESTION: IF SWALLOWED, GIVE 1 OR 2 GLASSES OF WATER, BUT DO  
NOT INDUCE VOMITING. EYE CONTACT: FLUSH EYES IMMEDIATELY WITH  
PLENTY OF WATER FOR AT LEAST 30 MINUTES. SKIN CONTACT: FLUSH  
IMMEDIATELY WITH PLENTY OF WATER FOLLOWED BY WASHING WITH SOAP AND  
WATER. INHALATION: IF AFFECTED BY INHALATION OF VAPORS OR SPRAY  
MIST, REMOVE TO FRESH AIR. INGESTION, ANY TYPE OF OVEREXPOSURE OR  
SYMPTOMS OF OVEREXPOSURE OCCURS DURING OR FOLLOWING THE USE OF  
THIS PRODUCT.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:40.6C, 105.F  
Autoignition Temp:Autoignition Temp Text:NONE  
Lower Limits:NONE  
Upper Limits:NONE  
Extinguishing Media:USE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)  
CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL, OR UNIVERSAL  
AQUEOUS FILM FOAMING FOAM) DESIGNED TO EXTINGUISH NFPA CLASS.  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER SPRAY  
MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP  
AND POSSIBLE AUTOIGNITION OF EXPLOSION WHEN EXPOSED TO EXTREME  
HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.  
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE  
FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAMES. CLOSED  
CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE MAXIMUM VENTILATION. ONLY PERSONNEL  
EQUIPPED WITH PROPER RESPIRATORY AND SKIN AND EYE PROTECTION SHOULD  
BE

E PERMITTED IN THE AREA. REMOVE ALL SOURCES OF IGNITION. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERICULITE, OR OTHER ABSORBENT MATERIAL AND CONTAINERS SHOULD BE RECYCLED OR DISPOSED OF THROUGH AN APPROVED WASTE MANAGEMENT FACILITY.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120 DEGREES F. STORE LARGE QUANTITIES IN BUILDING DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS IC FLAMMABLE LIQUIDS.

Othe

r Precautions:IF THIS MATERIAL IS PART OF A MULIPLE COMPONENT SYSTEM, READ THE MATERIAL SAFETY DATA SHEET(S) FOR THE OTHER COMPONENTS BEFORE BLENDING AS THE RESULTING MIXTURE MAY HAVE THE HAZARDS OF ALL OF ITS PART S.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:(NIOSH/MSHA APPROVED AIR PURIFYING OR AIR SUPPLIED RESPIRATORS MAY ALSO REDUCE EXPOSURE.

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN.

Protective Gloves:WEAR IMPERMEABLE CLOTHING SUFFICIENT TO COVER EXPOSED SKIN SURFACES CONSTRUCTED

Eye Protection:WEAR CHEMICAL TYPE SPLASH GOGGLES OR FULL FACE SHIELD.

Other Protective Equipment:CLEAN OR DISCARD CONTAMINATED CLOTHING AND SHOES.

Work Hygienic Practices:NONE

Supplemental Safety and Health

NONE

=====  
Physical/Chemical Properties  
=====

Boiling Pt:=154.4C, 310.F

Melt/Freeze Pt:M.P/F.P Text:NONE

Decomp Temp:Decomp Text:NONE

Vapor Pres:2.0

00 MMHG AT 68 F

Vapor Density:4.9

Spec Gravity:1.62-1.65

Appearance and Odor:NONE

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG ALKALIS, STRONG MINERAL ACIDS, OR STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID CONTACT WITH STRONG ALKALIS, STRONG MINERAL ACIDS, OR STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:NONE

=====  
Disposal Considerations  
=====

=====

Waste Disposal Methods:WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL STATE, PROVINCLAL, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person util

izing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.