

GRIGGS PAINT -- A-A-2335 SEALER, VARNISH -- 8010-00-243-0961

=====
Product Identification
=====

Product ID:A-A-2335 SEALER, VARNISH

MSDS Date:08/01/1999

FSC:8010

NIIN:00-243-0961

Status Code:A

MSDS Number: CLFZC

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:800-424-9300

Prepar

er's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:58963

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBONS(STODDARD TYPE)

CAS:8052-41-3

Code:F

RTECS #:WJ8925000

= Wt:29.

OSHA PEL:2900 MG/M3;500 PPM

ACGIH TLV:525 MG/M3;100 PPM

=====
Hazards Identificati
=====

on =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:REPEATED CONTACT MAY CAUSE SKIN IRRITATION.INHALATION OF HIGH CONCENTRATION OF VAPORS MAY LEAD TO LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION, AND CENTRAL NERVOUS SYSTEM DEPRESSION. IN GESTION MAY CAUSE GASTROINTESTINAL DISTUBANCES.

Effects of Overexposure:INHALATION: VAPOR CONCENTRATIONS MAY CAUSE DROWSINESS, DIZZINESS, FATIGUE, FOLLOWED BY COM

A. EYE: DIRECT

CONTACT WITH VAPORS MAY CAUSE IRRITATION. SKIN: REPEATED CONTACT MAY CAUSE IRRITATION AND/OR DE RMITITIS. MAY BE ABSORBED THROUGH THE SKIN.INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCES.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKIN CENTRAL NERVOUS SYSTEM, LIVER AND KIDNEY.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNT S OF WATER FOR 15 MINTES.

SEEK MEDICAL ATTENTION. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. SEEK MEDICAL AID. INGESTION: IMMEDIATELY SEEK MEDICAL AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=37.8C, 100.F

Autoignition Temp:Autoignition Temp Text:NONE

Lower Limits:1.0%

Upper Limits:NONE

Extinguishing Media:FOAM, C02, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING OERSONEL

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA WITH WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE .

===== **Handling and Storage**=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID BREATHING OF VAPORS AND SPRAY MIST AVOID SKIN AND EYE CONTACT.
Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK ORPIT, WITHOUT ADEQUATE VENTILATION.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:USE MSHA/NIOSH APPROVED UNITS.
Ventilation:LOCAL AND MECHANICAL EXHAUST.
Protective Gloves:RUBBER GLOVES.
Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES.
Other Protective Equipment:EYE BATH AND SAFETY SHOWER.
Work Hygienic Practices:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS WITHOUT ADEQUATE VENTILATION.
Supplemental Safety and Health

===== **Physical/Chemical Properties**=====

Boiling Pt:=167.8C, 334.F
Melt/Freeze Pt:M.P/F.P Text:NONE
Deco
mp Temp:Decomp Text:NONE
Vapor Density:HEAVIER
Spec Gravity:(H2O=1):0.9
VOC Pounds/Gallon:502
VOC Grams/Liter:4.19
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:ESSENTIALLY NIL
Appearance and Odor:VISCIOUS LIQUID WITH TYPICAL PAINT ODOR

===== **Stability and Reactivity Data**=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDZING AGENTS.
Stability Condition to Avoid:FLAMES, SPARKS, SMOKING AND HEAT.
Hazardous Decomposition Products:CARB

ON MONOXIDE AND CARBON DIOXIDE.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:USE INERT ABSORBENT MATERIALS ON SPILLS. DISPOSE
OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.