

CLIFTON ADHESIVE INC -- FA-1053 MIMM-A-1617, TYPE 1 -- 8040-00-262-9025

=====
Product Identification
=====

Product ID:FA-1053 MIMM-A-1617, TYPE 1
MSDS Date:02/06/1995
FSC:8040
NIIN:00-262-9025
Status Code:A
MSDS Number: CLGDD
=== Responsible Party ===
Company Name:CLIFTON ADHESIVE INC
Address:BURGESS PL
City:WAYNE
State:NJ
ZIP:07470
Country:US
Info Phone Num:201-694-0845; 973-694-0845
Emergency P
hone Num:201-694-0845
Preparer's Name:ERNEST CARTER
Chemtre Ind/Phone:(800)424-9300
CAGE:79833

==== Contractor Identification ====
Company Name:CLIFTON ADHESIVE INC
Address:BURGESS PL
Box:City:WAYNE
State:NJ
ZIP:07470
Country:US
Phone:201-694-0845; 973-694-0845
CAGE:79833

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE
CAS:110-54-3
RTECS #:MN9275000
OSHA PEL:1800 MG/M3;500 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:STYRENE BUTADIENE RUBBER
CAS:900

3-56-9
Code:F
RTECS #:AT6970000

Ingred Name:NATURAL RUBBER
CAS:9006-04-6

Ingred Name:TERPINE PHENOL RESIN

===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:NAUSEA AND/OR NARCOSIS. MAY CAUSE
NERVE DAMAGE. HEXANE MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS OR
DAMAGE PERIPHERAL NERVE TISSUE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATIO
N TO EYES AND MUCOUS MEMBRANES. CAN
ALSO CAUSE SKIN DRYNESS: LIQUID INGESTION MAY RESULT IN VOMITING.
NUMBNESS, TINGLING AND WEAKNESS OF ARMS AND LEGS.
Medical Cond Aggravated by Exposure:RESPIRATORY ALIMENTS.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH EYES ABUNDENTLY
WITH CLEAN WATER AND REFER TO PHYSICIAN. INGESTION: DO NOT INDUCE
VOMITING.REFER TO PHYSICIAN. EXCESSIVE INHALATION: REMOVE PATIENT
TO FRES H AIR.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=-3.7C, 25.F
Autoignition Temp:=-265.6C, 510.F
Lower Limits:1.0
Upper Limits:7.5
Extinguishing Media:CO2, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING
APPARATUS SHOULD BE WORN.
Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL
CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASHBACK.

=====

=== Accidental Release Measures =====

Spill Release Procedures: ABSORB SPILL IN SAND, EARTH, VERMICULITE, OIL-DRI, OR SOL-SPEED-DRI, SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER AND COVER.

Neutralizing Agent: NONE

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN APPROVED SOLVENT STORAGE AREA. KEEP TIGHTLY CLOSED.

Other Precautions: NONE

===== Exposure Controls/Personal Protection =====

Re

spiratory Protection: USE NIOSH APPROVED ATMOSPHERE SUPPLYING OR AIR PURIFYING RESPIRATOR.

Ventilation: VENTILATION: LOCAL EXHAUST: Protective Gloves: PROTECTIVE GLOVES: PVA GLOVES.

Eye Protection: EYE PROTECTION: SAFETY GLASSES.

Other Protective Equipment: PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices: KEEP AREA CLEAN. CLEAN UP SPILLS IMMEDIATELY.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

Bo

iling Pt: =65.C, 149.F

Melt/Freeze Pt: M.P/F.P Text: NONE

Decomp Temp: Decomp Text: NONE

Vapor Pres: (MM HQ @ TEMP): Vapor Density: 3.0

Spec Gravity: 0.816

VOC Pounds/Gallon: 465

VOC Grams/Liter: 3.9

Appearance and Odor: AMBER, MILD HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE

Stability Condition to Avoid: AVOID HEAT, OPEN FLAMES, SPRKS, HOT SURFACES, AND OXIDIZING AGENTS.

Hazardous Decomposition Products: OXIDES OF

CARBON.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,
AND LOCAL CHEMICAL AND SOLVENT WASTE DISPOSAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:ADHESIVES, UN1133

===== Regulatory Information =====

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of
this information to their
particular situation.