View NSN Online: https://aerobasegroup.com/nsn/8030-01-118-4083

PRC-DESOTO INTL/FORMERLY COURTAULDS AEROSPACE -- POLYSULFIDE RUBBER COMPOUND

PR1725 B-1/2 1725B2 BASE COMPOUN -- 8030-01-118-4083

Product ID:POLYSULFIDE RUBBER COMPOUND PR1725 B-1/2 1725B2 BASE COMPOUN

MSDS Date:07/24/1998

FSC:8030

NIIN:01-118-4083 Status Code:A

MSDS Number: CLGDW === Responsible Party ===

Company Name: PRC-DESOTO INTL/FORMERLY COURTAULDS AEROSPA

CE

Address:5430 SAN FERNANDO RD

City:GLENDALE

State:CA ZIP:91203 Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

======= Composition/Information on Ingredients ========

Ing

red Name: PHENOLIC RESIN

CAS:028470-78-2

< Wt:5.

Ingred Name:TITANIUM DIOXIDE

CAS:013463-67-7

= Wt:5.

OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: CALCIUM CARBONATE LIMESTONE

CAS:001317-65-3

= Wt:30.

OSHA PEL:15.0 MG/M3 ACGIH TLV:10.0 MG/M3

Ingred Name:TOLUENE

CAS:000108-88-3

< Wt:5.

OSHA PEL:100 PPM 23

_____ LD50 LC50 Mixture:NONE Routes of Entry: Inhalation: UNKNOWN Skin: YES Ingestion: YES Health Hazards Acute and Chronic:EYES: IT MAY CAUSE IRRITATION, REDNESS AND TEARING. SKIN: ALLERGIC SKIN RASH IN SENSITIZED INDIVIDUALS. INGESTION: MAY CAUSE GASTROINTESTINAL IRRITATION. MAY CAUSE DISTURBANCE IN MEMORY, THINKING ABI LITY, EMOTIONS AND COORDINATION. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: EYES: MAY CAUSE BURNING, TEARING AND REDDENING. SKIN: EXPOSURE MAY CAUSE DRYING AND CRACKING OF SKIN, AND POSSIBLE DERMATITIS. INHALATION: MAY CAUSE DIZZINESS, DROWSINESS AND FATIGUE.MAY CAUSE LIVER A ND KIDNEY DAMAGE. INGESTION: MAY CAUSE DROWSINESS, DIZZINESS AND NAUSEA. Medical Cond Aggravated by Exposure: NONE First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: CONS ULT A PHYSICIAN. Flash Point Method:CALC Flash Point:>93.3C, 200.F Autoignition Temp: Autoignition Temp Text: NONE Lower Limits: NONE **Upper Limits:NONE** Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER. Fire Fighting Procedures: USE AIR SUPPLIED RESPIRATOR. Unusual Fire/Explosion Hazard: HIGH TEMPERATURE MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINER. ======== Accidental Release Measures ========= Spill Release Procedures: SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH A SUITABLE SOLVENT. Neutralizing Agent:NONE ============= Handling and Storage ==========================

Handling and Storage Precautions: WASH THOROUGHLY AFTER HANDLING AND BEFORE SMOKING OR EATING.

Other Precautions: EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:USE AN ORGANIC VAPOR CARTRIDGE OR AIR SUPPLIED RESP

Protective Gloves:SOLVENT RESISTANT GLOVES. Eye Protection:SAFETY GLASSES. Other Protective Equipment:KEEP CONTAINER TIGHTLY CLOSED. Work Hygienic Practices:NONE Supplemental Safety and Health NONE
========== Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:NONE Melt/Freeze Pt:M.P/F.P Text:NONE Decomp Temp:Decomp Text:NONE Vapor Density:HEAVIER Spec Gravity:1.6 VOC Pounds/Gallon:55 Appearance an d Odor:WHITE PASTE Percent Volatiles by Volume:5.0%
========= Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NONE Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE, TRACES OF HYDROGEN SULFIDE. Conditions to Avoid Polymerization:WILL NOT OCCUR.
======= Disposal Considerations ==========
Waste Disposal Methods:CONSULT STATE REGULATIONS PRIOR T O DISPOSAL OF SPILLAGE.
=========== Other Information ===============
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to veri

Ventilation: GENERAL VENTILATION TO MAINTAIN VAPORS BELOW TLV.

IRATOR.

fy and assume responsibility for the suitability of this information to their particular situation.