View NSN Online: https://aerobasegroup.kr/nsn/1430-00-740-3920

TECHNICAL COATINGS, INC -- 5959190, N-39 ACCELERATOR -- 1430-00-740-3920

Product ID:5959190, N-39 ACCELERATOR MSDS Date:08/02/1996 FSC:1430 NIIN:00-740-3920 Status Code:A Kit Part:Y MSDS Number: CLGGG === Responsible Party === Company Name: TECHNICAL COATINGS, INC Address:216 BOLIVAR ST Box:296 **City:CANTON** State:MA ZIP:02021 Country:US Info Phone Num:781-828-6050 Emergency Phone Num: (800) 424-9300 Resp. Party Other MSDS Num.:60119 Chemtrec Ind/Phone:(800)424-9300 CAGE:6Y305 === Contractor Identification === Company Name: TECHNICAL COATINGS, INC Address:216 BOLIVAR ST Box:296 **City:CANTON** State:MA ZIP:02021 Country:US Phone:781-828-6050 Contract Num:SP0920-99-M-1898 CAGE:6Y305

Ingred Name:XYLENE CAS:1330-20-7 RTECS #:ZE2100000 &It; Wt:34. OSHA PEL:100 PPM ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:651 MG/M3;150 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:LEAD OXIDE CAS:1317-36-8 RTECS #:OG1750000 &It; Wt:57. OSHA PEL:0.05 MG/M3 ACGIH TLV:0.05 MG/M3

Ingred Name:POLYBUTENE CAS:9003-29-6 RTECS #:EM9032000 &It; Wt:4.

Ingred Name: CONDENSATION BUTYRALDEHYDE & ANILINE

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: DRYNESS. INHALATION: IRRITATION TO MUCOUS MEMBRANES. INGESTION: LIQUID MAY

RESULT IN VOMITING. XYLENE BASED ON ANIMAL DATA MAY CAUSE ANEMIA, LIVER ABNORMALITIES, KIDNEY, EYE DA MAGE. IN HUMANS-CARDIAC ABNORMALITIES. LEAD MAY CAUSE EFFECTS OF BLOOD GASTROINTESTINAL, NERVOUS, REPRODUCTIVE SYSTEMS. CHRONIC: PROLONGED SKIN CONTACT MAY CAUSE IRRITATION. EXCESSIVE INGESTION MAY CA USE METALLIC TASTE, MUSCLE ACHES, ABDOMINAL PAINS, WEAKNESS. EXCESSIVE EXPOSURE TO LEAD MAY EFFECT CIRCULATORY, NERVOUS, DIGESTIVE SYSTEMS. DAMAGE TO KIDNEYS MAY OCCU

R WITHOUT SYMPTOMS. LEAD CAN CROSS THE PLECENTA, CAUSING BIRTH DEFECTS.

Effects of Overexposure:EYES: MAY CAUSE IRRITATION. SKIN: CAN CAUSE SKIN DRYNESS. INHALATION: MAYCAUSE IRRITATION TO MUCOUS MEMBRANES. SWALLOWING: LIQUID INGESTION MAY RESULT IN VOMITING. Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS.

First Aid:EYES: FLUSH ABUNDANTLY WITH CLEAN WATER AND REFER TO PHYSICIAN. SKIN: WASH WITH SOAP

AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR OR GIVE OXYGEN. USE CPR IF PATIENT IS NOT BREATHING. REFER TO PHYSICIAN. SWALLOWED: DO NOT INDUCE VOMITING. REFER TO PHYSICIAN.

Flash Point Method:TCC Flash Point:=26.7C, 80.F Lower Limits:1.0 Upper Limits:7.0 Extinguishing Media:CO2, FOAM, DRY CHEMICAL. Fire Fighting Procedures:NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING

APPARATUS SHOULD BE WORN. USE WATER SPRAY TO COOL FIRE EXPOSED STRUCTURES AND DISPERSE VAPOR CLOUD IF FIRE IS NOT PRESENT. Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASHBACK. MAY LIBERATE TOXIC (LEAD) FUMES WHEN BURNING. SENSITIVITY TO STATIC DISCHARGE: N/A. SENSITIVITY TO I MPACT: N/A.

Spill Release Procedures: ABSORB SPILL IN SAND, EARTH, VERMICULTIE, OIL-DRI, OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL

CONTAINER AND COVER.

Handling and Storage Precautions:STORE IN APPROVED SOLVENT STORAGE AREA. KEEP TIGHTLY CLOSED. KEEP AWAY FROM HEAT, OPEN FLAMES, SPARKS, HOT SURFACES, AND OXIDIZING AGENTS. Other Precautions:KEEP OUT OF REACH OF CHILDREN.

======= Exposure Controls/Personal Protection ==========

Respiratory Protect

ion:USE NIOSH-APPROVED ATMOSPHERE SUPPLYING OR AIR PURIFYING RESPIRATOR FOR ORGAINC VAPORS AS REQUIRED TO MAINTAIN EXPOSURE LEVELS BELOW RECOMMENDED LIMITS.
Ventilation:LOCAL EXHAUST: REMOVE VAPORS DURING PROCESSING. MECHANICAL EXHAUST: EXPLOSION PROOF EQUIPMENT. SPECIAL: REDUCE VAPOR CONCENTRATIONS BELOW LIMITS.
Protective Gloves:PVA GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:FULL PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.
Work Hygienic P HCC:F5 Boiling Pt:=138.3C, 281.F Vapor Density:3.7 Spec Gravity:1.705(H2O=1) VOC Pounds/Gallon:566 Appearance and Odor:OPAQUE DISPERSION, CHARACTERISTIC SOLVENT ODOR.

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID HEAT, OPEN FLAMES, SPARKS, HOT SURFACES, AND OXIDIZING AGENTS.
Hazardous Decomposition Products:OXIDES OF CARBON, LEAD, NITROGEN.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

====== Disposal C

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL CHEMICAL AND SOLVENT WASTE DISPOSAL REGULATIONS.

Transport Information:SHIPPING NAME:U.S. DOT: FLAMMABLE LIQUIDS, TOXIC, N.O.S.;3; UN 1992; PG I I I. IMDG: FLAMMABLE LIQUIDS, N.O.S.; 3; UN 1992. IATA: FLAMMABLE LIQUIDS, TOXIC N.O.S.; 3; UN 1992; PG I I I.

====== Regulatory Informatio

State Regulatory Information: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. PRODUCT CONTAINS LEAD.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied , warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.