

AMERICAN SAFETY TECHNOLOGIES INC -- NORCAST A-4000 PART B -- 8040-01-027-4900

=====
Product Identification
=====

Product ID:NORCAST A-4000 PART B
MSDS Date:12/14/1998
FSC:8040
NIIN:01-027-4900
Status Code:A
MSDS Number: CLGSV
=== Responsible Party ===
Company Name:AMERICAN SAFETY TECHNOLOGIES INC
Address:565 EAGLE ROCK AVE
City:ROSELAND
State:NJ
ZIP:07068
Country:US
Info Phone Num:973-403-2600
Em
ergency Phone Num:1-800-424-9300
Preparer's Name:ERNEST CARTER
Chemtrec Ind/Phone:(800)424-9300
CAGE:88444

=== Contractor Identification ===
Company Name:AMERICAN SAFETY TECHNOLOGIES INC
Address:565 EAGLE ROCK AVE
Box:City:ROSELAND
State:NJ
ZIP:07068
Country:US
Phone:973-403-2600
CAGE:88444

=====
Composition/Information on Ingredients
=====

Ingred Name:ORGANOSILANE ESTER
CAS:919-30-2
Code:F
RTECS #:TX2100000
Minimum % Wt:75.
Maximum % Wt:100.

=====
Hazards I
=====

dentification =====

Effects of Overexposure:IRRITANT TO SKIN, EYES AND RESPIRATORY TRACT.
PROLONGED BREATHING OF VAPORS CAN
CAUSE DIZZINESS, NAUSEA, AND HEADACHE. REPEATED CONTACT CAN CAUSE
DEFFATTING AND
DERMATITIS.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:INHALTION: REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT
SYMPTOMATICALLY. EYE
CONTACT: FLUSH WITH ALRGE VOLUMES OF WATER FOR AT LEA
ST 15 MINUTES.
TAKE TO A
PHYSICIAN FOR MEDICAL TREATMENT. SKIN CONTA CT: WASH AFFECTED AREA WITH
SOAP &
WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. INGESTION:
DRINK 1 OR 2
GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=82.2C, 180.F
Autoignition Temp:Autoignition Temp Text:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:DRY CHEMICAL, FOAM, OR CARBO
N DIOXIDE. WATER.
Fire Fighting Procedures:FIGHT AS VOLATILE LIQUID FIRE. USE WATER TO
KEEP FIRE-EXPOSED CONTAINERS COOL TO REDUCE PRESSURE.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT SPARKS AND OPEN
FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR
ABSORBENT, OR OTHER ABSORBENT MATERIAL
AND PICK UP WITH SHOVEL. ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES
INCLUDING
PILOT LIGHT

