

INTERNATIONAL LUBRICANTS -- LUBRICATING OIL COMPOUNDED GRADE 7 -- 9150-00-231-6646
===== Product Identification =====

Product ID:LUBRICATING OIL COMPOUNDED GRADE 7

MSDS Date:04/07/1998

FSC:9150

NIIN:00-231-6646

Status Code:A

MSDS Number: CLHVW

=== Responsible Party ===

Company Name:INTERNATIONAL LUBRICANTS

Address:10363 AIRLINE HIGHWAY

City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Info Phone Num:

504-469-0940

Emergency Phone Num:504-469-0940

CAGE:74898

=== Contractor Identification ===

Company Name:INTERNATIONAL LUBRICANTS

Address:10363 AIRLINE HIGHWAY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940

CAGE:74898

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic

:CHRONIC EFFECTS OF OVEREXPOSURE: NO DATA AVAILABLE.

Effects of Overexposure:CHRONIC EFFECTS OF OVEREXPOSURE: NO DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES AND CALL A PHYSICIAN. SKIN CONTACT: REMOVE EXCESS WITH CLOTH OR PAPER. WASH THOROUGHLY WITH SOAP AND WATER. INHALATION: RE MOVE VICTIM TO FRESH AIR. CALL A PHYSICIAN. IF SWALLOWED: CONTACT A PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:>200.C, 392.F
Extinguishing Media:DRY CHEMICAL, OR WATERFOG OR CO2 OR FOAM. CLOSED CONTAINERS EXPOSED TO FIRE MAY BE COOLED WITH WATER.
Fire Fighting Procedures:DO NOT USE WATER EXCEPT AS FOG.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:TRANSFER BULK OF MIXTURE INTO ANOTHER CONTAINER. ABSORB RESIDUE WITH AN INERT MATERIAL SUCH AS EARTH, SAND OR VERMICULITE. SWEEP UP AND DISPOSE AS SOLID WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT HANDLE OR STORE AT TEMPERATURES OVER 100 DEGREES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA CERTIFIED RESPIRATOR WITH ORGANIC VAP

OR CARTRIDGE IF VAPOR CONCENTRATION.

Ventilation:(LOCAL, MECHANICAL, SPECIAL): SEE COMMENTS SECTION.

Protective Gloves:NEOPRENE TYPE

Eye Protection:CHEMICAL SAFETY GOGGLES

Other Protective Equipment:NONE

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>330.C, 626.F

Vapor Pres:0

Vapor Density:NOT VOLATI

Spec Gravity:.89

Viscosity:GREATER THAN OR-TO 100

Evaporation Rate & Reference:0

Solubility in Water:0 AT 20C

Appearance

and Odor:VISCOUS LIQUID COLOR DARK GREEN, PUNGENT, SULFUR
TYPE ODOR.

===== Stability and Reactivity Data =====

Stability Condition to Avoid:PRODUCT IS STABLE UNDER NORMAL CONDITIONS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE LOCAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:NOT REGULATED.

===== Regulatory Information =====

State Regulatory Information:PENNSYLVANIA WORKERS AND COMMUNITY
RIGHT-TO-KNOW-ACT: THIS PRODUCT CONTAINS THE FOLLOWING
INGREDIENT(S): HYDROCARBON OILS, CAS# 820-83-5. THE ADDITIVE
MIXTURES IN THIS PRODUCT HAVE BEEN DECLARED A TR ADE SECRET BY THE
ADDITIVE MANUFACTURERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Departmen

t

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.