

ADVANCED CHEMISTRY & TECHNOLOGY -- AC-275 CLASS B BASE -- 8030-01-195-0655  
===== Product Identification =====

Product ID:AC-275 CLASS B BASE  
MSDS Date:05/06/1999  
FSC:8030  
NIIN:01-195-0655  
Status Code:A  
MSDS Number: CLKHW  
=== Responsible Party ===  
Company Name:ADVANCED CHEMISTRY & TECHNOLOGY  
Address:7341 ANACONDA AVE  
City:GARDEN GROVE  
State:CA  
ZIP:92841-2921  
Country:US  
Info Phone Num:714-373-2837  
Emergency Phone Num:(800)424-9300  
Preparer's Name:HENRY SIMMONS  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:1DWR5  
=== Contractor Identification ===  
Company Name:ADVANCED CHEMISTRY & TECHNOLOGY  
Address:7341 ANACONDA AVE  
Box:City:GARDEN GROVE  
State:CA  
ZIP:92841-2921  
Country:US  
Phone:714-373-2837  
CAGE:1DWR5

===== Composition/Information on Ingredients =====

Ingred Name:LIMESTONE  
CAS:1317-65-3  
RTECS #:EV9580000  
Minumum % Wt:30.  
Maxumum % Wt:40.  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ing

red Name:CALCIUM CARBONATE

CAS:471-34-1

RTECS #:FF9335000

Minumum % Wt:5.

Maxumum % Wt:10.

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Minumum % Wt:1.

Maxumum % Wt:5.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:FORMALDEHYDE

CAS:50-00-0

RTECS #:LP8925000

&lt; Wt:.1

OSHA PEL:SEE 1910.1048

ACGIH STEL:C0.37 MG/M3;C0.3 PPM

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES I

ngestion:NO

Health Hazards Acute and Chronic:LUNGS AND RESPIRATORY SYSTEM.

Effects of Overexposure:EYE CONTACT: MAY CAUSE MECHANICAL IRRITATION

SKIN CONTACT: INCIDENTAL CONTACT IS NOT EXPECTED INHALATION

(BREATHING): EXPOSURE IS UNLIKELY INGESTION (SWALLOWING): EXPOSURE

IS UNLIKELY, MAY CAUSE N AUSEA, VOMITING, PAIN, AND STOMACH UPSET

(E.G., DIARRHEA)

Medical Cond Aggravated by Exposure:LUNGS AND RESPIRATORY SYSTEM

=====  
===== First Aid Measures =====

=====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

SKIN CONTACT: IMMEDIATELY FLUSH WITH WATER. REMOVE CONTAMINATED CLOTHIN G AND SHOES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

PROFESSIONALLY WASH CLOTHING AND SHOES BEFORE RE-USE. INHALATION

(BREATHING): REMOVE TO FRESH AIR. IF SYMPTOMS DEVELOP, SEEK

IMMEDIATE MEDIC AL ATTENTION. IF NOT BREATHING, GIVE ARTIFICIAL

RE

SPARATION. INGESTION (SWALLOWING): SEEK MEDICAL ATTENTION:  
IMMEDIATELY INDUCE VOMITING, AS DIRECTED BY MEDICAL PERSONNEL.  
NEVER GIVE ANYTHING BY MOUT H TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>93.3C, 200.F

Extinguishing Media:SMALL FIRES: DRY CHEMICAL, CARBON DIOXIDE, HALON,  
WATER SPRAY, OR FOAM. LARGE FIRES: WATER SPRAY, FOG, OR ALCOHOL  
FOAM.

Fire Fighting Procedures:FIRE FIGHTERS AND OT  
HERS WHO MAY BE EXPOSED TO

THE PRODUCTS OF COMBUSTION SHOULD BE EQUIPPED WITH NIOSH-APPROVED  
POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS (SCBA) AND  
FULL PROTECTIVE CLOTHIN G.

Unusual Fire/Explosion Hazard:DURING A FIRE, IRRITATING AND HIGHLY  
TOXIC GASES MAY BE GENERATED DURING COMBUSTION OR DECOMPOSITION.

===== Accidental Release Measures =====

Spill Release Procedures:ISOLATE HAZARD AREA. KEEP UNNECESSARY AND  
UNPROTECTED PERSONNEL FROM  
ENTERING. SAFETY STOP DISCHARGE.

CONTAIN MATERIAL, AS NECESSARY, WITH A DIKE OR BARRIER. STOP  
MATERIAL FROM CONTAMINATING SOIL, OR FROM ENTERING SEWERS OF  
BODIES OF WATER. APPROPRIATE SAFETY MEASURES AND PROTECTIVE  
EQUIPMENT SHOULD BE USED. USE SUPPLIED AIR RESPIRATOR OF  
SELF-CONTAINED BREATHING APPARATUS IN ENCLOSED SPACES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED  
AREA AW

AY FROM HEAT, IGNITION SOURCES, AND DIRECT SUNLIGHT. KEEP  
CONTAINERS TIGHTLY CLOSES. TRANSFER- NO SPECIAL PRECAUTIONS ARE  
NEEDED. FOLLOW GOOD MANUFACTURING A ND HANDLING PRACTICES.

Other Precautions:THIS CONTAINER CAN BE HAZARDOUS WHEN EMPTY. FOLLOW  
LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED SINCE EMPTY  
CONTAINERS MAY RETAIN PRODUCT RESIDUES. DO NOT REUSE EMPTY  
CONTAINER WITHOUT PROFESSIONAL CLEANING FOR FOOD, CLOTHING, OR  
PRODUCTS FOR HUMAN OR ANIMAL CONSUMPTION OR

WHERE SKIN CONTACT CAN OCCUR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: AVOID BREATHING VAPOR OR MIST. WEAR NIOSH/MSHA-APPROVED EQUIPMENT. DETERMINE THE APPROPRIATE TYPE BY CONSULTING THE RESPIRATOR MANUFACTURER. HIGH AIRBORNE CONCENTRATION MAY NECESSITATE THE USE OF SELF-CONTAINED BREATHING APPARATUS (SCBA) OR A SUPPLIED AIR RESPIRATOR. RESPIRATORY PROTECTION PROGRAMS MUST BE IN COMPLIANCE WITH 29 CFR 1910.134

Ventilation: LOCAL EXHAUST VENTILATION WHEN VAPORS, MISTS, OR DUSTS CAN BE RELEASED IN EXCESS OF ESTABLISHED AIRBORNE EXPOSURE LIMITS (TLV'S OR PEL'S)

Protective Gloves: WEAR PROTECTIVE CLOTHING AND APPROPRIATE IMPERVIOUS GLOVES.

Eye Protection: WEAR CHEMICAL SPLASH GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING, DRINKING, SMOKING, AND USING RESTROOM FACILITIES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity: 1.61

Solubility in Water: INSOLUBLE

Appearance and Odor: OFF-WHITE PASTE AND SULFIDE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
OXIDIZERS, ACIDS

Stability Condition to Avoid: HIGH TEMPERATURES

Hazardous Decomposition Products: SMOKE, SOOT, AND TOXIC/IRRITATING FUMES (I.E., CARBON DIOXIDE, CARBON MONOXIDE, ETC). FORMALDEHYDE AND/OR OTHER ALDEHYDES. OXIDES OF SULFUR, HYDROGEN SULFIDE

===== Toxicological Information =====

Toxicological Information: LIMESTONE REPEATED EXPOSURE TO DUST CAN LEAD TO PARTICULATE IN THE LUNGS (I.E., PNEUMONIOSIS). CAN CONTAIN TRACE AMOUNTS OF CRYSTALLINE SILICA AS AN IMPURITY. CALCIUM CARBONATE: REPEATED EXPOSURE TO DUSTS CAN LEAD TO PARTICULATE IN THE LUNGS (I.E., PNEUMONIOSIS). TITANIUM DIOXIDE: IN A 2 YEAR STUDY, AN INCREASE IN BENIGN AND MALIGNANT LUNG TUMOR

S WERE OBSERVED AT  
250-MG/M3 RESPIRABLE DUST LEVEL. THIS LEVEL IS 50 TIMES THE  
CURRENT OCCUPATIONAL EXPOSURE LEVEL AND IS NOT EXPECTED TO  
CORRELATE TO HUMAN EXPOSURES. FORMALDEHYDE: SEVERELY IRRITATING  
TO THE EYES, SKIN, AND RESPIRATORY TRACT.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO APPLICABLE LOCAL, STATE  
AND FEDERAL REGULATIONS OF THE METHODS OF DISPOSAL CURRENTLY  
AVAILABLE, IT IS RECOMMENDED THAT AN ALTERNATIVE BE ACCORDING OR  
THE FOLLOWING ORDER OF PREFERENCE. BASED UPON ENVIRONMENTAL  
ACCEPTABILITY. (1) RECYCLE OR REWORK, IF FEASIBLE; (2) INCINERATE  
AT AN AUTHORIZED FACILITY.

===== Regulatory Information =====

SARA Title III Information:SECTION 311/312 HAZARD CATEGORIES-IMMEDIATE  
HEALTH HAZARD  
SARA SECTION 302 EXTREMELY HAZARDOUS MATERIAL FORMALDEHYDE SARA  
SECTION 313 TOXIC CHEMICALS FORMALDEHYDE  
Federal Regulatory Information:UNITED STATES CHEMICAL COMPONENTS THIS  
PRODUCT ARE ON THE SECTION 8(B) CHEMICAL SUBSTANCE INVENTORY LIST  
(40 CFR 710)  
State Regulatory Information:STATE RIGHT TO KNOW PENNSYLVANIA-NEW  
JERSEY R-T-K LIMESTONE 1317-65-3 80-90% CALCIUM CARBONATE  
474-34-1 5-10% TITANIUM DIOXIDE 13463-67-7 1.5% FORMALDEHYDE  
50-00-0