

FARWEST PAINT MANUFACTURING CO -- GLOSS LACQUER COLOR #13538 -- 8010-00-527-2624  
===== Product Identification =====

Product ID:GLOSS LACQUER COLOR #13538  
MSDS Date:02/17/1999  
FSC:8010  
NIIN:00-527-2624  
Status Code:A  
MSDS Number: CLLMS  
=== Responsible Party ===  
Company Name:FARWEST PAINT MANUFACTURING CO  
Address:4522 SOUTH 133RD ST  
City:TUKWILA  
State:WA  
ZIP:98168  
Country:US  
Info Phone Num:206-244-8  
844  
Emergency Phone Num:800-424-9300  
Preparer's Name:ERNEST CARTER  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:6F266

=== Contractor Identification ===  
Company Name:FARWEST PAINT MANUFACTURING CO  
Address:4522 SOUTH 133RD ST  
Box:City:TUKWILA  
State:WA  
ZIP:98168  
Country:US  
Phone:206-244-8844  
CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE  
CAS:110-19-0  
RTECS #:AI4025000  
= Wt:7.4  
OSHA PEL:700 MG/M3;150 PPM  
ACGIH TLV:713 MG/M3;150 PPM  
EPA Rpt Qty

:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE  
CAS:1330-20-7  
RTECS #:ZE2100000  
= Wt:13.3  
ACGIH TLV:434 MG/M3;100 PPM  
ACGIH STEL:651 MG/M3;150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE  
CAS:108-88-3  
RTECS #:XS5250000  
= Wt:19.3  
OSHA PEL:SEE TABLE Z-2  
ACGIH TLV:188 MG/M3;50 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE  
CAS:78-93-3  
RTECS #:EL6475000  
= Wt:9.2  
OSHA PEL:590 MG/M3;200 PPM  
ACGIH TLV:590 MG/M3;200 PPM  
ACGIH STEL:885 MG/M3;300 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE  
CAS:108-10-1  
RTECS #:SA9275000  
= Wt:4.8  
OSHA PEL:410 MG/M3;100 PPM  
ACGIH TLV:205 MG/M3;50 PPM  
ACGIH STEL:307 MG/M3;75 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL  
CAS:67-63-0  
RTECS #:NT8050000  
= Wt:6.3  
OSHA PEL:980 MG/M3;400 PPM  
ACGIH TLV:983 MG/M3;400 PPM  
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:MINERAL SPIRITS  
CAS:64742-89-8  
Code:F  
= Wt:9.9

===== Hazards Identific

ation =====

LD50 LC50 Mixture:NONE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:SKIN: THIS MATERIAL MAY CAUSE

IRRITATION, SENSITIZATION, DEFATTING UPON PROLONGED OR REPEATED CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MIST CAN RESULT IN HEADACHE, DIZZINESS, NAUSEA AND LOSS OF CONSCIOUSNESS. EYES: THIS MATERIAL MAY BE AN EYE IRRITANT.

Explanation

of Carcinogenicity:THIS PRODUCT CONTAINS NO KNOWN

CARCINOGENS IN REPORTABLE QUANTITIES AS DEFINED BY ACGIH, OSHA, NTP, IARC.

Effects of Overexposure:NONE

Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRCUTIONS.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES. SWALLOWING: DO NOT INDUCE VOMITING. KEEP PERSON WARM

AND QUIET AND GET MEDICAL ATTENTION.

ASPIRATION OF MAT ERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALATION: REMOVE VICTIM TO FRESH AIR IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:20 F.

Autoignition Temp:Autoignition Temp Text:NONE

Lower Limits:1.1

Upper Limits:NONE

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING; THOSE EXP  
POSED TO

VAPORS OR PRODUCTS OF COMBUSTION MUST WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE WHEN

EXPOSED TO EXTREME HEAT. VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN THE AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC.

===== Accidental Release Measures =====

Spill Release Procedures:PLACE MATERIAL INTO A CLOSED CONTAINER.

Neutralizing Agent:NONE

===== Handling and Storage =====

=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER TYPE RESPIRATOR.

Ventilation:GENERAL VENTILATION IS REQUIRED.

Protective Gloves:CHEMICAL RESISTANT NITRILE, NEOPRENE OR RUBBER GLOVES REQUIRED.

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

THE INFORMATION IN THIS DATA SHEET IS BELIEVED TO BE ACCURATE AND TRUE AT THE TIME OF PREPARATION OF THIS DOCUMENT. THIS IS NOT A WARRANTY OF PRODUCT OR PRODUCT SPECIFICATION. THE END-USER OF THIS PRODUCT IS ADVISED TO VERIFY IN ADVANCE THAT THE INFORMATION IN THIS SHEET IS CURRENT, APPLICABLE, AND SUITABLE.

===== Physical/Chemical Properties =====

Boiling

Pt:B.P. Text:160-340 F.

Melt/Freeze Pt:M.P/F.P Text:NONE

Decomp Temp:Decomp Text:NONE

Vapor Pres:70MMHG@20C

Vapor Density:HEAVIER

VOC Pounds/Gallon:692

VOC Grams/Liter:7.6

Evaporation Rate & Reference:FASTER THAN ETHER

Solubility in Water:NIL.

Appearance and Odor:CLEAR LIQUID, OR COLOR OF TINT.

Percent Volatiles by Volume:76.0%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES A

ND EPOXY HARDENERS

UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAME. AVOID CONTACT WITH STRONG OXIDANTS, ACIDS,

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL AGENCIES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.