

COURTAULDS AEROSPACE INC -- MANGANESE DIOXIDE DISPERSION PRO-SEAL B-1/2 0870B9 --  
8030-01-184-0329

===== Product Identification =====

Product ID:MANGANESE DIOXIDE DISPERSION PRO-SEAL B-1/2 0870B9

MSDS Date:10/21/1993

FSC:8030

NIIN:01-184-0329

Status Code:A

MSDS Number: CLLSH

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635

Preparer's Name:ERNEST CARTER

Chemtec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:HYDROGENATED TERPHENYL

CAS:061788-32-7

= Wt:3

0.  
OSHA PEL:0.5 PPM  
ACGIH TLV:0.5 PPM

Ingred Name:DIPHENYL GUANIDINE GUANIDINE, N, N, DIPHENYL  
CAS:000102-06-7  
&lt; Wt:5.

Ingred Name:MANGANESE DIOXIDE  
CAS:001313-13-9  
= Wt:50.  
OSHA PEL:5 CEILING MG/M3  
ACGIH TLV:5 AS MN MG/M3

Ingred Name:MAGNESIUM CHROMATE  
CAS:013423-61-5  
= Wt:10.

===== Hazards Identification =====

Effects of Overexposure:EYES: SEVERELY IRRITATING. SKIN: TOXIC BY SKIN  
ABSORPTION. INHALATION: MAY BE A SENSITIZATIZER. AIRBORNE MATERIAL  
MAY PRODUCE IRRITATION, AND MAY BE ABSORBED THROUGH THE THE LUNGS.  
INGESTION: TOXIC ON ORAL CONSUMPTION. BASED ON INCONCLUSIVE  
STUDIES, REPRODUCTIVE EFFECTS HAVE BEEN REPORTED.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. SKIN: WASH  
WITH SOAP AND WATER. INHALATION: REMOVE TO RFESH AIR. INGESTION:  
CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:CALC  
Flash Point:=93.3C, 200.F  
Autoignition Temp:Autoignition Temp Text:NONE  
Lower Limits:NONE  
Upper Limits:NONE  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER.  
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL  
HEAT EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE DECOMPOSITION OF  
MANGANESE DIOXIDE, RESULTING IN OXIDATION AND POSSIBLE IGNITION OF  
HYDROCARBON VEHICLE.

===== Accidental Rele

ase Measures =====

Spill Release Procedures:SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH A  
SUITABLE SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING AND  
BEFORE SMOKING OR EATING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE  
Ventilation:GENERAL VENTILATION.  
Protective Gloves:SOLVENT GLOVES.  
Eye Protection:SAFETY GLASSES.  
Suppleme  
ntal Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NONE  
Melt/Freeze Pt:M.P/F.P Text:NONE  
Decomp Temp:Decomp Text:NONE  
Spec Gravity:1.93  
Viscosity:1500 #7 @ 10 RPM  
Appearance and Odor:BLACK PASTE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
EASILY OXIDIZING MATERIALS.  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN.  
  
MANGANESE AND CHROMIUM COMPOUNDS.  
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this inform

ation to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.