

PRC-DESOTO INTL/FORMERLY COURTAULDS AEROSPACE -- 910K021 S.K.ACTIVATOR PWA 569G
-- 8010-01-076-6178

=====
===== Product Identification =====

Product ID:910K021 S.K.ACTIVATOR PWA 569G

MSDS Date:10/20/1995

FSC:8010

NIIN:01-076-6178

Status Code:A

MSDS Number: CLLXM

=== Responsible Party ===

Company Name:PRC-DESOTO INTL/FORMERLY COURTAULDS AEROSPACE

Address:5430 SAN FERNANDO RD

City:GLENDALE

State:CA

ZIP:9

1203

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====
===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL

CAS:67-63-0

RTECS #:NT8050000

=

Wt:30.
OSHA PEL:980 MG/M3;400 PPM
ACGIH TLV:983 MG/M3;400 PPM
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:METHYL ETHYL KETONE
CAS:78-93-3
RTECS #:EL6475000
= Wt:25.
OSHA PEL:590 MG/M3;200 PPM
ACGIH TLV:590 MG/M3;200 PPM
ACGIH STEL:885 MG/M3;300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE
CAS:1330-20-7
RTECS #:ZE2100000
= Wt:40.
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:651 MG/M3;150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:1,2-ETHYLENEDIAMINE
CAS:107-15-3
RTEC
S #:KH8575000
< Wt:1.
OSHA PEL:25 MG/M3;10 PPM
ACGIH TLV:25 MG/M3;10 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SILOXANES
< Wt:5.

Ingred Name:ORGANO SILANE ESTER
CAS:1760-24-3
Code:F
RTECS #:KV7400000
< Wt:5.

===== Hazards Identification =====

Effects of Overexposure:ISOPROPYL ALCOHOL EYES: IRRITANT. SKIN:
IRRITANT. INHALATION: MAY CAUSE NOSE AND THROAT IRRITATION. MAY
CAUSE FLUSHING, HEADACHE, DIZZINESS, MENTAL DEPRESSION, NA

USEA,
VOMITING, NARCOSIS ANETHESIA AND COMA. INGESTION: MAY CAUSE HEADACHE, DIZZINESS, MENTAL DEPRESSION, NAUSEA, VOMITING, NARCOSIS, ANESTHESIA AND COMA. MEK EYES: MAY CAUSE BURNING, TEARING AND REDDENING. POSSIBLE TRANSIENT CLOUDING. SK IN: PROLONGED EXPOSURE MAY CAUSE REDNESS, BURNING, DRYING AND CRACKING OF SKIN. INHALATION: MAY CAUSE COUGHING, CHEST PAINS. THROAT IRRITATION. MAY CAUSE HEADACHES AND DIZZINESS; MAY BE ANESTHETIC AND MAY CAUSE OTHER CENTRAL NE
RVOUS SYSTEM.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. DO NOT USE SOLVENTS. REOMVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. IF SYMPTOMS PE RSITS, GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR FROM EXPOSURE. GIVE ARTIFICIAL RESPIRATION OR CARDIOPULMONARY RESUSCITATION (CPR) IF BREATHING IS DIIFICULT, GET MEDIC
AL ATTENTION. INGEST ION: GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:=7.2C, 45.F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. COOL FIRE EXPOSED CONTAINERS WOTH WATER. FOG NOZZLES ARE PREFERRABLE. WEAR NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CON TACT WITH SKIN AND EYES.
Unusual Fire/
Explosion Hazard:VAPORS MAY ACCUMULATE INADEQUATELY VENTILATED OR CONFINED AREAS. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS MAY TRAVEL LONG DISTANCE MIXTURES WITH AIR. VAPORS MAY FORM EXPLOSIVE MIXTURES WIT H AIR. VAPORS MAY TRAVEL LONG DISTANCE . FLASHBACK OR FLAME TO THE BUILDING SITE MAY OCCUR.

=====
===== Accidental Release Measures =====

Spill Release Procedures:PROTECT FROM IGNITION. WEAR AIR-SUPPLIED RESPIRATOR FOR UNVENTILATED SPILL

. COVER WITH ABSORBENT MATERIAL
AND SCOOP INTO CONTAINER. CLEAN RESIDUE WITH A SUITABLE SOLVENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM HEAT, ELETRICAL EQUIPMENT, SPARKS AND FLAME. DO NOT STORE ABOVE 120 DEG F. EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM. VAPORS OF THIS PRODUCT ARE HEAVIER THAN AIR AND MAY COLLECT IN LOW OR CONFINED AREAS

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WHEN SPRAYING OR APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF LLV, USE AN ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW TLV AND PEL.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:GOGGLES OR FULL-FACE SHIELD.

Other Protective Equipment:AVOID SKIN CONTACT BY USE OF OTHER

PROTECTIVE CLOTHING. SAFETY SHOWER, EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Boiling Pt:>79.4C, 175.F

B.P. Text:175-292F

Vapor Density:>AIR

Spec Gravity:.837

VOC Pounds/Gallon:655

VOC Grams/Liter:6.97

Appearance and Odor:CLEAR LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:95.5%

=====
Stability and Reactivity Data
=====

Stability

Indicator/Materials to Avoid: YES

NONE RECOGNIZED UNLESS NOTED BELOW.

Stability Condition to Avoid: NONW RECOGNIZED UNLESS NOTED BELOW.

Hazardous Decomposition Products: PRODUCTS OF COMBUSTION ARE HAZARDOUS INCLUDING CARBON DIOXIDE AND CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: WHEN DISPOSING OF THIS MATERIAL. ENSURE THAT IT IS PACKAGED, STORED, TRANSPORTED AND OTHERWISE MANAGED IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.