

GRIGGS PAINT -- TT-P-19D TY.II AMD1 #34088 OD -- 8010-00-055-5183

===== Product Identification =====

Product ID:TT-P-19D TY.II AMD1 #34088 OD

MSDS Date:07/15/1998

FSC:8010

NIIN:00-055-5183

Status Code:A

MSDS Number: CLMVF

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:800-424-9

300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:58963

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL

CAS:107-21-1

RTECS #:KW2975000

< Wt:5.

ACGIH STEL:C127 MG/M3;C50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:MAGNESIUM SILICATE

CAS:14807-96-6

Code:F

RTECS #:WW2710000
< Wt:5.
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:2 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:DIRECT CONTACT TO EYES MAY CAUSE IRRITATION. PROLONGED AND/OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. INHALATION OF HIGH CONCENTRATIONS OF VAPORS MAY LEAD TO LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION, AND CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCES.
Effects of Overexposure:INHALATION: BREATHING OF HIGH VAPOR CONCENTRATIONS MAY CAUSE DROWSINESS, DIZZINESS, FATIGUE, FOLLOWED BY COMA. EYE: DIRECT CONTACT AND/OR CONTACT WITH VAPORS MAY CAUSE IRRITATION. SKIN: PROLONGED AND/ OR REPEATED CONTACT MAY CAUSE IRRITATION AND/OR DERMATITIS. INGESTION: ASPIRATION OF THIS PRODUCT INTO THE LUNGS MAY CAUSE PNEUMONITIS, PULMONARY EDEMA AND HEMORRAGE.
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKINCENTRAL NERVOUS SYSTEM, LIVER AND KIDNEY.

===== First Aid Measures =====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. SEEK MEDICAL AID. SKIN: WASH THOROUGHLY WITH SOAP AND WATER.SEEK MEDICAL AID IF IRRITATION PERSISTS. INGESTION: IMMEDIATELY SEEK MEDICAL AID. DO NOT INDUCE VOMITING. DO NOT ATTEMPT TO GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Lower Limits:3.2%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONEL. WATER MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE

FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA WITH WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE .

===== Handling and Storage =====

Handlin

g and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC.AVOID BREATHING OF VAPOR AND SPRAY MIST. AVOID SKIN AND EYE CONTACT.

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK OR PIT, WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW TLV(PEL), USE MSHA /NIOSH APPROVED UNITS. USE UNITS PER CURRENT 29 CFR 1910.134 FOLLOW MANUFACTURER'S INSTRUCTIONS AND WARNINGS. IF WITHIN OS HA PROTECTION FACTOR, AIR PURIFYING OV/FILTER UNITS OK FOR USE.

Ventilation:LOCAL AND MECHANICAL EXHAUST.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES.

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS WITHOUT ADEQUATE VENTILATION.

Supplemental Safety and Health

AS THE CONDITIONS OR METHODS ARE BEYOND OUR CONTROL, WE DO NOT ASSUME ANY RESPONSIBILITY REGARDING USE OF PRODUCT. WE EXPRESSLY DISCLAIM ANY LIABILITY FORANY USE OF THIS MATERIAL. INFORMATION CONTAIN ED HEREIN IS BELIEVED TO BE ACCURATE ALL STATEMENTS OR SUGGESTIONS ARE MADE WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED TO

===== Physical/Chemical Properties =====

Boiling Pt.=100.C, 212.F

Vapor Density:HEAVIER

Spec

Gravity:1.4
VOC Pounds/Gallon:101
VOC Grams/Liter:.85
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:ESSENTIALLY NIL
Appearance and Odor:VISCOUS LIQUID WITH TYPICAL PAINT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:FLAMES. SPARKS, SMOKING AND HEAT.
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:USE INERT MATERIALS ON SPILLS. DISPOSE OF IN
ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.